



MECHANICAL KEYNOTES: (O) 1 REFER TO DIFFUSER CONNECTION DETAIL 1/M501. 2 REFER TO TYPICAL LOW PRESSURE DUCT DETAIL 2/M501. 3 REFER TO DUCTWORK HANGERS DETAIL 3/M501. (ERV) 6/6 VA ¬ 4/6 EA J 6/6 EA J 4/6 VA ¬ - 4/6 VA - 6/6 EA \_ 8/8 EA r 4/10 SA SE MECHANICAL SECTION
SOLE: 1/4" = 1'-0" ARCHITECT/ENGINEER OF RECORD STAMP CONSULTANT Office of RENOVATE TOWER BUILDING 1 438-18-102 MECHANICAL SECTIONS **BID DOCUMENTS** FARRIS ENGINEERING
OWAM | INCOM | SENT | COORDO 99No.5
Inchi-upo com
CO-PTICAT FE #18208.3
This document and the information contained may not written perspison of forms forgineering. Inc. Unconformed copyring, disclassors or construction use are prohibited by the copyright less. Construction Bu**ll**ding Number Bild Documents
Contract Documents 100% Submittal (CD)
Contract Documents 95% Submittal (CD) and Facilities 05/14/2019 04/11/2019 04/11/2019 02/18/2019 12/10/2018 10/08/2018 Date; CLH Calvin L. Hinz Management Approved: Project Director Location Sioux Falls, SD 57105 Drawling Number Contract Documents 35% Submittal (CD)
Contract Documents 35% Submittal (CD)
Design Development (DD)
Schematic Design (SD)
Revisions: FULLY SPRINKLERED ssue Date Drawn LMB M301 FARRIS ENGINEERING U.S. Department of Veterans Affairs

05/30/2019

JDB





DEVICE TYPE ABBREVIATIONS: ALABH ACHOMEDOE RESET PUS-BUTTON
AUTOMATE CONTINC DAMPER
ANALYSS SEGOR AN CUSHY
ARE FLOW SHITCH
ARE FLOW SHITCH
ALABH HORN
ALABH HORN HEAV
ANALYSS COUTPUT
ANALOG OUTPUT
ANALOG A IND:
HAMIOSTAT/ARMOTY SENSOR
HAM COSTROL
HAM COSTROL
HAM SENSOR
HA H HC HOA HSP IA IFD IFFR IFPH IFPL IPSH IPSL INSTRUMENT WHE

LEVEL ALAM HED HOW

LEVEL ALAM HED HOW

LEVEL AND HED HOW

LEVEL WITCH-HOW

LEVEL CONTROL WALVEL

LEVEL WITCH-HOW

LEVEL CONTROL WALVEL

LEVEL C LAH LAHL LC LG LH LL LMP LMPG LMPW LP LMPW LP LS LSH BPSL BRO BSR BSS BSSV BSSVV COMBUSTION AIR FLOW LOW (NC CONTACT/OPEN AT NORMAL AIR FLOW) CONDUCTIVITY ELEWENT CO2 ELEMENT (SENSOR) CONTROL RELAY CONTROL VALVE CONTROL VALVE CAFL CE CO2E CR CV CW LSL CONTROL WRE
DAMPER ACTUATOR
DIGITAL REPUT
DIGITAL OFFER
DI LT LTPB LTR LV DA
DI
DO
DPAH
DPAL
DPC
DPE
DPI
DPSH
DPSL
DPY
DTC NORMALLY CLOSED NORMALLY OPEN NC NO NOMALY OFD:

PRESSARE ALAM
PARCE AR FLOW ON'T NOMAL AR FLOW
PALES ACCOUNT AND ROUTE
PRESSARE CANADA ON THE PALES
PRESSARE CANADA ON THE PALES
PRESSARE CANADA COW
PRESSARE CANADA COW
PRESSARE CANADA COW
PRESSARE CANADA COW
PRESSARE CANADA
PRESSARE CANADA PA PAFL PAI PB PC PCV PE PI PPSPB PPSR PRV PS PSPB PSPB ENERGY MANAGEMENT CONTROL SYSTEM EMERGENCY SHUTDOWN RELAY EMERGENCY STOP PUSHBUTTON EMERGENCY STOP RESET PUSHBUTTON EXPANSION TANK WATER LEVEL HIGH EXPANSION TANK WATER LEVEL LOW EMCS ESDR ESPB ESR ESRPB ETWLH ETWLL FORCED DRAFT FAN DAMPER CLOSED FORCED DRAFT FAN SELECTION SWITCH FORCED DRAFT FAN MOTOR STARTER RELAY FORCED DRAFT FAN VANES OPEN (LUNCES WITCH) PSL (JAMT SWITGH)

FLOW ELDBERT (SPINGOR)

FLUE GAS RECRECIATION CAMPER

FLOW INDCATES

FLOW INDUCTION

FLOW INDCATES

FLOW INDUCTION

FLOW INDCATES

FLOW INDUCTION

FLOW INDCATES

FLOW INDC PSR PT PUS RSV RELIEF SAFETY VALVE RESISTANCE TEMPERATURE DETECTOR PRESSURE RELIEF VALVE (LIQUID) REMOTE—OFF—AUTO SENSOR (TEMPERATURE) SMOKE DETECTOR SAFETY SHUT—OFF PRESSURE SAFETY VALVE (VAPOR) RTD RV ROA S SMK SSO SV THE STATE AND HE SHOW THE PROSENT FOR THE PROPERTY OF THE PROPERTY OF THE PROSENT FOR THE PROPERTY OF THE PROSENT FOR THE PROPERTY OF THE PROSENT FOR THE PROPERTY OF THE PROP FSL FT GENERATOR PRESSURE HIGH
GROUND
GAS SUPPLY PRESSURE LOW
GAS SUPPLY PRESSURE HIGH
GAS SHUTOFF VALVE
GENERATOR WATER FLOW LOW
GENERATOR WATER TEMPERATURE HIGH VFD VARIABLE FREQUENCY DRIVE VLV VALVE ZS LIMIT SWITCH XFMR TRANSFORMER

ABBREVIATIONS

CALC = CALCULATION RM = ROOM
TRND = TREND
COND = CONDENSER
EFFIC = EFFICIENCY PRESS = PRESSURE
TOTAL = TOTALIZATION
CD = CONTROL DAMPER AHU = AIR HANDLING L

TRAN = TRANSMITTER
CH = CHILLER
BILR = BOLLER
STM = STEAM
STM COND = STEAM CONDENSATE
ERV = ENERGY RECOVERY VENTILATOR

#### CONTROLS/INSTRUMENTATION SUPPLEMENTAL LEGEND

MISC. CONTROLS/INSTRUMENTATION SYMBOLS: RC RECEIVER CONTROLLER

MS MOTOR STARTER  $\Diamond$ SWITCH TERMINAL POINT ♦ INTERLOCK IA INSTRUMENT AR PRESSURE IN PSIG VARIABLE FREQUENCY DRIVE (R) RESET cs FCP FIRE CONTROL PANEL (NDICATING LIGHT: A-AMBER R-RED.
B-BLUE W-WHITE
G-GREEN INSTRUMENT/ MEASURING DEVICE: SIGNAL LINES: PI DENOTES LOCAL MOUNTED INSTRUMENT // // INSTRUMENT AIR SIGNAL LINE DENOTES LOCAL PANEL MOUNTED INSTRUMENT ----- ELECTRICAL SIGNAL OR CONTROL POWER ANALOG OUTPUT FROM CONTROLLER DENOTES REMOTE PANEL MOUNTED INSTRUMENT Al ----- ANALOG INPUT TO CONTROLLER DENOTES INSTRUMENT
MOUNTED BEHIND
LOCAL PANEL

DENOTES INSTRUMENT MOUNTED BEHIND REMOTE PANEL

DENOTES INSTRUMENT FOR TWO MEASURED VARIABLES OR MORE THAN ONE FUNCTION

O CONTROLLER

DI ----- DIGITAL INPUT TO CONTROLLER

#### INSTALLATION NOTES

- THE CONTROL SYSTEM MAIN CONTROL PANEL SHALL BE LOCATED AND INSTALLED BY JCI WITH OWNER'S REPRESENTATIVE.
- CONTROL POINTS IN AND AROUND THE MAIN BUILDING MECHANICAL ROOM SHALL BE TIED TO THE CONTROL SYSTEM DIRECTLY THROUGH THE MAIN CONTROL PANEL OR THROUGH THE USE OF APPLICATION SPOOF CONTROLLERS OR UNITARY CONTROLLERS. CONTROLLERS SHALL BE ACCESSIBLE TO OPERATOR AND MOUNTED WITHEN 72-INDESS FROM DEPENTING FLOOR, PLATFORM OF MEZZANIE.
- CONTROL OF EQUIPMENT, CONTROL DAMPERS, ETC., BY PROGRAMMABLE CONTROLLERS LOCATED IN THE MIGNITY OF THE EQUIPMENT AND NETWORKED TO THE MAIN CONTROLLER.

		CONSULTANT	ARCHITECT/ENGINEER OF REC	RD STAMP	Office of	Drawing Title MECHANICAL CONTROL	Phase BID DOCUMENTS	Project Title RENOVATE TOWER BUILDING 1	Project Number 438-18-102
Bild Documents Contract Documents 100% Submittal (CD)	05/30/2019 05/14/2019	FARRIS ENGINEERING		AECHAY DA	Construction and Facilities	DIAGRAMS	BID BOOOMEIVIO		Bu <b>l</b> lding Number
Contract Documents 95% Submittal (CD) Contract Documents 35% Submittal (CD)	04/11/2019 02/18/2019	formi-use.com COPYRIGHT FE #:182083	CLH Calvin L. Hinz	SZHREIER SE	Management	Approved: Project Director		Cocation Sigux Falls, SD 57105	Drawling Number
Design Development (DD) Schematic Design (SD) Revoktions	12/10/2018 10/08/2018 Date:	be reproduced or excerpted from without the express written permission of Forns Engineering, Inc. Unauthorized copying, disclosure or construction use are prohibited by the copyright law.	3705 North 200th Street Ethrom, Nebraska 88022 (402) 291-6941	G 053072019	U.S. Department		FULLY SPRINKLERED	Issue Date Checked Drawn 05/30/2019 JDB LMB	M601


(RELIEF AIR) SPACE PRESS ZONE) TEMP FROST ACT BO CABINET/UNIT HEATER CONTROL DIAGRAM (AO) EA ACT ERV CONTROL DIAGRAM NO SCALE TO FIRE ALARM CONTROL
PANEL (FACP)\* SD TO FIRE ALARM® & INITIATE PHASE 1 RECALL SPACE TEMPERATURE SENSOR ZONE STPT ZONE TEMP : ))) 2. SHOW DAMPER LOCATION AND SIZE ON THE DRAWINGS. SPACE HUMIDITY SENSOR 3. PROVIDE A BINARY DOC POINT TO SOUND AN ALARM AT ECC. REMOTE ALARM SHALL BE ACTIVATED WHEN THE HOISTWAY SMOKE DETECTOR DETECTS SMOKE. (A) HOISTWAY VENT DAMPER (HVD) CONTROLS
NO SCALE — BD —(AO) L FAN COIL CONTROL DIAGRAM
NO SCALE ARCHITECT/ENGINEER OF RECORD STAMP CONSULTANT Office of RENOVATE TOWER BUILDING 1 438-18-102 MECHANICAL CONTROL **BID DOCUMENTS** FARRIS ENGINEERING
OMMIN LINCON LINCO Construction Bu**ll**ding Number DIAGRAMS and Facilities 05/14/2019 04/11/2019 04/11/2019 02/18/2019 12/10/2018 10/08/2018 Date; CLH Calvin L. Hinz Contract Documents 95% Submittal (CD) Approved: Project Director Location Drawling Number Management Contract Documents 35% Submittal (CD)
Contract Documents 35% Submittal (CD)
Design Development (DD)
Schematic Design (SD)
Revisions: Sioux Falls, SD 57105 FULLY SPRINKLERED Drawn LMB Issue Date M602 FARRIS ENGINEERING U.S. Department of Veterans Affairs JDB 05/30/2019

FAN COIL - 2 FLOW - SYSTEM POINTS LIST CONTROLLER POINT TYPE ALARMS SYSTEM POINT DESCRIPTION POINT X X SUPPLY AIR TEMPERATURE LOCAL X
ONDENSATE OVERFLOW DETECTION LOCAL X
SUPPLY FAN STATUS X
SUPPLY FAN STATUS LOCAL X
SUPPLY FAN SPEED X
SUPPLY FAN START/STOP X MAINTENANCE REQUIRED COOLING VALVE X HEATING VALVE X 74.0 dea. 70.0 deg. 80.0 deg. F 65.0 deg. F 85.0 deg. F UNOCCUPIED COOLING SETPOI UNOCCUPIED HEATING SETPOIN 60.0 deg. F BE AIR TEMPERATURE CONTROL POINTS BAS COMMUNICATION STATE 600 HRS BINARY INPUT UNIVERSAL INPUT GENERAL NOTES

#### FAN COIL SEQUENCE OF OPERATION (PATIENT ROOMS)

FAN COLL UNITSUMLL OFFERTE ON A SCHEDULE AS SET BY THE ECC. FAN SMALL RIN CONTROLLSY, FAN STATUS SMALL BE MONTORED MO. AM ALARM MESSACE SMALL BE STEP OF THE STATUS SMALL BE MONTORED FOR THE STATUS SMALL BE MONTORED FOR THE STATUS SMALL BY MONTORED FOR THE SMALL SMALL BY MONTORED FOR THE SMALL SMALL BY MONTORED FOR THE SMALL SMALL BY MONTORED FOR SMALL FAN FOR THE SMALL SMALL BY MONTORED FOR THE SMALL BY MONTORED FOR THE

FAM DOS. SECRETE OF DEPARTOR LINEWASTER FROMES FOR SHALL RUN CONTINUOUSX FOR MY ORD SHALL OFFER TO A SHALL RUN CONTINUOUSX IN COURSE MY ORD SHALL BE UNSTRONED AND ATTEM MESSAGE SHALL BE MORBATED IN THE CHAPTH THE UNIT RES



SYSTEM/POINT DESCRIPTION	LABEL	DEVICE TYPE	QUANTITY	GRAPHIC DISPLAY	POINT TYPE	ALARM	TREND	SAMPLE RATE (S)
HOT WATER SYSTEM								
Hot Water System Enable	HW,ENA	Software Point (i.e. setpoint)	1	Y	SW			
Steam Control Valve	HX1V1-O	Actuator - Control Valve	1	Υ	AO	П	Х	
Hot Water Return Temperature	HX1EW-T	Sensor - Temperature (Hydronic)	1	Υ	AI	П	Х	120
Hot Water Supply Temperature	HX1LW-T	Sensor - Temperature (Hydronic)	1	Υ	AI	П	Х	120
Hot Water Supply Temp. Setpoint	HX1LW-T,STP	Software Point (i.e. setpoint)	1	Υ	SW			
Hot Water Pump Start/Stop	HWPx=S	Relay - Equipment Start/Stop	2	Υ	BO		Х	
Hot Water Pump Status	HWPx=C	Relay - Equipment Status (Current)	2	Υ	BI	Х	Х	COV
Hot Water Differential Pressure	HW-DP	Sensor - Pressure (Hydronic)	1	Υ	Al	П	Х	60
Hot Water Diff, Pressure Setpoint	HW-DP,STP	Software Point (I.e. setpoint)	1	Υ	SW			$\overline{}$

- IOTES:


  FIELD VERIFY EXACT QUANTITIES OF DEVICES

  , AN "X" UNDER THE LABEL COLUMN DENOTES AN INDIVIDUAL EQUIPMENT NUMBER

  BI-BINARY INPUT, BO-BINARY OUTPUT, AI -ANALOG INPUT

  AO-ANALOG CUTPUT, SW-SOFTWARE POINT, COY-CHANGE OF VALUE





STEAM TO HOT WATER SYSTEM CONTROL DIAGRAM AND SEQUENCE

#### HOT WATER UNIT HEATERS


- A. A WALL MOUNTED DDC SENSOR SHALL CYCLE UNIT FAN MOTOR AND MODULATE HOT WATER VALUE TO MAINTAIN ADJUSTABLE HEATING SETPONT. SETPONT ADJUSTMENT BY DDC SYSTEM ONLY. 1. PROVIDE SWITCH FOR SUMMER FAN OPERATION.



#### ELECTRIC CABINET UNIT HEATER

A WALL MOUNTED DDC SENSOR SHALL CYCLE ON THE FAN AND HEATER TO MAINTAIN SETPOINT.





#### SEQUENCE OF OPERATION

SYSTEM ENABLE
THE HEATING SYSTEM WILL AUTOMATICALLY START WHEN THE SYSTEM ENABLE IS
MANUALLY TURNED "ON". WHEN THE SYSTEM ENABLE IS "OFF", THE HEATING
SYSTEM WILL BE DISABLED.

HEAT EXCHANGER CONTROL. THE STEAM INLET VALVE WILL MODULATE TO MAINTAIN THE DESIRED HOT WATER SUPPLY
TEMPERATURE SETPOINT. THE HOT WATER TEMPERATURE SETPOINT WILL BE
RESET BY THE OUTDOOR AIR TEMPERATURE.

SEASON LOOP PAYENGS
WHICH THE RESTAURT OF STEM IS EMABLED, THE PUMP WITH THE LOWEST RUNTIME
WILL BE STARTED. THIS LEAD PUMP WILL MODULATE TO MANTAN THE
PRESSURE SETORY (AD). IF THE LEAD PAMP ON NOT MANTAN THE
PRESSURE SETORY (AD).

THE SEASON WAS THE STANDARD OF THE STA

#### SEQUENCE OF OPERATIONS

BULDING AUTOMATION SYSTEM INTERFACE:
THE BULDING AUTOMATION SYSTEM (BAS) WILL SEND THE CONTROLLER OCCUPIED BYPASS, MORNING WARM-UP /
PRE-COOL, OCCUPIED / UNDOCCUPIED MOR HEAT / COOL MODES. IF A BAS IS NOT PRESENT, OR COMMUNICATION IS
LOST WITH THE BAS THE CONTROLLER WILL OPERATE USING DEVALUAT MODES AND SETPOINTS.

OCCUPIED MODE: DURN'S OCCUPIED PERIODS THE SUPPLY FAN WILL RUN CONTINUOUSLY. THE CHILLED WATER AND HOT WATER VALVE WILL MODULATE TO MAINTAIN THE ACTIVE SPACE TEMPERATURE SEPPOINT.

MINISTERS MINISTERS AND THE INCOMPED HARMS SETTORS OF MO. 06. F (AD.). THE SUPPLY WITH THE PROPERTY OF MO. 06. F (AD.). THE SUPPLY WITH THE PROPERTY OF MO. 06. F (AD.). THE SUPPLY WITH THE PROPERTY OF MO. 06. F (AD.). THE THE UNCOMPED PRITTERS OF MO. 16. F (AD.). THE THE UNCOMPED PRITTERS OF MO. 16. F (AD.). THE PROPERTY OF MINISTERS OF THE UNCOMPED PRITTERS OF MO. 16. F (AD.). THE PROPERTY OF MINISTERS OF THE UNCOMPED PROPERTY OF MINISTERS OF THE ORIGINATION OF MINISTERS OF THE PROPERTY OF THE PROPERTY OF MINISTERS OF THE ORIGINATION OF MINISTERS OF THE PROPERTY OF THE PROPER

OPTIMAL START:
THE BAS WILL MONITOR THE SCHEDULED OCCUPIED TIME, OCCUPIED SPACE SETPOINTS AND SPACE TEMPERATURE TO
CALCULATE WHEN THE OPTIMAL START OCCUPS.

MORNING WARM-UP MODE:

DURING OFFINAL START, IF HE SPACE TEMPERATURE IS BELOW THE OCCUPIED HEATING SETPOINT A MORNING WARM-UP MODE WILL BE ACTIVATED. WHEN MORNING WARM-UP IS INITIATED THE UNIT WILL DEMBLE, THE HEATING AND SUPPLY MODE WILL BE ACTIVATED. WHEN THE SPACE TEMPERATURE REACHES THE OCCUPIED LESTING SETPOINT (AUD.), THE UNIT WILL TRANSITION THE MORNING WARM-UP AND ADMINISTRATION OF THE OCCUPIED LESTING SETPOINT (AUD.), THE UNIT WILL TRANSITION TO ADMINISTRATION OF THE OCCUPIED LESTING SETPOINT (AUD.), THE UNIT WILL TRANSITION TO ADMINISTRATION OF THE OCCUPIED LESTING SETPOINT (AUD.), THE UNIT WILL TRANSITION TO ADMINISTRATION OF THE OCCUPIED LESTING SETPOINT (AUD.), THE UNIT WILL TRANSITION TO ADMINISTRATION OF THE OCCUPIED LESTING SETPOINT (AUD.), THE UNIT WILL TRANSITION TO ADMINISTRATION OF THE OCCUPIED LESTING SETPOINT (AUD.), THE UNIT WILL TRANSITION TO ADMINISTRATION OF THE OCCUPIED LESTING SETPOINT (AUD.), THE UNIT WARM ADMINISTRATION OF THE OCCUPIED LESTING SETPOINT (AUD.), THE UNIT WARM ADMINISTRATION OF THE OCCUPIED LESTING SETPOINT (AUD.), THE UNIT WILL TRANSITION TO ADMINISTRATION OF THE OCCUPIED LESTING SETPOINT (AUD.), THE UNIT WARM ADMINISTRATION OF THE OCCUPIED LESTING SETPOINT (AUD.), THE UNIT WARM ADMINISTRATION OF THE OCCUPIED LESTING SETPOINT (AUD.), THE OCCUPIED LESTING SETP PRE-COOL, MODE:
DURING OFFINIAL START, IF THE SPACE TEMPERATURE IS ABOVE THE OCCUPIED COOLING SETPOINT, PRE-COOL MODE
WILL BE ACTIVATED, WHEN PRE-COOL IS INITIATED THE UNIT WILL ENABLE THE FAN AND COOLING, WHEN THE SPACE
VICULENTIAL PERFARSE OF ONLY THE COOLINES METEORY (AGAIL). THE UNIT WILL TRANSITION TO THE OCCUPIED MODE

OFTIMAL STOP.

THE BAS WILL MONITOR THE SCHEDULED UNOCCUPIED TIME, OCCUPIED SETPOINTS AND SPACE TEMPERATURE TO CALCULATE WHEN THE OPTIMAL STOP OCCURS, WHEN THE OPTIMAL STOP MODE IS ACTIVE THE UNIT CONTROLLER WILL WILL STOP WIL OCCUPED BYPASS.
THE BAS WILL MONITOR THE STATUS OF THE "ON" AND "CANCEL" BUTTONS OF THE SPACE TEMPERATURE SENSOR, WHEN AN OCCUPED BYPASS REQUEST IS RECEIVED TROM A SPACE SENSOR. THE UNIT WILL TRANSFIRM FROM TO THE OCCUPENCE SENSOR WHO AND THE SPACE TEMPERATURE TO THE OCCUPENCE SENSOR WHO AND THE WISH MILL MARKEN THE SPACE TEMPERATURE TO THE OCCUPENCE SENSOR WHO AND THE WISH MILL MARKEN THE SPACE TEMPERATURE TO THE OCCUPENCE SENSOR WHO AND THE OFFICE SENSOR SENSOR WHO AND THE SPACE TEMPERATURE TO THE OCCUPENCE SENSOR WHO AND THE OCCU

CONDENSATE OVERFLOW MONITORING:
IF THE CONDENSATE LEVEL REACHES THE TRIP POINT, A CONDENSATE OVERFLOW DIAGNOSTIC WILL BE ANNUNCIATED AT
THE BBS. TO PREVENT THE CONDENSATE DRAIN PAIN FROM OVERFLOWING AND CAUSING WATER DAMAGE TO THE BUILDING.
THE FAS WILL BE INSURIED AND THE CHILLED WATER VALVE WILL CLOSE.

FILTER TMEER: THE FAME (HRS) WILL BE COMPARED TO THE FILTER MAINTENANCE TIMER SETPONT, ONCE THE SETPONT IS REACHED A FILTER TMEER ALARM DIGNOSTIC WILL BE ANNINCATED AT THE BAS, WHEN THE DIGNOSTIC IS CLEARED, AND THE TIMER BASS WHEN THE DIGNOSTIC IS CLEARED, AND THE TIMER BEGINS ACCUULATING FAM-FUND TIME AGAIN.

#### **ENERGY RECOVERY VENTILATOR**

- A FNERGY RECOVERY VENTILATOR:
  - REGIST RECOVERT VENTILLATUR:

    GENERAL: ENERGY RECOVERY VENTILLATOR CONTROLS ARE DEFINED IN SECTION 23

    7200. BMS CONTRACTOR SHALL INSTALL ALL DEVICES NOT FACTORY INSTALLED.

    ALL REQUIRED CONTROL DEVICES NOT FURNISHED UNDER SECTION 23

    7200 SHALL

    BE FURNISHED UNDER THIS SECTION.
- BE FURNISHED UNDER THIS SECTION.

  2 UNIT SHALL PROVIDE ROOM NEUTRAL AIR WITH 55 DEG F LEAVING AIR TEMPERATURE AT THE DIRECT EXPANSION (DX) COLL AND 70 DEG F LEAVING AIR TEMPERATURE AT THE HOT-GAS REHEAT COLL IN COOLING MODE.

  AS REQUIRED. IN HEATING MODE, THE HOT WATER HEATING COLL SHALL MODULATE AS REQUIRED. THE HOT WATER HEATING COLL SHALL MODULATE AS REQUIRED ON MAINTAIN ADJUSTABLE DISCHARGE AIR SET POINT. THE MAXIMUM RELATIVE HUMDITY OF THE SUPPLY AIR SHALL BE 50% (ADJUSTABLE) DISCHARGE AIR SET POINT. THE COOLED WINDERS FOR SHALL BE 50% (ADJUSTABLE) DISCHARGE AIR SET POINT.

  3. AIR—COOLED WINDERSEE FOR SHALL BE FANDEZE TO MAINTAIN COMPRESSOR HEAD

  3. AIR—COOLED WINDERSEE FOR SHALL BE FERDINGED TO TENANGE FANDE THROUGH THE SHALL BE 50% SHALL SHA

- PRESSURE WITHIN MANUFACTURER'S RECOMMENDATIONS.

  SEVEN-DAY PROGRAMMING SHALL BE PROVIDED TO ENABLE FANS THROUGH THE BUILDING DDC SYSTEM ACCORDING TO OWNER'S SCHEDULE.

  OCCUPIED OPERATION: ENV FANS SHALL BE ENABLED TO OPERATE CONTINUOUSLY, AND COMPRESSORS, HEATING COILS AND REHEAT COILS SHALL BE STAGED TO MAINTAIN OCCUPIED COLONIC OR HEATING SET POINT AS INDICATED BY BMS DISCHARGE, ARR SENSOR. THE OUTSIDE AR DAMPER AND EXHAUST DAMPER FALL OPER DURING OCCUPIED PERIODS.
- EMHAUST DAMPER SHALL OPEN DURING OCCUPIED PERIODS.

  BUNCOUPIED OPERATION: ENY FANS SHALL CYCLE, AND COMPRESSORS, HEATING COILS AND REHEAT COILS SHALL BE STACED TO MANTIAN NUCCOUPIED COOLING OF HEATING SET FONT AS INDICATED BY BMS DISCHARGE ARE SENSOR. THE OUTSIDE ARE DAMPER AND EXHAUST DAMPER SHALL REMAIN CLUSSED DURING UNCCUPIED PERIODS.

  SHALL REMAIN CLUSSED DURING UNCCUPIED PERIODS.

  NOT START UNTIL THE EMPERATURE IS BELOW 35 DEEP, THE SUPPLY FAN SHALL NOT START UNTIL THE EMHAUST FAN HAS OPERATED FOR 5 MINUTES
- (AUUSI MMEE).

  A WHEN THE EAV UNIT IS OPERATING IN AN OUTSIDE AIR COLUMN MODE. THE HEAT RECOVERY WHEEL SHALL ROTATE AS LONG AS THE OUTSIDE AIR ENTHALPY IS HIGHER THAN THE EXHAUST/RELIEF ENTHALPY, IF OUTSIDE AIR ENTHALPY IS EQUAL OR LOWER THAN THE EXHAUST/RELIEF AIR ENTHALPY, THE WHEEL SHALL NOT ROTATE.
- NOT ROTATE.

  WHEN THE ERV UNIT IS OPERATING IN AN OUTSIDE AIR HEATING MODE, THE HEAT RECOVERY WHEEL SHALL ROTATE AS LONG AS THE OUTSIDE AIR TEMPERATURE IS COMES THAN THE EDMALSTRELEF AIR TEMPERATURE. IF OUTSIDE AIR THE WIREL SHALL NOT ROTATE.


  A FACTORY-INSTALLED FROST PROTECTION SYSTEM SHALL BE ENABLED WHEN EXHAUST AIR TEMPERATURE FALLS BELOW 35 DEG F. AN ALARM SHALL ACTIVATE IF EXHAUST AIR TEMPERATURE FALLS BELOW 35 DEG F. AN ALARM SHALL ACTIVATE IF EXHAUST AIR TEMPERATURE FALLS BELOW 35 DEG F. AN ALARM SHALL ACTIVATE IF EXHAUST AIR TEMPERATURE FALLS BELOW 35 DEG F. AN ALARM SHALL ACTIVATE IF EXHAUST AIR TEMPERATURE FALLS BELOW 35 DEG F. AN ALARM SHALL ACTIVATE
- 9. INTERLOCK CONTROLS:
- INITERLOCK CUNINCLS:

  OUTSIDE DAMPER SHALL BE FULLY OPEN BEFORE SUPPLY FAN WILL START.

  B. EXHAUST/RELIEF DAMPER SHALL BE FULLY OPEN BEFORE EXHAUST/RELIEF FAN WILL START.

  C. DIRTY FILTER SWITCH: PROVIDE PRESSURE SWITCH TO INDICATE DIRTY FILTER
  AT EACH UNIT

		CONSULTANT	ARCHITECT/ENG	INEER OF RECORD	STAMP	Office of	Drawing Title MECHANICAL CONTROL	Phase BID DOCUMENTS	Project Title RENOVATE TOV	WER BUILDI	NG 1	Project Number 438-18-102
Bild Documents Contract Documents 100% Submittal (CD)	05/30/2019 05/14/2019	FARRIS ENGINEERING	67.77		THE CHANGE OF TH	Construction and Facilities	DIAGRAMS	BID DOGGINEIVIO				Bu <b>ll</b> ding Number
Contract Documents 95% Submittal (CD) Contract Documents 35% Submittal (CD)	04/11/2019 02/18/2019	Serie-secom  COPYRIGHT This document and the information contained may not	CLH Calvin L. Hinz 3705 North 200th Street Elstrom, Nabraska 68022		SIZHREIER SE E-4552 SIZ	Management	Approved: Project Director		Location Sioux Falls, SD 5	57105		Drawling Number
Design Development (DD) Schematic Design (SD) Revisions:	12/10/2018 10/08/2018 Date:	be reproduced or excerpted from without the express written permission of Fornis Engineering, Inc. Unauthorized copying, disclosure or construction use are prohibited by the copyright law.	3705 North 200th Street Elkhorn, Nebraska 68022 (402) 291-8941	FARRIS ENGINEERING	05/30/2019	U.S. Department of Veterans Affairs		FULLY SPRINKLERED	Issue Date 05/30/2019		Drawn LMB	M603



### CHILLED WATER PUMPING SYSTEM - CONTROL DIAGRAM

#### FIRE ALARM SHUTDOWN OF FIRE/SMOKE DAMPERS AND ENERGY RECOVERY UNIT - CONTROL SEQUENCE

THE SEQUENCE OF OPERATION SHALL BE SUCH THAT, WHEN THE FIRE ALARM SYSTEM IS ACTIVATED, FIRE ALARM RELAY(S) THROUGH ITS AUXILIARY CONTACTS SHALL CLOSE THE FIRE/SMOKE DAMPERS AND SHUT DOWN THE ENERGY RELAY(S) THROU-RECOVERY UNIT.

WHEN THE FIRE ALARM SYSTEM IS RESET TO NORMAL OPERATION, THE FIRE/SMOKE DAMPERS SHALL RETURN TO OPEN POSITION AND THE ENERGY RECOVERY UNIT SHALL RESTART.

COORDINATE ALL INSTALLATION OF FIRE ALARM SHUTDOWN CONTROLS WITH THE ELECTRICAL CONTRACTOR.

#### CHILLED WATER SYSTEM - CONTROL SEQUENCE

CHILLED WATER PUMP CONTROL: THE MOTOR STARTERS FOR THE CHILLED WATER PUMP'S SHALL BE CONTROLLED BY THE DDC CONTROL SYSTEM. PROVIDE A START/STOP DIGITAL OUT (DO) CONTROL POINT, AND A STATUS ALARM FOR EACH PUMP.

HAND-OFF-AUTO: WHEN THE SWITCH ON THE STARTER IS IN THE "OFF" POSITION, THE PUMP SHALL BE SHUT OFF. WHEN THE SWITCH IS IN THE "AUTO" POSITION, THE PUMP SHALL OPERATE AS DIRECTED BY THE DDC

CHILLED WATER PUMPS SHALL BE INTERLOCKED WITH

LOSS OF POWER: UPON LOSS OF POWER, THE CHILLER AND ASSOCIATED CHILLED WATER PUMPS SHALL SHUT DOWN, AND AN ALARM CONDITION SHALL ACTIVATION OF POWER, OPERATORS WILL MANUALLY RESTART CHILLED WATER FUNDERS AND CHILLER FROM DC FROMT-CHO. THE CHILLED WATER STYREM IS NOT CONNECTED TO THE EMBREROKY POWER SYSTEM.

PROVIDE THREE—WAY VALVES TO MAINTAIN CONSTANT FLOW THROUGH THE ENTIRE LOOP.

CHILER CONTROLS. PROVIDE A BUILDING MANAGEMENT SYSTEM INTERFACE CARD FOR THE CHILLER THAT MUSTOR THE CHILLER THAT MAN THE PROVIDE OF THE CHILLER THAT MAN THE CONTROLLER THE ABILTY FOR MAN THE CONTROLLER THE ABILTY FOR MAN THE CONTROLLER THE ABILTY TO MINIOR THE PROVIDE THE ABILTY TO MINIOR THE TAY THE ABILTY TO MINIOR THE SYSTEM ALARM CONDITIONS WITHIN THE CHILLER CONTROLLER.

CHILLER WATER TEMPERATURE RESET SHALL BE PROVIDED BASED ON THE RETURN WATER TEMPERATURE. PROVIDE A STOP/START (DO) CONTROL POINT FOR THE CHILLER.

WHEN THE OUTSIDE AMBIENT TEMPERATURE EXCEEDS 55 (ADJUSTABLE) DEG F THE DOC CONTROLLER SHALL SEND START SKANL DO COLLEGE. THE DOC CONTROLLER MS START SKANL DE COLLEGE MS THE DOC CONTROLLER MS BEEN PROVEN THROUGH THE FLOW SWITCH, THE CHILLER CONTROLLER SHALL START THE COMPRESSOR. THE DOC CONTROLLER SHALL SHALT THE THE CHERATION OF THE CHILLER WATER PUMPS ON A WEEKLY BASIS.

THE CHILLER CONTROLLER SHALL MAINTAIN LEAVING CHILLED WATER TEMPERATURE OF 42 DEG F, AND ACTIVATE THE REQUIRED NUMBER OF COMPRESSORS TO MEET CHILLED WATER SET—POINT.

FLOW SWITCH: CONTRACTOR SHALL FIELD MOUNT AND WIRE CHILLED WATER FLOW SWITCH TO THE CHILLER.

# HARDWARE SOFTWARE HILLED WATER SYSTEM COUPANCY TIME CHILLED WATER PUMP CHILLED WATER SUPPLY CHILLED WATER RETURN

#### SUMP PUMP -SP-1, SP-2, SP-3 CONTROL SEQUENCE

SP-1, SP-2, SP-3 LOCATED IN PIT. PROVIDE A STATUS ALARM POINT TO SEND A SIGNAL TO THE DDC CONTROLLER WHEN THE HIGH WATER ALARM CONDITION OCCURS. PROVIDE A WATER LEVEL SENSOR IN EACH SLIMP PLIMP RASIN TO SIGNAL THAT A PLIMP FAILURE HAS OCCURRED DUE TO THE WATER LEVEL EXCEEDING A

#### CHILLED WATER PUMPING SYSTEM -CONTROL SEQUENCE

PROVIDE VARIABLE FREQUENCY DRIVES (VFD) FOR THE PUMPS. 4-20MA SIGNALS, AND VFD STATUS/ALARMS. PROVIDE A DIFFERENTIAL PRESSURE SENSOR FOR CONTROLLING THE VFD'S. PROVIDE CHILLED WATER TEMPERATURE SENSORS FOR THE CHILLED WATER LOOP.

## VARIABLE REFRIGERANT SYSTEM

DUCTLESS SPLIT SYSTEM UNIT


A UNIT SHALL BE FURNISHED WITH MANUFACTURER'S INSTALLED CONTROL PACKAGE AND A REMOTE CONTROLLER. THE CONTROLLER SHALL BE CAPABLE OF MONTORING AND SETTING DESIRED ROOM TREMPERATURE, TEMPERATURE SETPOINT, FAN ON/OFF SPEED CONTROL AND NIGHT SETBACK CONTROL.

DEC SENSOR IN ROOM SHALL MONITOR SPACE TEMPERATURE. PROVIDE AN ALARM AT THE FRONT END IF ROOM TEMPERATURE IS OUT OF RANGE (COORDINATE WITH OWNER ON ACCEPTABLE TEMPERATURE RANGES).

BUILDING NO.

#### A. VARIABLE REFRIGERANT SYSTEM:

- I. YAMABLE REPRIGERANT SYSTEM SHALL BE PROVIDED WITH FACTORY MOUNTED CONTROLS EXCLUDING THE WALL THEMMOSTAT PROVIDED BY THE TEMPERATURE CONTROL CONTRACTOR. THE WALL THEMMOSTAT SHALL CONTRACTOR. THE WALL THEMMOSTAT SHALL FALLE THE WALL THEMMOSTAT SHALL FALLE THE WALL THEMMOSTAT WILL CONTROL THE SEQUENCE AND OCCUPIED/UNOCCUPIED SET POINTS. THE FACTORY AND FIELD MOUNTED CONTROLS SHALL COMMUNICATE VIA BACKET MSTP TO THE BUILDING WEB BASED BUILDING MANAGEMENT SYSTEM.
- OCCUPIED OPERATION: FAN SHALL RUN CONTINUOUSLY ON A CALL FOR HEATING OR COOLING, THE HEAT PUMP UNIT SHALL CYCLE.
- 3. UNOCCUPIED OPERATION: FAN SHALL CYCLE ON A CALL FOR HEATING OR COOLING, THE FAN SHALL CYCLE ALONG WITH THE HEAT PUMP UNIT.



BUILDING NO.								н	٩R	D١	VΑ	RI	Ε															S	OF	T۷	VΑ	RE	:								
				out	PU	Т		Т					-16	PU	r							Al	AR	ws			П				400			-	RO	001				_	-
		D)	SIT	AL.	Т	ANA	LO	3		DIG	ITAI	L	Т		Α	NAL	.OG				DIG	TAL		A)	<b>L</b> AL	OG	1_				477	LIG	VIII.	M I	·NOI	310	(NO				
SYSTEM(S)	Т	Т	П	Т	Т	Т	П	Т	Т	Т	П	П	Т	Т	П	П	Т	Т	П	П	Т	Т	П	Т	Т	Т	П	Т	Т	Т	Г	П	Т	Т	П	П	Т	Т	П	П	1
MISCELLANEOUS			ш		н		ш		١.	ı	ш	- 1	Į.		ш	ш		П	Ш	ш	П	П	Ш		П	П	ш		П			Ш	П		1.7	н			П	Ш	
			ш		н		ш		Ιĝ	1	ш	- 1			ш	ш		П	Ш	ш	П	18	Ш		П	П	ш		П			L.	П			н			П	×	
	- 1		ш		-   5	8	ш		SWITC	1	ш	- 1	Ü		ш	ш		П	Ш	Ш	П	119	Ш		П	П	ш		П			ATTON	- 1		S	ıl	- 1	1	ш	ı	
			ш		DOME AN HOTHERE	4	ш				ш	<i>~</i>	andopau	씵	Ы	ш	t	1	Ш	Ш	3	ECHUN PERATURE DEVIATION	Ш	삞	П	П	9.		П			3	Ш	18		н		150	Ш		
	-		ш		5	3	ш		18	1	ш	TOR	18	16	E	Ш		il.	Ш	Ш	ALARM ALARM	ŏ	ð	립	П	П		9	П	I.,		5	副	ΙĚ	: [교	н	- Is	- 18	ы		
DOCUPANCY TIME			Ш		Ila	ŝI.	9	ջ .	PRESSURE	1		읾	JRE SENSOR	MPERATURE	3		JE S	KWHR	s	Ш		-14	ONDITION	ERATURE	П	П	T/STOP		П	Ĭ		RECIRCU	K RESET	. E	WATER BONLER SELEC	н	골	3 6	13	J	
	b				-13	ساك		Ę	일 월	1	ONTAC	91	있	d.	101	l li	318	3   3	8	Ш	5	텔딩	2	9	П	П	181	2	2	기원	1	ĕ	X	ál 5	네벨!	ıl	HI:	:IE	₽	ONTRO	
	12				13	Į٤		Ř.	واع	Ιz		ᆲ	SENS	P	8	RATE	MPER		9		٣.	ECITOR	ŏ		П	П	8		غاڭ	8	100	5	ĕ۱٩	3 8	18	ы		48		Ę	
	ŭ	١.		oli	ŝΙĕ	1>	9	ě	끼긑	ĮΕ	l:	2	00 9	AIR TEA	삤	5	3 8	Ş Ş	MAND DOWN	2		:119		3	Ш	П		20	CYCLING NO HATTING	ξļţ		MOUN	010 050	ál E	181			5 I II			
	Ιğ	ŏ		51	واع	힘		텕	51ŵ	NS.		äl	91	15		8	E			텕	31	기프	3	ŏI:		H	텡	3	K   2	100	18	₹	ğ F	418	설팅	樫	œ	318	ĕ	mHG.	
GRAPHIC DISPLAY	. 15		φl	3	MKI/SIO	ΙĘ	崱	35	낆뱚	DW SWIT	IBI	削	탏	Ĭ	12			0	ø	W FAIL	ᆲ	희종	윺	뙤	315	1	CHEDILLED START	≊.	2 3	818	CONOMIZER	VENTIL	٤l٩	ψB	131		313	ᆁᄚ	ıΞ	Ē	
POINT DESCRIPTION	-18		HAND	8	SIMKIS	18		3	DIFFERENTIAL PRE	15	AUXILIARY CON	≨	MOISTURE	SUPPLY	8	ARFLO			l#	3	윏	ROOM TEMP	έĐ	HIGH ROOM		3	ŝ	8	DUTYCYC		lă M	9	HOT/C		HOT WATER BOIL	ı≩l	CHILLER SELECTION	318	CHILLER DEMAND LIMIT	ŝ	
UNIT HEATER UH-1	+	۳	Ħ	Ť,	•		H	7	۳	۳	н	Ť	-		۲	Н	۳	۳	۳	Ħ	7	۳	Ħ	7	+	+	H	Ť	۲	+	Ť	H	Ŧ	Ŧ	Ħ	ĒΤ	7	۳	Ħ	Ħ	1
SUMP PUMP SP-1	$^{-}$	1	П	٦,	•	1	П	$^{+}$	1	Т	П	_	•	1	П	П	+	Т	П	П	١.	•	۰	$\neg$	+	1	П	_	+	Т	Т	П	+	$\top$	П	П	$^{+}$	т	П	г	۰
SUMP PUMP SP-2	$\neg$	т	П	٦.	•	т	П	$\neg$	$^{\dagger}$	Т	П	╗	•	т	П	П	$\top$	т	П	П	1	•	•	╛	$\top$	T	П	┪	T	$^{\dagger}$	Т	П	T	$\top$	П	П	$\top$	т	П	П	1
SUMP PUMP SP-3		т	п	П.	•	_	П	$\neg$	_	т	П	╗	•	т	П	П	_	т	П	П	_			$\neg$	т	$\top$	П	$\neg$	$\top$	т	т	П	$\top$	$\top$	П	$\Box$	$\neg$	$\top$	П	г	

							(Draw <b>i</b> ng T <b>hi</b> e	Phase	Project Title			[Project Number
		CONSULTANT	ARCHITECT/ENGI	NEER OF RECORD	STAMP	Office of	MECHANICAL CONTROL	BID DOCUMENTS	RENOVATE TO	WER BUILD	ING 1	438-18-102
					Manual Control	Construction		DID DOGGINEIVIO				Bullding Number
Blid Documents 0	5/30/2019	FARRIS ENGINEERING			ME CHAN CA THE	Oonstruction	DIAGRAMS					Do soing incurred
Contract Documents 100% Submittal (CD)	5/14/2019	OWAHA   LINCOLN   SIDNEY   COLORADO SPRINGS	COT TT		Shill Asse	and Facilities						1 1
Contract Documents 95% Submittal (CD) 0	4/11/2019	forris-use.com		=	ENGLYHOP MARKET	Management	Approved: Project Director	i i	Location			Drawling Number
Contract Documents 35% Submittal (CD) 0	2/18/2019	сорумент FEI #:182083	CLH Calvin L. Hinz	\ <del></del>	SZHREIER AN	ivialiagement	l'' '		Sioux Falls, SD	57105		"
Design Development (DD) 1:	2/10/2018	This document and the information contained may not be reproduced or excerpted from without the express	Calvin L. Finiz		11.//			FULLY SPRINKLERED			Te.	4
Schematic Design (SD)	0/08/2018	written permission of Ferris Engineering, Inc. Unauthorized copying, disclosure or construction use are prohibited by	3705 North 200th Street	FARRIS ENGINEERING	THE OF MERSEN	M. IIS Department		I LOTTI SEVINGTERED	II .		Drawn	∏ M604
	late:	the copyright law.	3705 North 200th Street Elkhom, Nebraska 68022 (402) 291-8941	OWNER TRACON   BONEY   COSONADO SPISNOS fortir-com	05/30/2019	U.S. Department of Veterans Affairs			05/30/2019	JDB	LMB	

#### ENERGY RECOVERY VENTILATION UNIT SCHEDULE DESIGN CONDITION COOLING MODE AT DEMON 2,250 1,5 80,0°F 66,1°F 44,8°F 42,4°F 52,2°F 51,3°F 91,8 61,8 80,5° F 62.4° F 12.7 44.8° F 71.4° F 180.0° F 150.0° F 65,4

The second secon

PRIORIDE WITH FACTORY PROGRAMMANE CONTROLS.

PROMOSE WITH PACE PRIORIPE STATE AND PRIVATED BICATOR ROOF CURB AND HAIL GLARGE.

PROMOSE URIT WITH PERMATRON REMOVABLE BESH FAMILY COMPRISER OLD, SCREENS.

HELD MIGHTED CONTROLS, CORONDAY WITH CONTROLS CONTROLING WITH CONTROLS CONTROLING THE CONTROL CONTROLING PACE PROMOSE OR ACCITIONAL INCOMMITTION.

REPORT OF MONTHS OF CONTROLS.

										AIR-CO	OLI	ED CHIL	LER	SCHED	ULE							
MARK	SERVES	COMPRESSOR TYPE	CAPACITY TONS	AMBIENT TEMP.	ARI EER	IPLV EER	EWT DEG F	LWT DEG F	DESIGN FLOW GPM	MIN. FLOW GPM	NO.	COMP	RESSORS STEPS	RLA(EA)		kW (EA)	FANS FLA (EA)	SOUND POWER LEVEL dBA	SOUND PRESSURE LEVEL dBA	WEIGHT LBS.	MANUFACTURER & MODEL NO.	REMARKS
CH-1	BUILDING 1 TOWER	SCROLL	31,21	95° F	9,58	15.31	54,00	44,00	82.00	40,00	2	1	2	53.0/73.90	3	3,613	6,57	0,08	63,0	2630	TRANE CGAM 35	1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11

С

SEE MICHARIDAMELICITIONAL COORDINATION SCHIPDUL FOR BLICTICAL DAYA, PROVIDE URT WITH PERMATRON REMAVABLE MESH FARRIC CONDENSER COLL SORESIN, PROVIDE URT WITH THE PROMOTED REMAVABLE MESH FARRIC CONDENSER COLL SORESIN, PROVIDE URT WITH HOT OR SPYMASS. PROVIDE URT WITH HOT OR SPYMASS. PROVIDE URT WITH HOT OR SPYMASS. PROVIDE COMPRESSOR SOUND BLANKETS, SUPER DUET SOUND PROVIDE, CONCRET SHIPTO CONTINUES, DOCIDIONAL THE CONTINUES CONTINUES.

PROVIDE CONDENSING UNIT WITH FLEXBLE REFRIGERANT PPING CONNECTIONS AND FLEXBLE CONDUCT CONNECTIONS
COORDINATE FLOW REQUIREMENTS WITH PPING AND CONTROLS CONTRACTOR FOR SIZINGLOCATION OF BYPASS VALVE

					s	TEA	M TO HOT WATER CO	ONVERTOR SC	HEDUI	LE				
							TUBE SIDE (WATER)			SHELL	SIDE (STI	EAM)		
MARK	SERVES	TYPE	GPM	E.W.T.	L.W.T.	P.D. FT.	MIN. SURFACE AREA (SQ. FT.)	NUMBER OF PASSES	FOUL FACTOR	PRESS. PSIG	LB/HR	MBH	MANUFACTURER & MODEL NO.	REMARKS
HX-1	BUILDING 1 TOWER	HEATING HOT	100.0	140° F	180° F	1.14	49.58	2.00	0.00079	10	2056.9	1959.2	BELL & GOSSETT	1

PROVIDE FLOAT AND THERMOSTATIC TRAP, STRAINER AND STEEL SUPPORT STRUCTURE, SIZE TRAP FOR TWO TIMES LISTED FLOW RATE.

						SPLIT	SYSTEM	UNIT SC	HEDULE				
INDOOR	OUTDOOR		CLG (MBH)	VOLTAGE	PHASE		OUTDOOR UNIT	MANUFACTURER				OUTDOOR UNIT	REMARKS
UNIT MARK	UNIT MARK		TOTAL			MCA	MCA		INDOOR UNIT	OUTDOOR UNIT	MODEL NO.	MODEL NO.	
10-2	00-2	480 <b>-</b> 635	24,0	208	1	1	18	MITSUBISHI	53	163	PKA-A24FA	PUY-A24NHA	1, 2, 3, 4, 5, 6, 7

SEE MECHANICALIELECTRICAL COORDINATION SCHEDULE FOR ELECTRICAL DATA.

UNIT SHALL BE ABLE TO COOL WITH AMBIENT TEMPERATURES AS LOW AS 0 DEG.F.
PROVIDE WALL CONTROLLER INTEGRAL CONDENSATE PUMP, CRANKCASE HEATER, WALL BRACKET, WIND BAFFLE AND INSULATED LINE SETS.

REFRIGERANT SHALL BE R-410A.

UNIT SHALL BE MINIMUM 13.5 SEER.
PROVIDE WITH WALL BRACKETS FOR OUTDOOR UNIT.
PROVIDE UNIT WITH PERMATRON REMOVABLE MESH FABRIC CONDENSER COIL SCREEN.

		HYDE	RONIC	SYS	TEM	SPECIA	LTIES SC	HEDULE	
MARK	SERVES	TYPE	GPM	HEAD (FT)	GAL.	CONNECTION (IN)	DRY WEIGHT (LBS)	MANUFACTURER & MODEL NO.	REMARKS
GF-1	HEATING HOT WATER SYSTEM	MANUAL CHEMICAL FEEDER		-	5	3/4"	33	JL WINGERT 5HD	1
CF-2	CHILLED WATER SYSTEM	MANUAL CHEMICAL FEEDER			5	3/4"	33	JL WINGERT 5HD	1
AS-1	HEATING HOT WATER SYSTEM	AIR SEPARATOR	100	0.6		3*	114	BELL & GOSSETT CRSN43F	2, 3
AS-2	CHILLED WATER SYSTEM	AIR SEPARATOR	60	0.4		2-1/2"	99	BELL & GOSSETT CRSN-2 1/2F	2, 3
ET-1	HEATING HOT WATER SYSTEM	EXPANSION TANK			44,4	1/2"	145	BELL & GOSSETT D-80	4, 5
ET-2	CHILLED WATER SYSTEM	EXPANSION TANK			33,6	1/2"	103	BELL & GOSSETT D-(0)	4, 5

PROTORE WITH INTERPOLATION OF CHICADO ON THE PROTOR CONTROL OF CHICAGO ON THE CONTROL ON THE

		VARIABLE FR	EQUENCY DR	IVE SCHEDULE
MARK	SERVES	TYPE	CONTROL SIGNAL	REMARKS
VFD-CWP-1.1	CWP-1.1	PULSE WIDTH MODULATION	4 - 20 MA	1, 2, 3, 4
VFD-CWP.1.2	CWP-1.2	PULSE WIDTH MODULATION	4 - 20 MA	1, 2, 3, 4
VFD-HWP,1,1	HWP-1.1	PULSE WIDTH MODULATION	4 - 20 MA	1, 2, 3, 4
VFD-HWP,1,2	HWP-1,2	PULSE WIDTH MODULATION	4 - 20 MA	1, 2, 3, 4
REMARKS:				

SEE MECHANICAL ELECTRICAL COORDINATION SCHEDULE DOD ELECTRICAL DATA

SEE NECHANICALELECTRICAL COCKRIMATION SCHEDICLE FOR ELECTRICAL DATA.

ULT SHALL HAVE PHEGRALL COCKRIGE DISCONNECT.

ALL MOTORS WITH HYD'S SHALL BE INVESTOR RATED, PREMIUM EFFICIENCY AND PROVIDED WITH SHAFT GROUNDING KITS.

PROVIDED BY THEMPRATURIS CONTROLOR INSTALLED BY ELECTRICAL CONTRACTOR.

					FAN C	OIL UN	т ѕсн	EDULE			
MARK	TYPE	CFM	COOLING	CAP MBH	COOLI	IG COIL	HEATING	HEATIN		MANUFACTURER	REMARKS
MARK	1176	CFM	TOTAL	SENSIBLE	GPM	PD (FT)	CAP MBH	GPM	PD (FT)	& MODEL NO.	KEMMAKA
FC-1	VERTICAL	300	8,17	6.70	1,80	1,59	18,98	0.96	0.89	TRANE FCVA030	1, 2, 3, 4, 5, 6, 7, 8, 9
FC-2	VERTICAL	400	9,55	8,37	2,10	1,90	22,40	1,12	1,20	TRANE FCVA040	1, 2, 3, 4, 5, 6, 7, 8, 9
FC-3	HORIZONTAL	300	8,17	6,70	1,80	1,59	18,98	0,95	0,89	TRANE FCEB030	1, 2, 3, 4, 5, 6, 7, 8, 9

SEE MECHANICAL/ELECTRICAL COORDINATION SCHEDULE FOR ELECTRICAL DAT

CHILLED WATER COOLING COIL CONDITIONS ARE 80°F DE80°F WB E.A.T. AND 44°F E.W.T. HOT WATER HEATING COIL CONDITIONS ARE 70°F E.A.T. AND 180°F E.W.T.

PROVIDE INTEGRAL ELECTRICAL DISCONNECT WITH UNIT.

PROVIDE UNIT WITH ECM HIGH STATIC MOTOR, STAINLESS STEEL DRAIN PAN AND HIGH LEVEL CONDENSATE SWITCH.

PRODUCE UNITY AND INCIDENCE, SETTIN TO ANNE TO REACTIONAL PRODUCTION.

PROVIDE UNITY THAT COLOR SETTIN TO ANNE TO REACTIONAL PRODUCTION.

PROVIDE UNITY THAT COLOR SETTIN TO ANNE TO ANNE TO AND THAT COLOR SETTING.

CORROBATE COLOR OF GRELENCESES ANNELS WITH ANOHITECT.

ANY PROFFUEDE COLOR SOUTHOR.

		нот w	/ATE	R UN	IIT HEA	TER	SCF	IEDUL	E	
MARK	TYPE	ARRANGEMENT	CFM	E.W.T	HEATING CAP, MBH	GPM	P.D. FT.	FAN RPM	MANUFACTURER & MODEL NO.	REMARKS
UH-1	EXPOSED	HORIZONTAL	500	180°F	18.0	1.7	0.83	1550	TRANE	1, 2, 3, 4, 5

SEE MECHANICAL/ELECTRICAL COORDINATION SCHEDULE FOR ELECTRICAL DATA.

PROVIDE INTEGRAL DISCONNECT.

CONTROLS BY REMOTE DOC SENSOR, PROVIDE RELAY AS NECESSARY PROVIDE RELAY AS NECESSARY PROVIDE RELAY AS NECESSARY AS PROPYLENE GLYCOL SOLUTION.

TY RELIEF HOOD SCHEDULE											
CFM	MAX S.P. DROP (IN W.C.)	MAX. THROAT VELOCITY (FPM)	MANUFACTURER & MODEL NO.	REMARKS							
			GREENHECK FGR	1,2							
٠			GREENHECK FGR	1,2							
		GREENHECK FGR	1, 2								

PROVIDE 24" ROOF CURB & BIRDSCREEN

SERVES

18"X26" COORDINATE WITH ARCHITECT FOR FINISH COLOR.

GRAVI

THROAT SIZE

18"X26" RH2 ELEVATOR 18"X26"

	REGISTER - GRILLE - DIFFUSER SCHEDULE													
MARK	FUNCTION	TYPE	TYPE CFN MAX SIZE BORDER OR MATERIAL RANGE N.C. (INCHES) FRAME ALUM STEEL		FINISH	ACCESS.	MANUFACTURER & MODEL NO.	REMAR						
8-1	SUPPLY	SQUARE FACE NOMINAL PNL.	0 - 130	25	er ø NECK	24 x 24 LAY- <b>N</b>		×	STND. WHITE	-	KRUEGER SERIES 1400	1, 2,		
5-2	SUPPLY	SQUARE FACE NOMINAL PNL.	131 - 250	25	8" BI NECK	24 x 24 LAY- <b>N</b>		×	STND. WHITE	-	KRUEGER SERIES 1400	1, 2,		
8-3	SUPPLY	SOUARE FACE NOMPHAL PML	251 - 400	25	10" Ø NECK	24 x 24 LAY- <b>P</b> N		х	STND. WHITE	-	KRUEGER SERJES 1400	1, 2,		
5-4	SUPPLY	DOUBLE DEFLECTION	0 - 150	25	10 x 6	SURFACE MOUNT		х	STND. WHITE		KRUEGER SERIES 880H	1, 2,		
R+1	RETURN) EXHAUST	PEXED DEFL. 35" BLADE	0 - 130	25	6×6	SURFACE MOUNT	х		STND. WHITE		KRUEGER SER <b>E</b> S SSIGH	1, 2,		
R42	RETURNI EXHAUST	PERF, PANEL 12x24 FAGE	0 - 175	25	50 NECK	12 × 24 LAY- <b>N</b>		×	STND. WHITE	-	KRUEGER SERIES (49)	1, 2,		
R-3	RETURNI EXHAUST	PERF, PANEL 12x24 FACE	175 - 450	25	18x6 9Q NECK	12 x 24 LAY- <b>N</b>		×	STND. WHITE	-	KRUEGER SERIES 6490	1, 2,		
REMAR	KS:					•								

COORDINATE BORDER OR FRAME TYPE WITH COORDINATE COLOR/FINISH WITH ARCHITECT

ELECTRIC CABINET UNIT HEATER SCHEDULE												
MARK	TYPE	ARRANGEMENT	CFM	HEATING CAP. (KW)	MANUFACTURER & MODEL NO.	REMARKS						
ECUH-1	WALL SURFACE	FRONT INLET/OUTLET	250	5.0	BERKO CUH935 SERIES	1, 2, 3, 4						
ECUH-2	WALL	FRONT INLET/OUTLET	250	5,0	BERKO CUHRIS SERIES	1, 2, 3, 4						
ECUH-3	WALL SURFACE	FRONT INLET/OUTLET	250	5.0	BERKO CUH935 SERIES	1, 2, 3, 4						
ECUH-4	CEILING	FRONT	250	3.0	BERKO	1, 2, 3, 4, 5						

6 7 8 9

SEE MECHANICAL/ELECTRICAL COORDINATION SCHEDULE FOR ELECTRICAL DATA.

PROVIDE INTEGRAL ELECTRICAL DISCONNEC

COORDINATE COLORFINISH WITH ARCHITECT.
CONTROLS BY REMOTE DDC SENSOR, PROVIDE RELAY AS NECESSARY,
PROVIDE RECESS TRIM KIT.

### HOT WATER HEATING COIL SCHEDULE ARK SERVES FACE VELOCITY CFM E.A.T. L.A.T. MAX.AIR MN. TOTAL MAX. FINSIM.

40% PROPYLENE GLYCOL SOLUTION

PROVIDE STEEL BASE RAIL WITH ALL UNITS. COIL SHALL OPERATE AS MAIN HEATING COIL

COLLAIR PRESSURE DROP LISTED FOR MAXIMUM AIR HANDLING UNIT ARFLOW. FURNISH PRESSURE INDEPENDENT CONTROL VALVES FOR ALL COLLS.

VARIABLE REFRIGERANT FLOW ZONING SYSTEM SCHEDULE											
MARK	ARRANGEMENT	CFM	COOLING DATA TOTAL (MBH)	HEATING DATA CAP (MBH)	MANUFACTURER & MODEL NO.	REMARKS					
10-1	CASSETTE	245-335	12,0	13,5	MITSUBISHI PLFY-P12NFMU-E	1, 2, 3, 4, 5, 8					

SECURION DE LA COMPANIA DE L'ESTRE A CONSTRUTORI SOLICIOLE PER ECTRE A DATA.

MANIACTURIRE SUN L'ESTRE PERIORIPATE PERS CORRIGHE, TORIN DE LA COMPANIA DE RESURED PER SIZES AD REPRIGERANT ACCESSORIES.

REPRIGERANT SUL ESTRE PERIORIS CONTRACTOR FOR ALL CONTROL IN METER PARAMESICAMICHA.

CONNECT REPRIGERANT SUL ES ER MAN.

CONNECT REPRIGERANT SUL ES ER MAN.

CONNECT REPRIGERANT SUL ES ER MAN.

CONNECT REPRIGERANT SUL CONTRACTOR CONTRACTOR DE LA CONTRACTOR DE L'ESTRE MANIFOLISME SE PER MANIFOLISME.

CONDECTE REPRIGERANT SUL CONTRACTOR DE L'ESTRE PERIORI DE L'ESCRESSIONES AS REQUESTES YET ME MANUFACTURE.

	CONSULTANT	ARCHITECT/ENGINEER OF RECORD	STAMP	000	Drawling Title MECHANICAL SCHEDULES	Phase BID DOCUMENTS	Project Title RENOVATE TOWER BUILDING 1	Project Number 438-18-102
Bid Documents         05/30/2019           Contract Documents 100% Submittal (CD)         05/14/2019	FARRIS ENGINEERING		ALCHAN AND AND AND AND AND AND AND AND AND A	Construction and Facilities	MEST WITHOUTE SOME DEED	DID DOGGINEITTO		Bu <b>ll</b> dling Number
Contract Documents 95% Submittal (CD)	ferria-use.com  COPYRIGHT  This document and the information contained may not be reproduced or excerpted from without the express	CLH Calvin L. Hinz	SZHREIER SE E-4552	Management	Approved: Project Director	ELILLY ODDING EDED	Cocation Sioux Falls, SD 57105	Drawling Number
Design Development (LC)	be reproduced or excerpted from without the express written permission of Forns Engineering, line, Unauthorized copying, disclosure or construction use are prohibited by the copyright law.	3705 North 2009 Street Elchom, Nabraska 68022 (402) 291-8941 FARRIS ENGINEERING OWNH I InfCONT Ignet   CONTINUE OF THE INFO	05/30/2019	U.S. Department of Veterans Affairs		FULLY SPRINKLERED		M701
2	3 4	5	1	6	7	8	9	10

MECHANICAL / ELECTRICAL COORDINATION SCHEDULE

ASSSEVIATION ELECTRICAL CONTRACTOR MECHANICAL CONTRACTOR
INTEGRAL WITH EQUIPMENT
COMBINATION STARTER AND

SAFETY SWITCH CIRCUIT BREAKER NF NON-FUSED NR NON-REVERSING

FLA	FULL LOAD AMPS		3R	NEWA 3	R R TO SPECIFI	O A TROMO	ST COD 4000	THERMA						
				NEFER	TOOFEGE		CONNECT	KURAL RE	WINDW		R STARTI	IR.	NAMEPLATE	
MARK	DESCRIPTION	LOAD	ATING	PH	FURNISHI INSTALL BY	TYPE	RATING (AMPS)	FUSE	ENCL.	FURNISHI INSTALL BY	TYPE/ NEMA SIZE	ENCL.	MINIMUM SCCR (AMPS)	RE
ERV-1	ENERGY RECOVERY VENTILATOR	56,58 FLA	208	3	MI MI	-	-			M1	SIZE	-	7,000	_
FC-1	FAN COL.	3.6 FLA	120	-1	MI					MI				
FC-2	FAN COL	3.6 FLA	120	-1	M1		-	٠		MI				
FC-3	FAN COIL	91 WATTS	120	-1	M1			-	-	MI				
IU-1	INDOOR FAN COLUNIT	0.33 FLA	208	-1	££	SH	20	NR	NI				5,000	
[U-2	NOOR FAN COLUNT	0.43 FLA	206	-1	6.6	SH	20	MR	N				6,000	
OU+2	OUTDOOR UNIT	14 FLA	208	-1	£E	SS	30	MR	3R				5,000	
CWP-1	CHILLED WATER PUMP	5.0 HP	208	3	ME		-	-		ME	VFD		7,000	
HWP-1	HEATING HOT WATER PUMP	5.0 HP	208	3	ME			-		ME	VFD		7,000	
CH-1	CHILLER	52,3 KVA	208	3	££	55	400	NR	3R	MI			10,000	
UH-1	UNIT HEATER	16 WATTS	120	-1	MI							٠		
ECUH-1	ELECTRIC CABINET UNIT HEATER	5,0 KW	208	-1	MI								5,000	
ECUH-2	ELECTRIC CABINET UNIT HEATER	5,0 KW	208	-1	MI		-	-					5,000	
ECUH-3	ELECTRIC CABINET UNIT HEATER	5,0 KW	208	-1	MI			-					5,000	
ECUH4	ELECTRIC CABINET UNIT HEATER	3,0 KW	208	-1	MI			-					5,000	
SP-1	SUMP PUMP	3/4 HP	120	-1										
SP-2	SUMP PUMP	3/4 HP	120	-1					٠				-	
SP-3	SUMP PUMP	3/4 HP	120	-1					-					

UNES:
VERTIVICOORGINATE ALL RATINSS FOR EQUIPMENT, WHERE SUCH RATINGS ARE OTHER THAN THAT INJURATED ON MECHANICALELECTRICAL COCREMATION
SCHEDULE, PROVIDE OBJECONNECTS, MOTOR STATERS, OVERCURRENT CRIVESS AND RELATED REVISIONS ACCORDINGLY. WHERE EQUIPMENT IS PROVIDED WITH
RATINGS OTHER THAN THAT REJECTION, CONTRACTOR SHALL BE RESPONJED FOR COCKRIGATING AND ACCORDING COSTS FOR REINSTOLD.

PROVIDE FRACTIONAL HORSEPOWER MOTORS WITH INTEGRAL OVERLOAD PROTECTION. EQUIPMENT LISTED IN SCHEDULE MAY APPEAR INHUMEROUS LOCATIONS, EQUIPMENT MARKS ARE DESIGNATED BY UNDUE IDENTIFIERS ON THE PLANS LE., HP-1.1, HP-1.2, IN THESE INSTANCES, THE ELECTRICAL REQUIREMENTS DO NOT CHANGE FROM ONE MARK TO THE NEXT, ONLY THE UNDUE DENTIFIER CHANGES.

HORSEPOWER RATED SWITCHES (SH); FOR 150 V MOTORS LESS THAN 12 HP, PROVIDE PUSEHOLDER WITH SMITCH, FURED PER MANUFACTURERS RECOMMENDATION, AND BEG REQUIREMENTS, FOR 150 V MOTORS ARTED 123 PF OR 150 PF, PROVIDE HP PARTED TOGGLE SMITCH (MH-FRE BRANCH CRICUIT OVERCURRENT DEVICE MEETS NOW REQUIREMENTS FOR SHORT-GALT/IT PROTECTION OF NOSED SMETTS WAS RATIO.).

NO STALL COTTES AND AS SERVICES OF HE WATEL SO, DOTO COTTESLESS, REBELT BENEFICIAL INCORPORATION COMPRESSORS AND EXCHANGE THAN A SHARED WITH HERMOLE AND AND ADMINISTRATION OF THE WATER AND ADMINISTRATION COMPRESSORS AND EXCHANGE THE WATER AND ADMINISTRATION OF THE WATER ADMINISTRATION OF THE W

FOR MOTORS CONTROLLED BY WARMALE FREQUENCY DRIVES, PROVIDE FACTORY HISTALLED SHAFT GROUNDING THAT RECURRES NO MANTENANCE FOR THE SERVIC LIFE OF THE MOTOR.

PUMP SCHEDULE GPM HEAD RPM TYPE MARK SERVES REMARKS & MODEL NO. BELL & GOSSETT E-1510 1,59C 75 1,790 CHILLED WATER 75 1,750 BELL & GOSSETT F-1510 1 59C HEATING HOT WATER BASE MOUNTED END SUCTION

SEE MECHANICAL/ELECTRICAL, COORDINATION SCHEDULE FOR ELECTRICAL DATA, PROVIDE WITH PREMIUM EFFICIENCY INVERTERS-DUTY MOTOR. PROVIDE FACTORY INTENDLED MOTOR OF WITH SWAFT OROUNDEND KIT, PROVIDE ANGEOSHA COUPT ING GUARD, BASED ON AND REPORT LENG FUND SOUTHON.

GPM MAX. PD(FT) REMARKS 550 2.250 45°F 71°F 0.28 2 65.4 10

HOT WATER PERFORMANCE BASED ON 150°F E.W.T. AND 180°F L.W.T.

