





U.S. FISH & WILDLIFE SERVICE

HURON WMD

MULTIPURPOSE BUILDING AND VISITOR CENTER CONSTRUCTION DOCUMENTS

SHEET INDEX

SHEET #	SHEET NAME
C001	COVER SHEET
C002	CIVIL NOTES AND LEGEND
C101	DEMOLITION PLAN
C201	HORIZONTAL CONTROL PLAN
C301	CIVIL SITE PLAN
C401	GRADING PLAN
C402	GRADING DETAIL
C501	UTILITY PLAN
C502 TO C503	UTILITY DETAILS
C504 TO C506	SITE DETAILS
C507	DRIVEWAY AND PARKING LOT PROFILES
C601	EROSION CONTROL PLAN
C602	EROSION CONTROL NOTES
C603	EROSION CONTROL DETAILS
A001	ABBREVIATIONS AND MOUNTING HEIGHTS
A002	LIFE SAFETY AND CODE ANALYSIS
A100	GROUND FLOOR PLAN
A101	ROOF PLAN
A120	REFLECTED CEILING PLAN
A200	BUILDING ELEVATIONS
A300	BUILDING AND WALL SECTIONS
A301 TO A303	WALL SECTIONS
A400	ENLARGED FLOOR PLANS
A401 TO A402	INTERIOR ELEVATIONS
A403	ADA SIGNAGE
A500 TO A501	INTERIOR DETAILS
A510 TO A511	EXTERIOR DETAILS
A600	DOOR SCHED., DOOR & WINDOW ELEV.
A800	ROOM FINISH FLOOR PLAN
A801	FURNITURE PLAN
S101	GENERAL STRUCTURAL NOTES
S201	STRUCTURAL FOUNDATION PLAN
S301	MAIN LEVEL FRAMING PLAN
S401	ROOF FRAMING PLAN
S501 TO S503	STRUCTURAL SECTIONS AND DETAILS
M001	MECHANICAL COVER SHEET
M002 TO M004	MECHANICAL SCHEDULES
M100	UNDERFLOOR MECHANICAL HVAC PLAN
M101	FIRST FLOOR MECHANICAL HVAC PLAN
M102	FIRST FLOOR MECHANICAL PIPING PLAN
M103	ROOF MECHANICAL PLAN
M104	MECHANICAL ZONE PLAN
M201	MECHANICAL SECTIONS AND ENLARGED PLANS
M301 TO M304	MECHANICAL DETAILS
E001	ELECTRICAL COVER SHEET
E002 TO E003	ELECTRICAL SCHEDULES
E101	ELECTRICAL POWER AND SPECIAL SYSTEMS PLAN
E102	ELECTRICAL LIGHTING PLAN
E301 TO E302	ELECTRICAL DETAILS
ES101	ELECTRICAL SITE PLAN
P001	PLUMBING COVER SHEET
P101	FIRST FLOOR PLUMBING DOMESTIC WASTE AND VENT PLAN
P102	FIRST FLOOR PLUMBING DOMESTIC WATER PLAN
P103	ROOF PLUMBING PLAN
P301 TO P302	PLUMBING DETAILS
PS101	PLUMBING SITE PLAN



VICINITY MAP
NO SCALE

APPROVAL SIGNATURES

REGIONAL ENGINEER	DATE
PROGRAM SUPERVISOR	DATE
ASST. REGIONAL DIR.	DATE
FACILITIES	DATE
SAFETY	DATE
CULTURAL RESOURCES	DATE

NOTE TO BIDDERS:
ANY PRINT ACCOMPANYING THIS INVITATION TO BID MAY BE A REDUCED REPRODUCTION OF THE WORKING DRAWINGS. IF LINE BELOW DOES NOT MEASURE SIX INCHES IN LENGTH, THE INDICATED SCALES ARE TO BE ADJUSTED ACCORDINGLY.



UNITED STATES DEPARTMENT OF THE INTERIOR
FISH AND WILDLIFE SERVICE
REGION 6 ENGINEERING - DENVER, COLORADO

HURON
WMD


BEADLE COUNTY, SOUTH DAKOTA

MULTIPURPOSE BUILDING AND VISITOR CENTER

COVER SHEET

DESIGNED: MH	DRAWN: JB	CHECKED: BD
DATE: 2022.04.29		SHEET 1 OF 74

REVISIONS			
REV	DATE	DESCRIPTION	BY



GENERAL NOTES

1. THE UTILITIES SHOWN IN PLAN AND PROFILE ARE INDICATED IN ACCORDANCE WITH AVAILABLE RECORDS. (ALL UTILITIES MAY NOT BE SHOWN.) THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING EXACT LOCATIONS AND ELEVATIONS OF ALL UTILITIES FROM THE OWNERS OF RESPECTIVE UTILITIES. ALL UTILITIES SHALL BE NOTIFIED AT LEAST 72 HOURS PRIOR TO EXCAVATION.
2. ALL MINOR OBSTRUCTIONS MAY NOT BE SHOWN ON PLANS. THE CONTRACTOR SHALL VISIT THE SITE AND DETERMINE THE ACTUAL CONDITIONS WITH REGARD TO THE EXISTENCE OF FENCES, DRIVEWAYS, TREES, SIDEWALKS, CULVERTS, UTILITIES AND OTHER MISCELLANEOUS OBSTACLES THAT MAY INTERFERE WITH CONSTRUCTION PRIOR TO SUBMITTING BIDS.
3. PROTECT OR RESTORE ALL LOT CORNERS AND SURVEY MONUMENTS.
4. SYMBOLS ON THE DRAWINGS (BECAUSE OF THEIR SIZE) MAY NOT REPRESENT THE EXACT LOCATION OF EITHER PROPOSED OR EXISTING UTILITIES. (EX. GATE VALVES & HYDRANTS)
5. ALL UNITS ARE IN FEET, UNLESS OTHERWISE NOTED.
6. IF INSTALLATION DETAILS AND MANUFACTURER'S INSTALLATION REQUIREMENTS DO NOT MATCH, THE PROJECT OWNER SHALL BE CONSULTED ON DISCREPANCIES.

UTILITIES

ELECTRIC:
 NORTHWESTERN ENERGY
 600 MARKET STREET W
 HURON, SD 57350
 CONTACT: KIRBY WICKS
 PHONE: 605-352-8411

WATER:
 MID DAKOTA RURAL WATER SYSTEM
 608 W 14TH STREET
 MILLER, SD 57362-0318
 CONTACT: DEANN HARGENS
 PHONE: 605-853-3159

COMMUNICATIONS:
 SANTEL COMMUNICATIONS
 308 SOUTH DUMONT AVE
 WOONSOCKET, SD 57385
 CONTACT: PAM KOPFMAN
 PHONE: 605-796-4411

SD DEPARTMENT OF TRANSPORTATION
 HURON AREA OFFICE
 901 DAKOTA AVE N
 HURON, SD 57350
 CONTACT: BRAD LETCHER
 PHONE: 605-353-7140

FWS WETLAND DISTRICT MANAGER:
 HURON WMD
 PO BOX 1377
 HURON, SD 57350
 CONTACT: MATTHEW GRUNIG
 PHONE: 605-354-0533

CONTACTS

FWS ENGINEERING:
 REGIONAL OFFICE 6
 134 UNION BLVD
 LAKEWOOD, CO 80228
 CONTACT: MICHAEL LEMIEUX
 TELE: 303-236-4474

CIVIL ENGINEER:
 DOWL
 1833 S. SHERIDAN AVE.
 SHERIDAN, WY 82801
 CONTACT: MARK HINES, P.E.
 TELE: 307-257-8667

ARCHITECT:
 STANLEY CONSULTANTS INC.
 225 IOWA AVENUE
 MUSCATINE, IA 52761
 CONTACT: CHAD CHAMBERLIN, A.I.A.
 TELE: 563-264-6671


ELECTRICAL ENGINEER:
 ASSOCIATED CONSTRUCTION ENGINEERING (ACE)
 2040 HARNISH BLVD.
 BILLINGS, MT 59101
 CONTACT: CHRIS GREEN, P.E.
 TELE: 406-245-0136

MECHANICAL/PLUMBING ENGINEER
 ASSOCIATED CONSTRUCTION ENGINEERING (ACE)
 2040 HARNISH BOULEVARD
 BILLINGS, MT 59101
 CONTACT: AARON SADOWSKI, P.E.
 TELE: 406-245-0136

STRUCTURAL ENGINEER:
 DOWL
 222 NORTH 32ND STREET, SUITE 700
 BILLINGS, MT 59101
 CONTACT: MATTHEW METTLER, P.E.
 TELE: 406-869-6384

CIVIL SITE LEGEND

PROPOSED	EXISTING	PROPOSED	EXISTING
—W— WATER LINE	—w—w—w— WATER LINE	Ⓢ CURB STOP	Ⓜ WATER METER
—S— SEWER LINE	—s—s—s— SEWER LINE	■ SANITARY SEWER CLEAN OUT	⊗ WATER VALVE
▬ STORM	—sd—sd—sd— STORM	▲ TRANSFORMER	⊕ UTILITY POLE
—E— UNDERGROUND ELECTRIC CONDUIT	—e—e—e— UNDERGROUND ELECTRIC CONDUIT	--- GRADING LIMIT	⊙B-1 BORE HOLE LOCATION
—G— GAS LINE	—g—g—g— GAS LINE	■ TRAFFIC SIGN	
—FO— FIBER OPTIC	—fo—fo—fo— FIBER OPTIC	▬ CONCRETE	
—1400— MAJOR CONTOUR	—1400— MAJOR CONTOUR	▬ RIPRAP	
—1401— MINOR CONTOUR	—1401— MINOR CONTOUR	▲CP-102 REBAR CONTROL POINT	
▬ CURB AND GUTTER		—x—x—x— FENCE	
→ DITCH/SWALE		★ LIGHT POLE OR FLOOD LIGHT	
--- EDGE OF GRAVEL	--- EDGE OF GRAVEL		





C:\dowl_pw\cd0393906\SA-CS-CV-27083.dwg

HURON WMD				SUB-SHEET
CIVIL NOTES AND LEGEND				C002
MULTIPURPOSE BUILDING AND VISITOR CENTER				
DESIGNED MH	DRAWN JB	CHECKED BD	DATE 2022.04.29	SHEET 2 OF 74




- GENERAL NOTES**
1. CONTRACTOR SHALL COORDINATE DEMOLITION, TEMPORARY RELOCATIONS, ETC. WITH NEW CONSTRUCTION AS REQUIRED.
 2. CONTRACTOR TO BACKFILL DEMOLISHED AREAS WITH COMPACTED SOIL FILL OR TOPSOIL FROM APPROVED SOURCE TO MATCH ADJACENT GRADES.
 3. CONTRACTOR TO VERIFY ALL UTILITIES ARE DISCONNECTED PRIOR TO DEMOLITION. CONTRACTOR SHALL VERIFY EXTENT OF DEMOLITION IN THE FIELD, MARK AND PROTECT EXISTING UTILITIES FOR FUTURE CONNECTION. CONTRACTOR TO COORDINATE WITH UTILITY COMPANIES AND FWS AS NEEDED.
 4. REMOVE EXISTING SURFACING AND TOPSOIL AS REQUIRED.
 5. ALL DEMOLISHED STRUCTURES AND DEMOLITION DEBRIS SHALL BECOME THE PROPERTY OF THE CONTRACTOR UNLESS OTHERWISE NOTED. ALL MATERIALS AND DEBRIS SHALL BE REMOVED FROM THE SITE AND DISPOSED OF AT A PERMITTED LANDFILL FACILITY.

- DEMOLITION KEYNOTES**
1. DEMOLISH AND REMOVE EXISTING GRAVEL APPROACH.
 2. SAWCUT EXISTING ASPHALT SHOULDER TO CLEAN VERTICAL EDGE.
 3. REMOVE ANY EXISTING CULVERT ENCOUNTERED.
 4. REMOVE GATE AND 60' FENCING.



C:\dowl_pw\0393906\SC-CS-DM-27083.dwg

HURON WMD				SUB-SHEET	
DEMOLITION PLAN				C101	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED MH	DRAWN JB	CHECKED BD	DATE 2022.04.29	SHEET 3 OF 74	




HORIZONTAL CONTROL NOTES

1. ALL DIMENSIONS ARE TO THE FACE OF BUILDING, FACE OF CURB, EDGE OF SIDEWALK, OR CENTER OF STRUCTURE.
2. DIMENSIONS ALONG ACCESS ROAD, WHERE CURB IS NOT PRESENT, ARE TO EDGE OF GRAVEL.

COORDINATE SYSTEM DETAILS

THIS PROJECT USES THE SOUTH DAKOTA STATE PLANE COORDINATE SYSTEM, NORTH ZONE (4001); DATUM: NAD 1983 (CONUS) (MOLODENSKY); GEOID MODEL: GEOID18 (CONUS); UNITS: US SURVEY FEET. THE VERTICAL DATUM IS NAVD88.

ALL VALUES AND DISTANCES ARE GRID VALUES, WHICH DO NOT EQUAL TRUE GROUND VALUES. TO DETERMINE GROUND VALUES AT THIS SITE, MULTIPLY GRID VALUE BY A COMBINED SCALE FACTOR OF 1.0000489712. COMPLETE CARTESIAN AND GEODETIC CONTROL VALUES ARE SHOWN BELOW.
DOWL ESTABLISHED PROJECT CONTROL WITH AN OPUS POSITION AT POINT NUMBER 100 (CP 100).



NO. 100
SET REBAR
N: 199930.9550
E: 2390980.7040
ELEVATION: 1318.43
CP-100

NO. 101
SET REBAR
N: 199921.9660
E: 2391611.2970
ELEVATION: 1315.08
CP-101

ET BED
N: 199848.3791
E: 2390988.4708
BTM OF SAND EL=1318.50

ET BED
N: 199848.4096
E: 2391073.5210
BTM OF SAND EL=1318.50

ET BED
N: 199778.4139
E: 2390988.4959
BTM OF SAND EL=1318.50

ET BED
N: 199778.3834
E: 2391073.4959
BTM OF SAND EL=1318.50


BUILDING CORNER
N: 199676.9826
E: 2391359.3474

BUILDING CORNER
N: 199627.7657
E: 2391337.1333

BUILDING CORNER
N: 199612.3987
E: 2391502.4374

BUILDING CORNER
N: 199563.1830
E: 2391480.2239

NO. 102
SET REBAR
N: 199364.6240
E: 2391787.0130
ELEVATION: 1315.31
CP-102




HORIZONTAL CONTROL

Point ID	Northing	Easting	Elevation	Latitude (Local)	Longitude (Local)	Ellipsoid Height (Local)	Feature Code
100	199930.955	2390980.704	1318.43	N44°22'12.58452"	W98°23'03.52575"	1236.5240	SET-REBAR
101	199921.966	2391611.297	1315.08	N44°22'12.37141"	W98°22'54.84888"	1232.9650	SET-REBAR
102	199364.624	2391787.013	1315.31	N44°22'06.83424"	W98°22'52.58378"	1233.1880	SET-REBAR



HURON WMD				SUB-SHEET	
HORIZONTAL CONTROL PLAN				C201	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED MH	DRAWN JB	CHECKED BD	DATE 2022.04.29	SHEET 4 OF 74	

C:\dowl_pw\0303906\SC-CS-HC-27083.dwg




KEYNOTES

1. 8" AGGREGATE SURFACE COURSE OVER GEOGRID OVER 12" SUBGRADE COMPACTED TO 95% OF STANDARD PROCTOR. WIDTH VARIES 24' TO 112'. CONTRACTOR SHALL BUILD, COMPACT AND MAINTAIN SUBGRADE AND POSITIVE DRAINAGE DURING CONSTRUCTION. AGGREGATE SURFACE COURSE AND GEOGRID FURNISHED AND INSTALLED BY OTHERS (NOT IN CONTRACT). SEE SHEET C507 NOTES.
2. 6" CLASS B CONCRETE OVER 6" AGGREGATE BASE COMPACTED TO 95% OF STANDARD PROCTOR, OVER SEPARATION FABRIC, OVER 12" SUBGRADE COMPACTED TO 95% OF STANDARD PROCTOR. WIDTH AND JOINTING AS NOTED ON PLANS AND DETAILS.
3. 4" CLASS B CONCRETE SIDEWALK OVER 12" SUBGRADE COMPACTED TO 95% OF STANDARD PROCTOR. WIDTH AND JOINTING AS NOTED ON PLANS AND DETAILS.
4. SIDEWALK RAMP.
5. SIDEWALK DRAINAGE CHASE.
6. 6" TYPE B CONCRETE CURB.
7. DUPLEX LIFT STATION. SEE UTILITY SHEET AND DETAILS
8. SEPTIC TANK. SEE UTILITY SHEET AND DETAILS
9. PROPANE ENCLOSURE AND CONCRETE PAD. SEE DETAIL 5, SHEET C504
10. TRASH ENCLOSURE ON CONCRETE PAD. SEE DETAIL 5, SHEET C504
11. BACKUP GENERATOR ON CONCRETE PAD.
12. EVAPOTRANSPIRATION BED. SEE UTILITY PLAN AND DETAILS
13. RETENTION BASIN
14. "ACCESSIBLE PARKING SPACE" SIGN IN CONCRETE BOLLARDS.
15. "NO PARKING" SIGN.
16. RIPRAP
17. 18" CMP CULVERT WITH SLOPED END SECTIONS AND SAFETY BARS. SEE UTILITY PLAN
18. 30' FLAG POLE, 4" CONCRETE APRON AND FLAG POLE LIGHTS. SEE ELECTRICAL PLANS.
19. STOP SIGN FURNISHED AND INSTALLED BY OTHERS (NOT IN CONTRACT)
20. DOWNSPOUT EXTENSION AND PRECAST CONCRETE SPLASH PAD
21. PARKING STALLS SHOWN FOR REFERENCE ONLY (NO MARKINGS).
22. NORTH AREA OF PARKING LOT TO SERVE AS PULL-THRU PARKING FOR BUSES, RVs, ETC. AND AS FLEX PARKING AREA FOR VISITORS.
23. FURNISH AND INSTALL NEW BRACE POST ASSEMBLIES (2) AND LINE POSTS PER SOUTH DAKOTA DOT SPECIFICATIONS. RE-STING AND CONNECT EXISTING FENCE WIRE TO NEW POSTS.
24. "OVERSIZE VEHICLE" PARKING SIGN





C:\dowl_pw\0393906\SC-CS-SP-27083.dwg

HURON WMD				SUB-SHEET	
CIVIL SITE PLAN				C301	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED MH	DRAWN JB	CHECKED BD	DATE 2022.04.29	SHEET 5 OF 74	





GRADING PLAN NOTES

1. SURFACE CONTOURS BASED ON TOPOGRAPHICAL SURVEY PERFORMED BY DOWL OCTOBER 2021
2. FINISH CONTOURS ARE TO TOP OF FINISHED GRADE.
3. CURB ELEVATIONS ARE FLOW LINE (FL) OR TOP BACK OF CURB (TBC) AS LABELED.
4. TOP OF CURB IS 6" ABOVE CURB FLOW LINE UNLESS OTHERWISE NOTED.
5. DISTURBED AREAS SHALL BE PREPARED FOR SEEDING. RE-SEEDING SHALL BE CONDUCTED BY USFWS PERSONNEL.



C:\dowl_pw\0393906\SC-CS-GR-27083.dwg


HURON WMD				SUB-SHEET	
GRADING PLAN				C401	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED MH	DRAWN JB	CHECKED BD	DATE 2022.04.29	SHEET 6 OF 74	




HURON WMD				SUB-SHEET	
GRADING DETAIL				C402	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED MH	DRAWN JB	CHECKED BD	DATE 2022.04.29	SHEET 7 OF 74	



C:\dowl_pw\0393906\SC-CS-GR-DT-27083.dwg




- ### KEYNOTES
- 1500 GALLON SEPTIC TANK PER UTILITY DETAILS SHEET.
 - 4" SCH40 SANITARY SEWER LINE. CONNECT TO BUILDING SANITARY SEWER, SEE PLUMBING PLANS.
 - 4" X 2-WAY SANITARY CLEANOUT PER DETAIL 3, SHEET C503.
 - 2" SCH40 SANITARY SEWER FORCE MAIN.
 - 2" X 2-WAY SANITARY SEWER CLEANOUT WITH BALL VALVES PER DETAIL 4, SHEET C503.
 - DUPLEX LIFT STATION AND CONTROL PANEL PER DETAIL 2, SHEET C503. SEE ELECTRICAL PLANS
 - EVAPOTRANSPIRATION TREATMENT BED PER DETAILS ON SHEET C502.
 - WATER MAIN, CURB STOP AND METER PIT. CONTRACTOR TO COORDINATE WITH MID-DAKOTA RURAL WATER DISTRICT AS NECESSARY.
 - 2" DR 11 HDPE WATER SERVICE FROM METER PIT TO BUILDING WATER SERVICE. FURNISH AND INSTALL TRANSITION FITTINGS AT CONNECTION POINTS.
 - CONNECT TO BUILDING WATER PER PLANS
 - 18" CMP CULVERT WITH SLOPED ENDS AND SAFETY BARS. SEE SHEET C507.
 - TWO - 1,000 GALLON PROPANE TANKS. SEE PLUMBING PLANS.
 - GAS LINE FROM PROPANE TANK TO GENERATOR AND MECHANICAL ROOM. LENGTH PER PLAN. SEE PLUMBING PLANS FOR BUILDING CONNECTION LOCATION AND STRUCTURAL PLANS FOR PROPANE SLAB PENETRATION.
 - FIBER OPTIC COMMUNICATION SERVICE. CONNECT TO EXISTING CONDUIT AND EXTEND TO IT ROOM PER ELECTRICAL SHEETS. CONTRACTOR TO COORDINATE WITH SANTEL AS NECESSARY FOR FIBER INSTALLATION.
 - ELECTRICAL SERVICE. SEE ELECTRICAL SHEETS FOR PRIMARY ELECTRICAL AND TRANSFORMER LOCATION. CONTRACTOR TO COORDINATE WITH NORTHWESTERN ENERGY AS NECESSARY.
 - BACKUP GENERATOR. SEE ELECTRICAL PLANS.
 - AIR HANDLING UNIT. SEE MECHANICAL PLANS.
 - UNDERGROUND ELECTRICAL. SEE ELECTRICAL SHEETS.
 - LIGHT POLE. SEE ELECTRICAL SHEETS.
 - FLOOD LIGHT. SEE ELECTRICAL SHEET.




C:\dowl_pw\0393906\SC-CS-UT-27083.dwg


HURON WMD		UTILITY PLAN		SUB-SHEET	
		MULTIPURPOSE BUILDING AND VISITOR CENTER		C501	
DESIGNED MH	DRAWN JB	CHECKED BD	DATE 2022.04.29	SHEET 8 OF 74	




1 E.T. BED PLAN
C502 NOT TO SCALE




2 OBSERVATION PIPE DETAIL
C502 NOT TO SCALE




4 FLUSHING ASSEMBLY DETAIL
C502 NOT TO SCALE




3 DISTRIBUTION VALVE ASSEMBLY
C502 NOT TO SCALE




5 DIVERSION SWALE DETAIL
C502 NOT TO SCALE



6 E.T. BED PROFILE
C502 NOT TO SCALE




7 E.T. BED SECTION
C502 NOT TO SCALE




8 DISTRIBUTION LATERAL DETAIL
C502 NOT TO SCALE

EVAPOTRANSPIRATION (ET) BED NOTES:


- CONTRACTOR SHALL VERIFY ET BED LAYOUT AND FINISH FLOOR ELEVATIONS WITH ENGINEER PRIOR TO EXCAVATION. TREATMENT BEDS TO BE CONSTRUCTED ON TEST PIT SITES AND MAY ONLY BE MOVED WITH ENGINEER'S APPROVAL.
- SCARIFY BOTTOM OF ET BED TO A DEPTH OF 6 INCHES, HAND RAKE AND LEVEL SCARIFIED AREA.
- EXCAVATION SHALL BE PROTECTED FROM ALL PEDESTRIAN, VEHICULAR, AND OTHER ACTIVITY THAT COULD CAUSE COMPACTION OF SOILS.
- PLACEMENT OF SAND AND GRAVEL MATERIALS SHOULD BE FROM EDGES TOWARD CENTER OF ET BED.
- TREATMENT BED SHALL BE PARALLEL TO CONTOURS; BOTTOM OF BED(S) AND PIPES MUST BE LEVEL.
- ROUTE SURFACE DRAINAGE AWAY FROM BED AREA.
- IRRIGATION WITHIN 50 FEET OF ET BED AREA SHOULD BE AVOIDED AS THIS MAY ADVERSELY IMPACT THE SYSTEM EFFICIENCY.
- PLANTING IN THE BED AREA SHALL BE DEEP-ROOTED, DROUGHT-RESISTANT NATIVE TYPE GRASSES REQUIRING MINIMAL WATERING.
- FINAL CONSTRUCTION SHALL BE PROTECTED FROM ALL VEHICULAR ACTIVITY AND ANY DISTURBANCE.




HURON WMD				SUB-SHEET	
UTILITY DETAILS				C502	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED MH	DRAWN JB	CHECKED BD	DATE 2022.04.29	SHEET 9 OF 74	




1 1500 GALLON SEPTIC TANK DETAIL
C503 NOT TO SCALE



2 DUPLEX LIFT STATION
C503 NOT TO SCALE




3 2-WAY 2-PORT CLEANOUT DETAIL
C503 NOT TO SCALE




4 2-WAY 2-PORT CLEANOUT WITH BALL VALVES DETAIL
C503 NOT TO SCALE

SEPTIC TANK AND LIFT STATION NOTES:

1. CONTRACTOR SHALL VERIFY FINAL LOCATION AND ELEVATION OF SEPTIC TANK AND LIFT STATION PRIOR TO ORDERING COMPONENTS AND INSTALLING THEM AT THE SITE.
2. SEPTIC TANK SHALL BE BALLASTED AS NECESSARY TO AVOID BOUANCY DUE TO HIGH GROUNDWATER AT ELEVATION 1315.00.
3. LIFT STATION VAULT SHALL BE BALLASTED TO AVOID BOUANCY DUE TO HIGH GROUNDWATER AT ELEVATION OF 1315.00.
4. DUPLEX LIFT STATION SHALL BE ZOELLER QLS SERIES DUPLEX 48" X 108" LIFT STATION WITH Z-RAIL, TWO ZOELLER 153, 0.5 HP, SINGLE PHASE, 60HZ PUMPS, OR APPROVED EQUAL. SYSTEM SHALL INCLUDE EXTERIOR RATED CONTROL PANEL WITH THREE FLOAT CONTROL SYSTEM, ALTERNATING LEAD/LAG OPERATION AND ALARM LIGHT.
5. FORCE MAIN SHALL BE INSTALLED WITH POSITIVE SLOPE THROUGHOUT ITS LENGTH WITH NO HIGH POINTS.
6. CONTRACTOR SHALL PRESSURE TEST FORCE MAIN BETWEEN LIFT STATION AND DISTRIBUTION VALVE AT 50 PSI FOR A MINIMUM OF 1/2 HOUR. IF PRESSURE DROPS MORE THAN 3 PSI, CONTRACTOR SHALL REPAIR AS REQUIRED AND RE-TEST.
7. CONTRACTOR SHALL PROVIDE NON-POTABLE WATER AND SHALL TEST OPERATION OF COMPLETED LIFT STATION, DISTRIBUTION VALVE AND PIPING. CYCLE THROUGH EACH ZONE A MINIMUM OF 3 TIMES AND VERIFY FLOW AT FLUSHING ASSEMBLIES.
8. CONTRACTOR SHALL PROVIDE LIFT STATION START UP, 1-DAY TRAINING OF OWNER PERSONNEL AND A LETTER CERTIFYING PROPER OPERATION AND INSTALLATION ALL PROVIDED BY MANUFACTURER'S AUTHORIZED REPRESENTATIVE.




5 SEWER AND FORCE MAIN PROFILE
C503 NOT TO SCALE




HURON WMD				SUB-SHEET	
UTILITY DETAILS				C503	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED MH	DRAWN JB	CHECKED BD	DATE 2022.04.29	SHEET 10 OF 74	


C:\dowl_pw\0393906\SA-CS-UT-DT-27083.dwg



1 TYPE 1 CURB RAMP (PERPENDICULAR CURB RAMP) NTS



2 TYPE 1 CURB RAMP (PERPENDICULAR CURB RAMP) NTS



4 TYPE B CONCRETE CURB NTS

TYPE B CONCRETE CURB				
TYPE	H (INCHES)	W (INCHES)	CUR. YD. PER LIN. FT.	CON. YD. PER LIN. FT.
B6	6	8	0.0353	28.4
B7	7	8-3/8	B6	26.1
B8	8	8-5/8	B6	24.1
B9	9	9	B6	22.3
B10	10	9-3/8	0.0485	20.6


GENERAL NOTES:

THE CONCRETE FOR THE TYPE B CONCRETE CURB WILL COMPLY WITH THE REQUIREMENTS OF THE SPECIFICATIONS FOR CLASS M6 CONCRETE.

A 1/2" PREFORMED EXPANSION JOINT FILLER WILL BE PLACED TRANSVERSELY IN THE FOLLOWING LOCATIONS:

- AT EACH JUNCTION BETWEEN THE RADIUS RETURN OF CURB AND CURB WHICH IS PARALLEL TO THE PROJECT CENTERLINE.
- AT EACH JUNCTION BETWEEN THE EXISTING CURB AND NEW CURB OR CURB AND GUTTER.
- AT EACH JUNCTION BETWEEN THE CURB AND EXISTING SIDEWALK TO THE DEPTH OF THE SIDEWALK.

SEE STANDARD PLATE 650.90 FOR CONTRACTION JOINTS IN THE CURB.



5 SCREEN WALL DETAIL NOT TO SCALE

GENERAL NOTES:

FOR ILLUSTRATIVE PURPOSE ONLY, TYPE 1 DETECTABLE WARNINGS ARE SHOWN IN THE DRAWINGS.

FOR ILLUSTRATIVE PURPOSE ONLY, PCC FILLET SECTIONS ARE SHOWN IN THE DRAWINGS. THE CURB RAMP DEPICTED ON THIS STANDARD PLATE MAY BE USED WITH A PCC FILLET SECTION OR CURB AND GUTTER.

FOR ILLUSTRATIVE PURPOSE ONLY, THE CURB RAMP LOCATION IS SHOWN AT THE CENTER OF A PCC FILLET SECTION. THE CURB RAMP WILL BE PLACED AT THE LOCATION STATED IN THE PLANS.

SIDEWALK WILL NOT BE PLACED ADJACENT TO THE CURB RAMP FLARES WHEN A 2-FOOT CURB TRANSITION IS USED UNLESS SHOWN OTHERWISE IN THE PLANS.

*CARE WILL BE TAKEN TO ENSURE A UNIFORM GRADE ON THE CURB RAMP, FREE OF SAGS AND SHORT GRADE CHANGES.

SURFACE TEXTURE OF THE CURB RAMP WILL BE OBTAINED BY COARSE BROOMING TRANSVERSE TO THE SLOPE OF THE CURB RAMP.


THE NORMAL GUTTER LINE PROFILE WILL BE MAINTAINED THROUGH THE AREA OF THE RAMP OPENING.

JOINTS WILL BE SAWED OR TOoled INTO THE CONCRETE ADJACENT TO THE DETECTABLE WARNINGS TO ALLEVIATE POSSIBLE CORNER CRACKING.


CARE WILL BE TAKEN TO ENSURE THAT THE SURFACE OF THE DETECTABLE WARNINGS ARE CLEAN AND MAINTAINS A UNIFORM COLOR.

THE DETECTABLE WARNINGS WILL BE CUT AS NECESSARY TO FIT THE PLAN SPECIFIED LIMITS OF THE DETECTABLE WARNINGS.

3 TYPE 1 CURB RAMP (PERPENDICULAR CURB RAMP) NTS




6 ADA PARKING SIGNAGE-VAN ACCESSIBLE NTS




7 CONCRETE CURB TAPER NTS




C:\dowl_p_w\0393906\SA-CS-DT-27083.dwg



1 JOINTS IN CONCRETE CURB AND GUTTER
C505 NTS




3 PCC SIDEWALK
C505 NTS




GENERAL NOTES:
 CONCRETE WILL BE CLASS M6 IN ACCORDANCE WITH SSDOT SPECIFICATIONS.
 REINFORCING STEEL WILL CONFORM TO ASTM A615, GRADE 60.
 STRUCTURAL STEEL WILL CONFORM TO ASTM A36. THE SIDEWALK DRAIN COVER WILL CONFORM TO ASTM A786.
 WELDING AND WELD INSPECTION WILL BE IN CONFORMANCE WITH THE CURRENT EDITION OF THE AWS D1.1 STRUCTURAL WELDING CODE-STEEL.
 THE COVER PLATE ASSEMBLY WILL BE GALVANIZED AFTER FABRICATION. GALVANIZING WILL BE IN ACCORDANCE WITH ASTM A123.


2 SIDEWALK DRAIN
C505 NTS




4 PCC SIDEWALK
C505 NTS




5 GRAVEL AGGREGATE SECTION
C505 NTS




6 CONCRETE SECTION
C505 NTS




7 CONTRACTION JOINT WITH DOWEL
C505 NTS




8 CONCRETE JOINT DETAIL
C505 NTS



9 ISOLATION JOINT
C505 NTS





10 REINFORCEMENT AT BOLLARD
C505 NTS



HURON WMD				SUB-SHEET	
SITE DETAILS				C505	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED MH	DRAWN JB	CHECKED BD	DATE 2022.04.29	SHEET 12 OF 74	


C:\dowl_pw_d0393906\SA-CS-DT-27083.dwg




GREEN BORDER AND LETTERING

1 PARKING SIGNAGE
C506 NTS

12" WIDE X 36" LONG
PRECAST CONCRETE SPLASH PAD




PLAN VIEW




ELEVATION VIEW

2 SPLASH PAD DETAILS
C506 NTS




3 ADA PARKING AREA AND SIDEWALKS
C506 SCALE: 1"=5'






4 HAND-PLACED RIPRAP DETAIL
C506 NTS


NOTES:
1. TOP OF RIPRAP TO BE AT FLOWLINE OR GRADE AS INDICATED ON PLAN (WITHIN VARIANCE GIVEN). RIPRAP PLACED ABOVE FINAL GRADE WILL NOT BE ACCEPTED.



HURON WMD				SUB-SHEET	
SITE DETAILS				C506	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED MH	DRAWN JB	CHECKED BD	DATE 2022.04.29	SHEET 13 OF 74	





- NOTES:**
- PORTIONS OF THIS PROJECT WILL BE CONSTRUCTED UNDER A SEPARATE CONTRACT BY THE FEDERAL HIGHWAYS ADMINISTRATION (FHWA) AS DESCRIBED HEREIN. USFWS CONTRACTOR (THIS CONTRACT) SHALL COORDINATE THEIR WORK WITH FHWA AND THEIR DESIGNATED CONTRACTOR. IT IS ANTICIPATED THIS USFWS CONTRACT WILL PRECEDE FHWA CONTRACT.
 - USFWS CONTRACTOR SHALL PERFORM ALL EARTHWORK, GRADING, CULVERT INSTALLATION AND EROSION CONTROL SHOWN ON PROJECT PLANS INCLUDING AREAS WITHIN HWY14 ROW.
 - USFWS CONTRACTOR SHALL BUILD, COMPACT AND MAINTAIN SUBGRADE DURING CONSTRUCTION AND PROVIDE FINISH GRADING AND COMPACTION OF SUBGRADE JUST PRIOR TO LEAVING PROJECT SITE.
 - USFWS CONTRACTOR SHALL FURNISH AND INSTALL CMP CULVERT WITH SLOPED ENDS AND SAFETY BARS PER SDDOT SECTION 450 AND APPLICABLE SECTION 450 STANDARD PLATES. CULVERT MATERIALS SHALL CONFORM TO SDDOT SECTION 990.
 - THE FOLLOWING ITEMS SHALL BE FURNISHED AND INSTALLED BY FHWA CONTRACTOR IN ACCORDANCE WITH FHWA FP-14 AND APPLICABLE SCRS:
 - SURFACE COURSE AGGREGATE SHALL BE PER SUBSECTION 703.05, CONFORMING TO TABLE 703-3.
 - GEOGRID SHALL BE PER SUBSECTION 714.03, CONFORMING TO TABLE 714-4.
 - FURNISH AND INSTALL 30" X 30" STOP SIGN, POST AND BREAKAWAY SUPPORT STUB INSTALLED PER SDDOT SECTION 632 AND APPLICABLE PLATES. SIGN MATERIALS SHALL CONFORM TO SDDOT SECTION 982.
 - FHWA CONTRACTOR SHALL PROVIDE FINISH GRADING AND FINAL CLEANUP OF ANY AREAS USED OR DISTURBED BY HIM DURING DRIVEWAY AND PARKING LOT CONSTRUCTION.



1 C507 HIGHWAY 14 APPROACH DETAILS

HURON WMD				SUB-SHEET	
DRIVEWAY AND PARKING LOT PROFILES				C507	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED MH	DRAWN JB	CHECKED BD	DATE 2022.04.29	SHEET 14 OF 74	




EROSION CONTROL LEGEND

(SF)	—(SF)—	SILT FENCE PER SD DOT STANDARD PLATE #734.05 ON SHEET C603
(TW)	[U-shaped symbol]	CONCRETE TRUCK WASHOUT PER DETAIL ON SHEET C603
(W)	[wavy line symbol]	EROSION CONTROL WATTLE

RETENTION BASIN
BOTTOM ELEVATION = 1317.00

NEW MULTIPURPOSE BUILDING
AND VISITOR CENTER
F.F. ELEV. = 1324.00

GRADING LIMIT



HURON WMD				SUB-SHEET
EROSION CONTROL PLAN				C601
MULTIPURPOSE BUILDING AND VISITOR CENTER				
DESIGNED MH	DRAWN JB	CHECKED BD	DATE 2022.04.29	SHEET 15 OF 74


C:\dowl_pw\0393906\SC-CS-EC-27083.dwg

ABBREVIATIONS

A	AMPERE	BRDG	BRIDGING	COMP	COMPACTED	DVTL	DOVETAIL	FH	FIRE HYDRANT, FLATE HEAD	GPT	GYPSUM TILE	PVC	POLYVINYL CHLORIDE
AAV	AUTOMATIC AIR VENT	BRG	BEARING	COMPT	COMPARTMENT	DWG	DRAWING	FHC	FIRE HOSE CABINET	GRP	GRASS REINFORCED PIPE	PVI	POINT OF VERTICAL INTERSECTION
A/C	AIR CONDITIONING	BRG PL	BEARING PLATE	CONC	CONCRETE	DWLS	DOWELS	FHMS	FLAT HEAD MACHINE SCREW	GRAN	GRADE LINE	QT	QUARTER
A/C UNIT	AIR CONDITIONING UNIT	BRK	BRICK	CONN	CONNECT	DWR	DRAWER	FHR	FIRE HOSE RACK	GR LN	GRADE LINE	QTR	QUARTER
AB	ANCHOR BOLT	BRKT	BRACKET	CONSTR	CONSTRUCTION	DWTR	DUMBWAITER	FHS	FIRE HOSE STATION	GRTG	GRATING	1/4 RND	QUARTER ROUND
ABV	ABOVE	BRZ	BRONZE	CONT	CONTINUE	DX	DIRECT EXPANSION	FHWS	FLAT HEAD WOOD SCREW	GYP	GYPSUM	R	RADIUS, RANGE, RIGHT, RISER
AC	ALTERNATING CURRENT	BS	BOTH SIDES	CONTR	CONTRACTOR	E	EAST, EASTING, ELECTRICAL	FIG	FIGURE	GYP BD	GYPSUM BOARD	RA	RETURN AIR
ACC	ACCESSIBLE	BSMT	BASEMENT	CORR	CORRIDOR	EA	EACH, EXHAUST AIR	FIN	FINISH	GYP PLAS	GYPSUM PLASTER	RA GR	RETURN AIR GRILLE
ACI	AMERICAN CONCRETE INSTITUTE	BTU	BRITISH THERMAL UNIT	COV	COVER	EAT	ENTERING AIR TEMPERATURE	FIN FLR	FINISH FLOOR	HB	HOSE BIBB	RAR	RETURN AIR REGISTER
ACP	ACCESS CONTROL POINT	BTUH	BTU PER HOUR	CPRS	COMPRESSIBLE	EF	EACH FACE, EXHAUST FAN	FIP	FEMALE IRON PIPE	HC	HOLLOW CORE	RB	RUBBER BASE, RESILIENT BASE
ACR	ACRYLIC PLASTIC	BTWN	BETWEEN	CPT	CARPET	EG	EXISTING GROUND	FIXT	FIXTURE	HCP	HANDICAPPED	RD	ROOF DRAIN
ACS DR	ACCESS DOOR	BUR	BUILT-UP ROOFING	CRS	COURSE(S)	EJ	EXPANSION JOINT	FJT	FLUSH JOINT	HDBD	HARDBOARD	RDG INS	RIGID INSULATION
ACS PNL	ACCESS PANEL	BVCS	BEGIN VERTICAL CURVE STATION	CS	CAST STONE	EL	ELEVATION - GRADE OR BUILDING	FL	FLOW LINE	HDW	HARDWARE	SA	SUPPLY AIR
ACST	ACOUSTIC	BVCE	BEGIN VERTICAL CURVE ELEVATION	CSK	COUNTERSUNK	ELEC	ELECTRIC	FLASH	FLASHING	HDWD	HARDWOOD	SB	SPLASH BLOCK
ACT	ACOUSTICAL CEILING TILE	BW	BOTH WAYS	CSMT	CASEMENT	EM	EXPANDED METAL	FLR	FLOORING	HK	HOOK(S)	SHT	SHEET
ADDM	ADDENDUM	CAB	CABINET	CSS	COMPACT SUBSTATION	EMD	ESTIMATED MAXIMUM DEMAND	FLEX	FLEXIBLE	HM	HOLLOW METAL	SHTHG	SHEATHING
ADH	ADHESIVE	CAP	CAPACITY	CT	CERAMIC TILE, CURRENT TRANSFORMER	EMER	EMERGENCY	FLG	FLOORING	HNDRL	HANDRAIL	SHV	SHELVING
ADJ	ADJACENT, ADJOINING, ADJUSTABLE	CB	CATCH BASIN, CIRCUIT BREAKER	C TO C	CENTER TO CENTER	ENCL	ENCLOSE(URE)	FLR PL	FLOOR PLATE	HORIZ	HORIZONTAL	SIM	SIMILAR
ADO	AUTOMATIC DOOR OPERATOR	CB	CATCH BASIN, CIRCUIT BREAKER	CTR	CENTER	ENTR	ENTRANCE, ENTERING	FLUOR	FLUORESCENT	HP	HIGH PRESSURE, HORSEPOWER	S&R	SHELF AND ROD
AF	AMP FRAME	CCT	CUBICLE CURTAIN TRACK	CU	CONDENSING UNIT	EP	ELECTRICAL PANELBOARD, END POINT	FN	FENCE	HPT	HIGH POINT	SS	SERVICE SINK, STANDING SEAM (ROOF)
AFB	ABOVE FINISHED FLOOR	CCTV	CLOSED CIRCUIT TELEVISION	CU FT	CUBIC FEET	EPDM	PROPYLENE-DIENE-MONOMER ROOF MEMBRANE	FOC	FACE OF CONCRETE	HR	HOUR	SST	STAINLESS STEEL
AGGR	AGGREGATE	CE	COVER ELEVATION	CUH	CUBIC FEET	EPDS	EMERGENCY POWER DOWN STATION/SWITCH	FOD	FOREIGN OBJECT DEBRIS	HS	HIGH STRENGTH	STD	STANDARD
AHR	ANCHOR	CEM	CEMENT	CULV	CULVERT	EPRF	EXPLOSION PROOF	FOF	FACE OF FINISH	HSVP	HIGH-STRENGTH GYPSUM PLASTER	STL	STEEL
AHU	AIR HANDLING UNIT	CEM PLAS	CEMENT PLASTER	CU YD	CUBIC YARDS	EPY	EPOXY COATING	FOM	FACE OF MASONRY	HSKPG	HOUSEKEEPING	STOR	STORAGE
AI	AREA INLET	CER	CERAMIC	CV	CEILING VENT, NON-SURGE CHECK VALVE W/ RATE OF FLOW CONTROLLER	EQ	EQUAL	FOS	FACE OF STUD	HT	HEIGHT	TBD	TO BE DETERMINED
AISC	AMERICAN INSTITUTE OF STEEL CONSTRUCTION	CFI	CONDUIT, CONCRETE CONDUCTIVE FLOORING	CW	COLD WATER	EQSP	EQUALLY SPACED	FT	FIRE PARTITION, FIREPROOF, FUELING PUMP	HTG	HEATING	T&G	TONGUE AND GROOVE
A.L.	ACTIVE LEAF	CFLG	COUNTERFLASHING	CYL	CYLINDER	EQUIP	EQUIPMENT	FR	FEET PER MINUTE	HTR	HEATER	TO	TOP OF
ALT	ALTERNATE	CFM	CUBIC FEET PER MINUTE	d	PENNY (AS IN NAIL - 10d)	ESCAL	ESCALATOR	FRG	FIRE RESISTANT, FRAME	HV	HIGH VOLTAGE	TOS	TOP OF SLAB, TOP OF STEEL
ALUM	ALUMINUM	CG	CORNER GUARD	DB	DRY BULB	ESO	EMERGENCY SHUT-OFF VALVE	FRM	FRAMING	HVAC	HEATING, VENTILATING AND AIR CONDITIONING	TOW	TOP OF WALL
AMB	AMBIENT	CH BD	CHALKBOARD	DBL	DOUBLE	EST	ESTIMATE(D)	FRG	FORGED	HVW	HEADWALL	TPD	TOILET PAPER DISPENSER
AMP	AMPERE	CHFR	CHAMFER	DBL ACT DR	DOUBLE ACTING DOOR	EVCS	END VERTICAL CURVE STATION	FRMG	FRAMING	IN	INCH	TPTN	TOILET PARTITION
ANOD	ANODIZE	CHIM	CHIMNEY	DC	DIRECT CURRENT	EVCE	END VERTICAL CURVE ELEVATION	FRT	FIRE-RETARDANT	INCL	INCLUDED	TV	TELEVISION
ANSI	AMERICAN NATIONAL STANDARDS INSTITUTE	CHK	CHECK	DCJ	DOWELED CONTROL JOINT	EW	EACH WAY	FS	FULL SIZE	INSF	INSULATING FILL	TYP	TYPICAL
APPD	APPROVED	CHR PL	CHROME PLATED	DCJ	DOWELED CONTROL JOINT	EWC	ELECTRIC WATER COOLER	FSCV	FILTER SEPARATOR CONTROL VALVE	INSUL	INSULATION	VB	VINYL BASE
APPROX	APPROXIMATE	CI	CAST IRON, CURB INLET	DC	DIRECT CURRENT	EWT	ENTERING WATER TEMPERATURE	FSI	FILTER SEPARATOR ISSUE	INT	INTERIOR	VCT	VINYL COMPOSITION TILE, VITRIFIED CLAY TILE
ARCH	ARCHITECT	CIP	CAST-IN-PLACE	DCJ	DOWELED CONTROL JOINT	EXC	EXCAVATE	FSR	FILTER SEPARATOR RECEIVING	INTM	INTERMEDIATE	WC	WATER CLOSET, WATER COLUMN
ARI	AMERICAN REFRIGERATION INSTITUTE	CIRC	CIRCULAR	DCJT	DUMMY CONTROL JOINT	EXH	EXHAUST	FT	FEET	JCT	JUNCTION	WD	WOOD, WOOD DOOR
ASB	ASBESTOS	CJ	CONSTRUCTION JOINT	DEGREE	DEGREE	EXH A	EXHAUST AIR	FTG	FOOTING	JKT	JOIST	WP	WATERPROOF(ING), WEATERPROOF, WORKING POINT
ASC	ABOVE SUSPENDED CEILING	CKT	CIRCUIT	DEPR	DEPRESSION	EXST	EXISTING	FTR	FIGHTER RAMP	KIT	KITCHEN	WRB	WARDROBE
ASPH	ASPHALT	CKT BRKR	CIRCUIT BREAKER	DEPT	DEPARTMENT	EXP BT	EXPANSION BOLT	FURG	FURRING	KPL	KICKPLATE	WT	WEIGHT
ATC	ACOUSTICAL TILE CEILING	CL	CENTER LINE	DET	DETAIL	EXT	EXTERIOR	FUT	FUTURE	L	ANGLE, LEFT, LINE	WWM	WELDED WIRE MESH
ATFP	ANTI-TERRORISM FORCE PROTECTION	CLG	CEILING	DF	DRINKING FOUNTAIN	F	FAHRENHEIT	FW	FIRE WATER	LAB	LABORATORY	WWR	WELDED WIRE REINFORCEMENT
AUTO	AUTOMATIC	CLG HT	CEILING HEIGHT	DFV	DEFUEL/FLUSH VALVE	FA	FIRE ALARM, FRESH AIR	FWC	FABRIC WALL COVERING	LAM	LAMINATE	XFR	TRANSFER
AVG	AVERAGE	CLGL	CLEAR GLASS	DH	DOUBLE HUNG, DUCT HEATER	FAC	FIRE APPARATUS CLOSET	G	NATURAL GAS	LAV	LAVATORY	XFMR	TRANSFORMER
AWG	AMERICAN WIRE GAUGE	CLJ	CONTROL JOINT	DIA	DIAMETER	FAI	FRESH AIR INTAKE	GA	GAGE	LBL	LABEL	ZCV	ZONE CONTROL VALVE
AWT	ACOUSTICAL WALL TREATMENT	CLL	CONTRACT LIMIT LINE	DIAG	DIAGONAL	F BRK	FIRE BRICK	GAL	GALLON(S)	LD	LOAD		
BB	BULLETIN BOARD	CLO	CLOSET	DJM	DIMENSION	FC	FACE BRICK	GALV	GALVANIZED	LG	LENGTH		
BC	BOOKCASE	CLOS	CLOSURE	DISC	DISCONNECT	FC BRK	FACE BRICK	GALV STL	GALVANIZED STEEL	LH	LEFT HAND(ED)		
BD	BOARD	CLR	CLEAR(ANCE)	DISP	DISPENSER	FCG	FACING	GB	GRAB BAR	LN	LINEAR		
BDRY	BOUNDARY	CLWG	CLEAR WIRED GLASS	DISTR PNL	DISTRIBUTION PANEL	FCJ	FLOOR CONSTRUCTION JOINT	GBB	GROUNDING BUSBAR (SECONDARY)	LKR	LOCKER		
BEJ	BRICK EXPANSION JOINT	CMP	CORRUGATED METAL PIPE	DM	DIMENSION	FCO	FLOOR CLEANOUT	GC	GENERAL CONTRACTOR	LMST	LIMESTONE		
BEV	BEVEL	CMPST	COMPOSITE	DL	DEAD LOAD	FCU	FAN COIL UNIT	GEN	GENERAL GENERATOR	LMT	LIMIT		
BJT	BED JOINT	CMU	CONCRETE MASONRY UNIT	DIV	DIVISION	FD	FLOOR DRAIN	GF	GROUND FACE	LNTL	LINTEL		
BL	BASELINE, BUILDING LINE	CND	CONDUIT	DMPF	DAMP PROOFING	FDMPR	FIRE DAMPER	GFCI	GROUND FAULT CIRCUIT INTERRUPTER	LR	LIVING ROOM		
BKR	BREAKER	CNR	CORNER	DMPR	DAMPER	FDTN	FOUNDATION	GFE	GOVERNMENT-FURNISHED EQUIPMENT	LVT	LUXURY VINYL TILE		
BLDG	BUILDING	CNTR	COUNTER	DMT	DEMOUNTABLE	FE	FINISH END	GFE/CI	GOVERNMENT-FURNISHED EQUIPMENT CONTRACTOR INSTALLED	LT	LEFT, LIGHT		
BLW	BELOW	CO	CLEANOUT	DN	DOWN	FEB	FIRE EXTINGUISHER BRACKET	GKT	GASKET(ED)	LT WT	LIGHTWEIGHT		
BM	BENCHMARK	CO2	CARBON DIOXIDE	DR	DOOR, DRAIN	FEC	FIRE EXTINGUISHER CABINET	GL	GLASS	LTG	LIGHTING		
BO	BOTTOM OF	COL	COLUMN	DRB	DRAINBOARD	FF	FACTORY FINISH, FINISH FLOOR	G, GND	GROUND	LTNG	LIGHTNING		
BOT	BOTTOM	COM	COMMON	DR CL	DOOR CLOSER	FFE	FINISH FLOOR ELEVATION	GPM	GALLONS PER MINUTE	LVR	LOUVER		
BRCG	BRACING	COMB	COMBUSTION	DS	DOUBLE STRENGTH (GLASS), DOWNSPOUT DRAIN TILE	FG	FINISHED GRADE			LWC	LIGHTWEIGHT CONCRETE		
				DT		FGL	FIBERGLASS			MATL	MATERIAL(S)		
										MAX	MAXIMUM		

RESTROOM ACCESSORY NOTES:


- MIRRORS MUST BE INSTALLED WITH THE BOTTOM EDGE OF THE REFLECTING SURFACE NO HIGHER THAN 40" ABOVE THE FINISH FLOOR. A SINGLE FULL-LENGTH MIRROR IS RECOMMENDED IN EACH WASHROOM BECAUSE IT CAN BE USED BY EVERYONE, INCLUDING CHILDREN.
- PAPER TOWEL DISPENSERS AND WASTE RECEPTACLES OR WARM-AIR HAND DRYERS SHOULD BE CONVENIENTLY LOCATED IN AN AREA THAT IS ACCESSIBLE TO WHEELCHAIRS, PREFERABLY ADJACENT TO A BARRIER-FREE LAVATORY. IT IS RECOMMENDED THAT ONE HAND DRYER BE MOUNTED WITH SUFFICIENT CLEAR FLOOR SPACE TO ALLOW BOTH LEFT AND RIGHT-HAND WHEELCHAIR APPROACHES; OR PROVIDE TWO DRYERS, ONE FOR EACH TYPE OF APPROACH. WHEN A SINGLE HAND DRYER IS INSTALLED IN A WASHROOM, IT IS RECOMMENDED THAT THE START BUTTON BE LOCATED 38" TO 40" ABOVE THE FINISH FLOOR. WHEN TWO OR MORE DRYERS ARE INSTALLED, MOUNT ONE DRYER SO ITS BUTTON IS 38" TO 40" ABOVE THE FINISH FLOOR; LOCATE OTHERS 41" TO 48".
- WASHROOM ACCESSORIES MUST NOT PROJECT MORE THAN 4" INTO A CLEAR ACCESS AISLE IF THEIR LEADING EDGE IS BETWEEN 27" AND 80" ABOVE THE FINISH FLOOR; IF THEIR LEADING EDGE IS AT OR BELOW 27", THEN THEY MAY PROJECT ANY AMOUNT AS LONG AS THE REQUIRED MINIMUM WIDTH OF AN ADJACENT CLEAR ACCESS AISLE IS MAINTAINED. THIS STANDARD IS SPECIFICALLY DESIGNED TO ENSURE DETECTION BY VISUALLY IMPAIRED PEOPLE. IT IS RECOMMENDED THAT ALL FLOOR-STANDING AND SURFACE-MOUNTED UNITS PROJECTING MORE THAN 4" BE LOCATED IN CORNERS, ALCOVES, OR BETWEEN OTHER STRUCTURAL ELEMENTS SO AS NOT TO BE A HAZARD TO VISUALLY IMPAIRED PEOPLE OR INTERFERE WITH ACCESS AISLES OR WHEELCHAIR TURNING AREAS. FULLY RECESSED ACCESSORIES ARE THE PREFERRED CHOICE THROUGHOUT UNIVERSALLY DESIGNED WASHROOMS.




1 MOUNTING HEIGHTS
1/4" = 1'-0"



C:\REVIT_2020_PROJECT_FILES\HURON_USFS_9822.rvt



1 LIFE SAFETY PLAN
3/32" = 1'-0"



APPLICABLE BUILDING CODES

IBC	INTERNATIONAL BUILDING CODE	2018
IEC	INTERNATIONAL ELECTRIC CODE	2017
IPC	INTERNATIONAL PLUMBING CODE	2018
ADA	AMERICANS WITH DISABILITIES ACT ACCESSIBILITY GUIDELINES	2010
NFPA 70	NATIONAL ELECTRICAL CODE	2017
NFPA 72	NATIONAL FIRE ALARM AND SIGNALING CODE	2019
NFPA 90A	STANDARD FOR THE INSTALLATION OF AIR-CONDITIONING AND VENTILATING SYSTEMS	2018
NFPA 101	LIFE SAFETY CODE	2018

USE GROUP / OCCUPANCY - Chapter 3 (IBC 2018)

B BUSINESS ENTIRE BUILDING 9,106 sq. ft. (GROSS AREA)

CONSTRUCTION TYPE - Chapter 6 (IBC 2018)

TYPE VB

FIRE SUPPRESSION - Chapter 9 (IBC 2018)

Non-Sprinklered

HEIGHT / STORIES - Chapter 5 (IBC 2018)

Allowable Height (Table 504.3): 40'-0" Designed Height: 25'-11" +/-
 Allowable Stories (Table 504.4): 2 Designed Stories: 1

AREA - Chapter 5 (IBC 2018)

Allowable Area (Table 506.2): B @ NS = 9,000 sq. ft.
 B @ S1 = 36,000 sq. ft.
 B @ SM = 27,000 sq. ft. Designed Area: 9,106 sq. ft.
 Allowable Area Increase by frontage: Aa=At+(NSxf) 15,750 sq. ft.

* PER CODE NO SPRINKLERS REQUIRED

OCCUPANCY SEPARATION - Chapter 5 - Table 508.4 (IBC 2018)

NONE REQUIRED

FIRE RESISTANCE RATINGS - Chapter 6 - Table 601 (IBC 2018)

Structural Frame	0
Bearing Walls	0
Interior	0
Exterior	0
Non-Bearing Walls and Partitions	0
Floor Construction	0
Roof Construction	0

EXTERIOR WALL RATINGS - Chapter 6 - Table 602 (IBC 2018)


Fire Separation Distance Greater than 30'	Type of Construction VB	Required 0	Designed 0
---	-------------------------	------------	------------

OCCUPANCY CALCULATIONS - Chapter 10 (Tables 1004.5, 1006.2.1, 1006.3.2, 1006.3.3(1), 1006.3.3(2)) - IBC 2018

OCCUPANT ANALYSIS

Mark	Name	Area	Area per Occupant	Occupant Count	Comments
100	VESTIBULE	82 SF	0	0	
101	HALL	73 SF	0	0	
102	JAN. CLS	55 SF	300	1	
103	RESTROOM	57 SF	0	0	
104	RESTROOM	57 SF	0	0	
105	VISITOR CONTACT	853 SF	150	6	
106	MECH/ELEC	294 SF	300	1	
107	CONF	518 SF	15	35	
108	ADMIN	111 SF	150	1	
109	STORAGE 3	206 SF	300	1	
110	REFUGE OPEN OFFICE	1641 SF	150	11	
111	OFFICE	114 SF	150	1	
112	OFFICE	116 SF	150	1	
113	LE OFFICE	114 SF	150	1	
114	HALL	64 SF	0	0	
115	RESTROOM	56 SF	0	0	
116	IT	44 SF	150	1	
117	STORAGE 2	136 SF	300	1	
118	BREAK	495 SF	150	4	
119	HALL	106 SF	0	0	
120	WORKROOM	249 SF	150	2	
121	LOCKER	132 SF	50	3	
122	STORAGE	146 SF	300	1	
123	REALTY OPEN OFFICE	1957 SF	150	14	
124	HALL	58 SF	0	0	
125	RESTROOM	54 SF	0	0	
126	JAN. CLS.	36 SF	300	1	
127	STORAGE 1	129 SF	300	1	
128	TEAM RM	115 SF	150	1	
129	OFFICE	116 SF	150	1	
130	OFFICE	116 SF	150	1	
131	OFFICE	116 SF	150	1	
Grand total		32	8417 SF	91	

EGRESS LEGEND



→ COMBINED OCCUPANT LOAD AT A GIVEN EXIT DOOR. THIS SUM EQUALS TOTAL OCCUPANT LOAD.
 # → OCCUPANT LOAD CAPACITY OF DOOR OR STAIR.
 THE CAPACITY OF DOORS IS DETERMINED AS FOLLOWS:
 CLEAR OPENING WIDTH IN INCHES DIVIDE BY 0.15.
 THE CAPACITY OF STAIRS IS DETERMINED AS FOLLOWS:
 WIDTH IN INCHES DIVIDE BY 0.20.



EXIT ACCESS TRAVEL DISTANCE - Chapter 10 - Table 1017.2 (IBC 2018)

B Occupancy	Non-Sprinklered	200 feet
	Fully Sprinklered	250 feet
	Maximum Distance	70 feet

EXIT WIDTH REQUIREMENTS - Chapter 10 - Section 1005 (IBC 2018)


Door Egress	# of Occ.	Inches/Occ.	Min. Width	# of Exits	Min. Width / Exit	Design Width
	-	0.15"	10.4"	5	36"	224"

PLUMBING FIXTURES - Chapter 29 - Table 2902.1 (IBC 2018)

Water Closets 1 per 25 for the first 50 and 1 per 50 for the remainder exceeding 50	Required (91 occupants) = 3	Provided = 4
Lavatories 1 per 40 for the first 80 and 1 per 80 for the remainder exceeding 80	Required (91 occupants) = 3	Provided = 4
Drinking Fountains 1 per 100	Required (91 occupants) = 1	Provided = 2
Other	Required = 1 Service Sink	Provided = 2

WALL TYPE SCHEDULE			
TYPE MARK	WIDTH	DESCRIPTION	COMMENTS
A	4 3/4"	5/8" GYP, 2x4 WOOD FRAMNG, 5/8" GYPSUM WALL BOARD	
B	4 3/4"	5/8" GYP, 2x4 WOOD FRAMING, SOUND BATT INSULATION, 5/8" GYPSUM WALL BOARD	
C	6 3/4"	2x6 WOOD FRAMING WITH SOUND BATT INSULATION, 5/8" GYP EACH SIDE	STC 50-PROVIDE RC-1 CHANNEL ONE SIDE OF WALL AT OFFICE AREAS
D	4 3/4"	2x4 WOOD STUD, SOUND BATT INSULATION, 5/8" GYPSUM WALL BOARD ABOVE WALL TILE (BOTH SIDES), WALL TILE ON 5/8" CEMENT BACKER BOARD (BOTH SIDES).	
E		2x4 WOOD STUD, SOUND BATT INSULATION, WALL TILE ON 5/8" CEMENT BOARD BELOW, 5/8" GYPSUM WALL BOARD ABOVE WALL TILE (RESTROOM SIDE), 5/8" GYPSUM WALL BOARD ON OTHER SIDE.	
F	5 1/2"	5/8" GYP, 2x4 WOOD FRAMING, SOUND BATT INSULATION, 3/4" RC-1 CHANNEL, 5/8" GYPSUM WALL BOARD	STC 50-PROVIDE RC-1 CHANNEL ONE SIDE OF WALL AT OFFICE AREAS
G	6 3/4"	1 HOUR 2x6 WOOD FRAMING WITH SOUND BATT INSULATION, 5/8" TYPE 'X' GYP EACH SIDE, RC-1 ON ONE SIDE OF WALL	STC 50-PROVIDE RC-1 CHANNEL ONE SIDE OF WALL AT OFFICE AREAS
G1	4 3/4"	1 HOUR 2x4 WOOD FRAMING WITH SOUND BATT INSULATION, 5/8" TYPE 'X' GYP EACH SIDE, RC-1 ON ONE SIDE OF WALL	STC 50-PROVIDE RC-1 CHANNEL ONE SIDE OF WALL AT OFFICE AREAS
H	5 1/2"	1 HR RATED, 5/8" GYP TYPE X ON BOTH SIDES, 2x4 WOOD FRAMING, SOUND BATT INSULATION, 3/4" RC-1 CHANNEL, WALL TILE ON 5/8" CEMENT BOARD ON SINK SIDE	STC 50-PROVIDE RC-1 CHANNEL ONE SIDE OF WALL AT OFFICE AREAS

- GENERAL NOTES:**
- COORDINATE BUILDING PLAN WITH SITE PLAN.
 - EXTERIOR WALL CONSTRUCTION ABOVE GRADE.
 - FIBER CEMENT BOARD SIDING, WEATHER BARRIER MEMBRANE, 8" SIPS PANELS, 5/8" TYPE "X" GYP BOARD AT INTERIOR.
 - WALLS ARE FULL HEIGHT TO UNDERSIDE OF STRUCTURE UNLESS NOTED OTHERWISE. ALLOW FOR DEFLECTION.
 - DIMENSIONS ARE TO FACE OF STUDS OR SIPS PANELS UNLESS NOTED OTHERWISE.
 - INTERIOR PARTITIONS ARE TYPE B UNLESS NOTED OTHERWISE.
 - WALL PENETRATIONS:
 - ALLOW FOR EXPANSION WHEN REQUIRED OR AS INDICATED BY OTHER DISCIPLINES.
 - DOOR RETURN - 4" ON HINGE SIDE UNLESS NOTED OTHERWISE.
 - FLOOR DRAINS: NOT ALL FLOOR DRAINS ARE SHOWN ON ARCHITECTURAL PLANS. SEE PLUMBING DRAWINGS FOR LOCATION AND TYPE OF ALL FLOOR DRAINS.
 - PROVIDE BLOCKING IN PARTITION WALLS AS FOLLOWS:
 - WOOD BLOCKING AND METAL REINFORCEMENT INSTALLED DURING CONSTRUCTION TO SUPPORT WALL HUNG ITEMS AND FIXTURES.
 - LOCKERS - PROVIDE ADDITIONAL BLOCKING IN WALLS FOR ATTACHMENT.
 - SIDEWALK, DOOR PADS AND STEPS, PAVEMENT GRADES AND ELEVATIONS TO BE COORDINATED WITH CIVIL DRAWINGS.
 - PROVIDE AND INSTALL NEW 20"x30" WALL ACCESS DOORS AT 12" ABOVE FINISH FLOOR. VERTICAL CENTERLINE OF ACCESS DOOR SHALL BE CENTERED ON THE HVAC DUCT LOCATED IN THE CHASE DIRECTLY BEHIND THE ACCESS DOOR - COORDINATE WITH MECHANICAL FOR LOCATION. ACCESS DOOR AND FRAME SHALL BE FABRICATED FROM 16 GAUGE, GALVANNEALD STEEL WITH A WHITE PRIME COAT FINISH, AND PAINTED TO MATCH THE ADJACENT GYPSUM WALL BOARD. DOORS SHALL HAVE ROUNDED SAFETY CORNERS AND A CONCEALED PIVOTING ROD HINGE. FRAME SHALL BE ONE PIECE CONSTRUCTION WITH NO MITERS OR WELDS ON THE FACE. LATCH SHALL BE SCREWDRIVER OPERATED. INSTALL PER MANUFACTURER'S RECOMMENDATIONS.



1 GROUND FLOOR PLAN
1/8" = 1'-0" GROSS AREA = 9,106 SF




C:\REVIT_2020_PROJECT_FILES\HURON_USFS_9922.rvt


HURON WMD				SUB-SHEET	
GROUND FLOOR PLAN				A100	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED CH	DRAWN CH	CHECKED CMC	DATE 2022.4.29	DRAWING NO.	SHEET 20 OF 74

ROOF PLAN NOTES:

1. COORDINATE LOCATIONS AND SIZE OF CURBS AND PENETRATIONS WITH STRUCTURAL ROOF FRAMING PLAN AND DISCIPLINE DRAWINGS.
2. PIPE PENETRATIONS SMALLER THAN 6" MAY NOT BE SHOWN. COORDINATE WITH DISCIPLINE DRAWINGS.
3. SOME MISCELLANEOUS ROOF PENETRATIONS NOT SPECIFICALLY SHOWN ON THIS DRAWING SHALL BE FLASHED AND SEALED ACCORDING TO DETAILS SHOWN, AND PER ROOFING MANUFACTURER'S RECOMMENDED GUIDE DETAILS.



1 ROOF PLAN
1/8" = 1'-0"



C:\REVIT_2020_PROJECT_FILES\HURON_USFS_9822.rvt


HURON WMD				SUB-SHEET	
ROOF PLAN				A101	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED CH	DRAWN CH	CHECKED CMC	DATE 2022.4.29	DRAWING NO.	SHEET 21 OF 74

RCP GENERAL NOTES:


1. CONTRACTOR TO FIELD VERIFY DIMENSIONS AND VERTICAL CONTROL POINTS PRIOR TO INSTALLATION OF CEILING SYSTEM.
2. CONTRACTOR SHALL PROMPTLY NOTIFY OWNER'S REPRESENTATIVE OF DISCREPANCIES IN WORK WHICH WILL AFFECT INSTALLATION OF CEILINGS AS SHOWN ON DRAWINGS.
3. GYP BOARD CEILINGS SHALL BE ATTACHED TO METAL FRAMING BELOW UNDERSIDE OF ROOF TRUSSES UNLESS NOTED OTHERWISE.
4. COORDINATE MECHANICAL, ELECTRICAL, AND FIRE PROTECTION SYSTEM INSTALLATION WITH RESPECTIVE DISCIPLINE DRAWINGS AND SPECIFICATIONS. CEILINGS SHALL BE 8'-0" A.F.F. UNLESS NOTED OTHERWISE.
5. REFERENCE SPECIFICATIONS AND ROOM FINISH SCHEDULE FOR CEILING TYPES AND FINISHES.
6. CONTRACTOR IS RESPONSIBLE FOR COORDINATION OF ABOVE CEILING WORK TO ENSURE CLEARANCES FOR SCHEDULED CEILING HEIGHTS.
7. SEE ELECTRICAL DRAWINGS FOR LIGHT FIXTURE LOCATION, TYPES, AND COUNT.

RCP LEGEND

	GYP BOARD		PENDANT LIGHTING
	ACT		PENDANT LIGHTING
	X-X' CEILING HEIGHT		FIXED LIGHTING
	CEILING SLOPE AS NOTED		SUPPLY AIR
	EXIT		RETURN AIR
	SMOKE DETECTOR		WALL MOUNTED LIGHT
	24x24" AP (ACCESS PANEL)		2'x4' LIGHT FIXTURE
	2'x4' LIGHT FIXTURE		2'x4' LIGHT FIXTURE



1 REFLECTED CEILING PLAN
1/8" = 1'-0"




C:\REVIT_2020_PROJECT_FLESHURON_USFS_9822.rvt


HURON WMD				SUB-SHEET	
REFLECTED CEILING PLAN				A120	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED CH	DRAWN CH	CHECKED CMC	DATE 2022.4.29	DRAWING NO.	SHEET 22 OF 74

GENERAL NOTES:


1. EXPOSED WOOD TRUSSES AND WOOD COLUMNS TO BE STAINED IN THE SAME COLOR.




1 NORTH ELEVATION
1/8" = 1'-0"




2 SOUTH ELEVATION
1/8" = 1'-0"



4 WEST ELEVATION
1/8" = 1'-0"




3 EAST ELEVATION
1/8" = 1'-0"




C:\REVIT_2020_PROJECT_FLESHURON_USFS_9922.rvt


HURON WMD					SUB-SHEET	
BUILDING ELEVATIONS					A200	
MULTIPURPOSE BUILDING AND VISITOR CENTER						
DESIGNED CH	DRAWN CH	CHECKED CMC	DATE 2022.4.29	DRAWING NO.	SHEET 23 OF 74	




1 BUILDING SECTION - 1
1/8" = 1'-0"




2 BUILDING SECTION - 2
1/8" = 1'-0"



3 BUILDING SECTION - 3
1/8" = 1'-0"




4 BUILDING SECTION 4
1/8" = 1'-0"




C:\AREVT_2020_PROJECT_FILES\HURON_USFS_9822.rvt


HURON WMD					SUB-SHEET
BUILDING AND WALL SECTIONS					A300
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED CH	DRAWN CH	CHECKED CMC	DATE 2022.4.29	DRAWING NO.	SHEET 24 OF 74




1 WALL SECTION @ CLERESTORY
1/2" = 1'-0"



2 SECTION THRU WALKWAY COVER
1/2" = 1'-0"




3 SECTION AT EXTERIOR COLUMN
1/2" = 1'-0"




C:\REVIT_2020_PROJECT_FILES\HURON_USFS_9822.rvt


HURON WMD				SUB-SHEET	
WALL SECTIONS				A301	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED CH	DRAWN CH	CHECKED CMC	DATE 2022.4.29	DRAWING NO.	SHEET 25 OF 74




2 TYPICAL FOUNDATION DETAIL
1" = 1'-0"




1 WALL SECTION
1/2" = 1'-0"




3 WALL SECTION - A
1/2" = 1'-0"



4 WALL SECTION - 4
1/2" = 1'-0"





5 WALL SECTION @ EAST PATIO
1/2" = 1'-0"




C:\REVIT_2020_PROJECT_FLESHURON_USFS_9822.rvt

HURON WMD					SUB-SHEET
WALL SECTIONS					A302
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED CH	DRAWN CH	CHECKED CMC	DATE 2022.4.29	DRAWING NO.	SHEET 26 OF 74




C:\REVIT_2020_PROJECT_FILES\HURON_USFS_9822.rvt

HURON WMD				SUB-SHEET	
WALL SECTIONS				A303	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED CH	DRAWN CH	CHECKED CMC	DATE 2022.4.29	DRAWING NO.	SHEET 27 OF 74




4 ENLARGED PLAN - ROOM 125
1/2" = 1'-0"


3 ENLARGED PLAN - ROOM 115
1/2" = 1'-0"




1 ENLARGED PLAN - ROOMS 102, 103, AND 104
1/2" = 1'-0"




6 ENLARGED PLAN - ROOM 121
1/2" = 1'-0"




7 ENLARGED COUNTER PLAN - ROOM 107
1/2" = 1'-0"



8 ENLARGED COUNTER PLAN - ROOM 118
1/2" = 1'-0"



5 ENLARGED PLAN - ROOM 108
1/2" = 1'-0"



TOILET ACCESSORY LEGEND	
MARK	DESCRIPTION
BCS	BABY CHANGING STATION
EHD	ELECTRIC HAND DRYER
GB	GRAB BAR
MG	MIRROR 24X36
MH	MOP AND BROOM HOLDER
PTD	PAPER TOWEL DISPENSER
RH	ROBE HOOK
SD	SOAP DISPENSER
TTD	TOILET TISSUE DISPENSER


ENLARGED FLOOR PLAN NOTES:

- WALLS ARE FULL HEIGHT TO UNDERSIDE OF STRUCTURE UNLESS NOTED OTHERWISE, ALLOW FOR DEFLECTION.
- DIMENSIONS ARE TO FACE OF STUDS OR SIPS PANELS UNLESS NOTED OTHERWISE.
- WALL PENETRATIONS:
A. ALLOW FOR EXPANSION WHEN REQUIRED OR AS INDICATED BY OTHER DISCIPLINES.
- INTERIOR PARTITIONS ARE TYPE A UNLESS NOTED OTHERWISE, SEE A100 FOR WALL TYPES.
- DOOR RETURN - MINIMUM OF 4" ON HINGE SIDE.
- FLOOR DRAINS: NOT ALL FLOOR DRAINS ARE SHOWN ON ARCHITECTURAL PLANS. SEE PLUMBING DRAWINGS FOR LOCATION AND TYPE OF FLOOR DRAINS.
- PROVIDE BLOCKING IN PARTITION WALLS AS FOLLOWS:
A. WOOD BLOCKING AND METAL REINFORCEMENT INSTALLED DURING CONSTRUCTION TO SUPPORT WALL HUNG ITEMS AND FIXTURES.
- SEE SPECIFICATIONS FOR TOILET ACCESSORIES.




C:\AREVT_2020_PROJECT_FILES\HURON_USFS_9822.rvt


HURON WMD				SUB-SHEET	
ENLARGED FLOOR PLANS				A400	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED CH	DRAWN CH	CHECKED CMC	DATE 2022.4.29	DRAWING NO.	SHEET 28 OF 74




4 RESTROOM 103 - WEST
1/2" = 1'-0"




3 RESTROOM 103 - SOUTH
1/2" = 1'-0"




2 RESTROOM 103 - EAST
1/2" = 1'-0"




1 RESTROOM 103 - NORTH
1/2" = 1'-0"




8 RESTROOM 115 - WEST
1/2" = 1'-0"




7 RESTROOM 115 - SOUTH
1/2" = 1'-0"




6 RESTROOM 115 - EAST
1/2" = 1'-0"




5 RESTROOM 115 - NORTH
1/2" = 1'-0"



10 JAN CLS 102 - NORTH
1/2" = 1'-0"




9 JAN CLS 102 - WEST
1/2" = 1'-0"




C:\REVIT_2020_PROJECT_FILES\HURON_USFS_9822.rvt

HURON WMD				SUB-SHEET	
INTERIOR ELEVATIONS				A401	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED CH	DRAWN CH	CHECKED CMC	DATE 2022.4.29	DRAWING NO.	SHEET 29 OF 74


C:\REVIT_2020_PROJECT_FILES\HURON_USFS_9822.rvt




4 ADMIN 108 - WEST
1/2" = 1'-0"




3 ADMIN 108 - NORTH
1/2" = 1'-0"




2 INTERIOR ADMIN ELEVATION 108 - EAST
1/2" = 1'-0"




1 INTERIOR ELEVATION LOCKER - WEST
1/2" = 1'-0"




7 CONF ROOM 107 - EAST
1/2" = 1'-0"




6 BREAK ROOM
1/2" = 1'-0"




5 INTERIOR ELEVATION LOCKER - EAST
1/2" = 1'-0"



10 WORKROOM 120 - WEST
1/2" = 1'-0"




9 WORKROOM 120 - EAST
1/2" = 1'-0"




8 WORKROOM 120 - NORTH
1/2" = 1'-0"

CASEWORK NOTES:

1. SEE SHEET A500 FOR TYPICAL CASEWORK SECTIONS.
2. ALL CABINETS ARE RED OAK - SEE 9/A500 FOR CASEWORK STYLE.
3. "FINISH EDGE" ABBREVIATED TO "FE" - THIS SHEET ONLY.




HURON WMD				SUB-SHEET	
INTERIOR ELEVATIONS				A402	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED CH	DRAWN CH	CHECKED CMC	DATE 2022.4.29	DRAWING NO.	SHEET 30 OF 74



SIGN MOUNT LOCATION 1
SIGN LOCATION FOR ADA COMPLIANCE. MOUNT SIGN ON LATCH SIDE OF DOOR. CENTER SIGN HORIZONTALLY WITHIN THE 18" CLEARANCE FOR ADA. SIGN SHOULD BE MOUNTED SO BOTTOM OF LOWEST TACTILE CHARACTER IS 48" AFF MINIMUM.

SIGN MOUNT LOCATION 2
CENTER SIGN ON DOOR. FIELD ADJUSTMENTS MAY BE NEEDED TO ACCOMMODATE EXISTING OBSTACLES. SIGNS SPECIFIED WITH THIS MOUNT SHOULD BE INSTALLED SO BOTTOM OF LOWEST TACTILE CHARACTER IS 48" AFF MINIMUM UNLESS OTHERWISE NOTED. ALSO USE THIS LOCATION WHEN SIGN MOUNT LOCATION 1 CANNOT BE ACHIEVED.


SIGN MOUNT LOCATION 3
CENTER SIGN HORIZONTALLY WITHIN THE 18" CLEARANCE FOR ADA. MOUNT SIGN SO BOTTOM OF LOWEST TACTILE CHARACTER IS 48" AFF MINIMUM.



SIGN MOUNT LOCATION 4
SIGN LOCATION FOR ADA COMPLIANCE WHERE RELITE OCCURS. CENTER SIGN HORIZONTALLY WITHIN THE 18" CLEARANCE FOR ADA ADJACENT TO THE RELITE. SIGN SHOULD BE MOUNTED SO BOTTOM OF LOWEST TACTILE CHARACTER IS 48" AFF MINIMUM.


SIGN MOUNT LOCATION 5
SIGN LOCATION FOR ADA COMPLIANCE WITH WALL MOUNT FLAG SIGN OCCURS. MOUNT SIGN ON LATCH SIDE OF DOOR. CENTER SIGN HORIZONTALLY ABOVE IDENTITY SIGNAGE BELOW IF PRESENT. IF NO OTHER SIGNAGE IS PRESENT OR SIGN IS NOT LOCATED ADJACENT TO DOOR LOCATE 6" FROM DOOR JAMB OR WALL EDGE. SIGN SHOULD BE MOUNTED SO THAT BOTTOM OF SIGN IS 80" AFF MINIMUM.

1 SIGNAGE MOUNTING HT
3/8" = 1'-0"




MOUNT AT RESTROOM 103 IN SIGN MOUNT LOCATION 1, ADJACENT TO ALL-GENDER RESTROOM SIGN

2 CHANGING STATION SIGN
3" = 1'-0"




MOUNT AT ALL RESTROOMS IN SIGN MOUNT LOCATION 1

3 ALL GENDER SIGN
3" = 1'-0"




MOUNT AT ALL EXITS IN SIGN MOUNT LOCATION 1 OR 4

4 EXIT SIGN
3" = 1'-0"




MOUNT AT ALL EXTERIOR DOORS IN SIGN MOUNT LOCATION 1 OR 4

5 SIGN 2
3" = 1'-0"




C:\REVIT_2020_PROJECT_FILES\HURON_USFS_9922.rvt


HURON WMD					SUB-SHEET	
ADA SIGNAGE					A403	
MULTIPURPOSE BUILDING AND VISITOR CENTER						
DESIGNED CH	DRAWN CH	CHECKED CMC	DATE 2022.4.29	DRAWING NO.	SHEET 31 OF 74	




1 CASEWORK - TYP BASE CABINET
 1 1/2" = 1'-0"





2 ADA ACCESS SINK BASE
 1 1/2" = 1'-0"




3 CASEWORK - TYP UPPER CABINET
 1 1/2" = 1'-0"




4 CASEWORK - UPPER CABINET ABOVE SINK/MICROWAVE
 1 1/2" = 1'-0"




5 SHELVING1
 1" = 1'-0"




6 SHELF DETAIL
 1" = 1'-0"




7 RECEPTION DESK SECTION
 1" = 1'-0"




8 FLOOR TRANSITION DETAIL - CARPET TO LVT
 3" = 1'-0"



9 FLOOR TRANSITION - CONCRETE TO CPT
 3" = 1'-0"




10 CASEWORK STYLE
 1 1/2" = 1'-0"




C:\REVIT_2020_PROJECT_FILES\HURON_USFS_9822.rvt

HURON WMD					SUB-SHEET	
INTERIOR DETAILS					A500	
MULTIPURPOSE BUILDING AND VISITOR CENTER						
DESIGNED CH	DRAWN CH	CHECKED CMC	DATE 2022.4.29	DRAWING NO.	SHEET 32	OF 74


C:\REVIT_2020_PROJECT_FILES\HURON_USFS_9822.rvt




6 WALL CAP DETAIL
3" = 1'-0"




3 ROLLING COUNTER DOOR HEAD
1 1/2" = 1'-0"




4 ROLLING COUNTER DOOR JAMB
1 1/2" = 1'-0"




1 INTERIOR DOOR HEAD DETAIL
1 1/2" = 1'-0"



2 INTERIOR DOOR JAMB DETAIL
1 1/2" = 1'-0"




5 ROLLING COUNTER DOOR SILL
1 1/2" = 1'-0"




HURON WMD					SUB-SHEET	
INTERIOR DETAILS					A501	
MULTIPURPOSE BUILDING AND VISITOR CENTER						
DESIGNED CH	DRAWN CH	CHECKED CMC	DATE 2022.4.29	DRAWING NO.	SHEET 33 OF 74	


C:\REVIT_2020_PROJECT_FLESHURON_USFS_9822.rvt




13 STOREFRONT FRAME SILL1
1 1/2" = 1'-0"




10 LOUVER HEAD DETAIL
1 1/2" = 1'-0"




7 STOREFRONT FRAME HEAD
1 1/2" = 1'-0"




4 EXTERIOR DOOR HEAD DTL
1 1/2" = 1'-0"




1 WINDOW HEAD DETAIL
1 1/2" = 1'-0"




11 LOUVER JAMB DETAIL
1 1/2" = 1'-0"




8 STOREFRONT JAMB
1 1/2" = 1'-0"




5 EXTERIOR DOOR JAMB DTL
1 1/2" = 1'-0"




2 WINDOW JAMB DTL
1 1/2" = 1'-0"




12 LOUVER SILL DETAIL
1 1/2" = 1'-0"




15 STOREFRONT DOOR SILL1
1 1/2" = 1'-0"












6 EXTERIOR DOOR SILL DTL
1 1/2" = 1'-0"



3 WINDOW SILL DTL
1 1/2" = 1'-0"



HURON WMD				SUB-SHEET	
EXTERIOR DETAILS				A510	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED CH	DRAWN CH	CHECKED CMC	DATE 2022.4.29	DRAWING NO.	SHEET 34 OF 74




C:\AREVIT_2020_PROJECT_FILES\HURON_USFS_9922.rvt

HURON WMD				SUB-SHEET	
EXTERIOR DETAILS				A511	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED CH	DRAWN CH	CHECKED CMC	DATE 2022.4.29	DRAWING NO.	SHEET 35 OF 74


WINDOW SCHEDULE			
MARK	HEIGHT	WIDTH	TYPE
W1	4'-0"	2'-6"	CASEMENT WINDOW
W2	4'-0"	2'-6"	CASEMENT WINDOW
W3	2'-0"	5'-0"	FIXED WINDOW
W5	6'-0"	10'-6"	TRANSLUCENT PANEL

DOOR SCHEDULE														
DOOR NO.	DOOR PANEL		DOOR LEAF	DOOR PANEL MATL	DOOR TYPE	FRAME		DETAILS			GLAZING SIZE	DOOR RATING	HWDR SET	NOTES
	WIDTH	HEIGHT				TYPE	MATL	HEAD	JAMB	SILL				
100A	6'-0"	8'-0"	2	ALUM	1	D	ALUM	7/A501	8/A501	9/A501			03	2,6
100B	6'-0"	8'-0"	2	ALUM	1	E	ALUM	7/A501	8/A501	9/A501			04	5,6
102	3'-0"	7'-0"	1	HM	4	C	HM	1/A502	2/A502				13	8
103	3'-0"	7'-0"	1	WD	2	C	HM	1/A502	2/A502				09	
104	3'-0"	7'-0"	1	WD	2	C	HM	1/A502	2/A502				09	
105	6'-0"	8'-0"	2	ALUM	1	G	ALUM	7/A501	8/A501	9/A501			02	6
106	6'-0"	7'-0"	2	HM	2	C	HM	1/A502	2/A502				07	
107A	3'-0"	7'-0"	1	WD	2	A	HM	1/A502	2/A502				11	
107B	3'-0"	7'-0"	1	WD	2	B	HM	1/A502	2/A502				12	
107C	3'-0"	7'-0"	1	HM	2	C	HM	1/A502	2/A502			60 MIN	14	
108A	3'-1"	7'-0"	1	WD	2	-	-						15	4,7
108B	5'-0"	4'-2"	1	ST	5	-	ST	3/A502	4/A502	5/A502				3
109	3'-0"	7'-0"	1	WD	2	C	HM	1/A502	2/A502				11	
110A	3'-0"	7'-0"	1	WD	2	B	HM	1/A502	2/A502				11	
110B	3'-0"	7'-0"	1	WD	2	A	HM	1/A502	2/A502				11	
111	3'-0"	7'-0"	1	WD	2	A	HM	1/A502	2/A502				10	
112	3'-0"	7'-0"	1	WD	2	A	HM	1/A502	2/A502				10	
113	3'-0"	7'-0"	1	WD	2	B	HM	1/A502	2/A502				10	
115	3'-0"	7'-0"	1	WD	2	C	HM	1/A502	2/A502				09	
116	3'-0"	7'-0"	1	WD	4	C	HM	1/A502	2/A502				13	8
117	3'-0"	7'-0"	1	WD	2	C	HM	1/A502	2/A502				11	
118	3'-0"	7'-0"	1	WD	2	G	ALUM	1/A502	2/A502				08	
118B	3'-0"	7'-0"	1	ALUM	1	F	ALUM	1/A502	2/A502				01	
119	3'-0"	7'-0"	1	WD	2	A	HM	1/A502	2/A502				11	
121	3'-0"	7'-0"	1	HM	2	C	HM	4/A501	5/A-501	6/A-501			06	1, 2
122	3'-0"	7'-0"	1	WD	2	C	HM	4/A501	5/A-501				12	
123	3'-0"	7'-0"	1	HM	2	A	HM	4/A501	5/A-501	6/A-501			05	1
125	3'-0"	7'-0"	1	WD	2	C	HM	1/A502	2/A502				09	
126	3'-0"	7'-0"	1	HM	4	C	HM	1/A502	2/A502				13	8
127	3'-0"	7'-0"	1	HM	2	C	HM	1/A502	2/A502				11	
128	3'-0"	7'-0"	1	WD	2	A	HM	1/A502	2/A502				10	
129	3'-0"	7'-0"	1	WD	2	A	HM	1/A502	2/A502				10	
130	3'-0"	7'-0"	1	WD	2	B	HM	1/A502	2/A502				10	
131	3'-0"	7'-0"	1	WD	2	B	HM	1/A502	2/A502				10	


- NOTES:
 1. GALVANIZED AND INSULATED.
 2. PREP DOOR TO RECEIVE ACCESS CONTROL. ACCESS CONTROL BY OTHER.
 3. ROLLING COUNTER DOOR.
 4. POCKET DOOR.
 5. USE GLASS TYPE 1.
 6. REMOVABLE MULLION
 7. INSTALL TRIMS PER SPECIFICATION
 8. 12" x 12" LOUVER




W1 W2 W3 W5
 1 WINDOW TYPES
 1/4" = 1'-0"



A HOLLOW METAL - PRIME AND PAINT
 B HOLLOW METAL - PRIME AND PAINT
 C HOLLOW METAL - PRIME AND PAINT
 D ALUMINUM
 E ALUMINUM
 F ALUMINUM
 G ALUMINUM
 2 FRAME TYPE
 1/4" = 1'-0"




1 FULL GLASS
 2 FLUSH
 3 NOT USED
 4 LOUVERED
 5 ROLLING COUNTER DOORS
 3 DOOR TYPE
 1/4" = 1'-0"



C:\REVIT_2020_PROJECT_FILES\HURON_USFS_9822.rvt

HURON WMD					SUB-SHEET	
DOOR SCHED., DOOR & WINDOW ELEV.					A600	
MULTIPURPOSE BUILDING AND VISITOR CENTER						
DESIGNED CH	DRAWN CH	CHECKED CMC	DATE 2022.4.29	DRAWING NO.	SHEET 36 OF 74	


ROOM FINISH SCHEDULE							
ROOM NO.	ROOM NAME	FLOOR	WALL BASE	WALLS	CEILING		NOTES
					MATERIAL	HEIGHT	
100	VESTIBULE	LUXURY VINYL TILE	VINYL	GYP SUM	GYP SUM	10'-0"	
101	HALL	LUXURY VINYL TILE	VINYL	GYP SUM	GYP SUM	10'-0"	
102	JAN. CLS	LUXURY VINYL TILE	VINYL	GYP SUM	GYP SUM	10'-0"	
103	RESTROOM	LUXURY VINYL TILE	TCB	CERAMIC TILE/GYP SUM	GYP SUM	10'-0"	
104	RESTROOM	LUXURY VINYL TILE	TCB	CERAMIC TILE/GYP SUM	GYP SUM	10'-0"	
105	VISITOR CONTACT	LUXURY VINYL TILE	VINYL	GYP SUM	EXPOSED STRUCTURAL		
106	MECH/ELEC	SEALED CONCRETE	WOOD	GYP SUM	EXPOSED STRUCTURAL		
107	CONF	CARPET	WOOD	GYP SUM	ACT	8'-0"	
108	ADMIN	CARPET	WOOD	GYP SUM	ACT	8'-0"	
109	STORAGE 3	CARPET	WOOD	GYP SUM	ACT	8'-0"	
110	REFUGE OPEN OFFICE	CARPET	WOOD	GYP SUM	EXPOSED STRUCTURAL		
111	OFFICE	CARPET	WOOD	GYP SUM	GYP SUM	8'-0"	
112	OFFICE	CARPET	WOOD	GYP SUM	GYP SUM	8'-0"	
113	LE OFFICE	CARPET	WOOD	GYP SUM	GYP SUM	8'-0"	
114	HALL	CARPET	WOOD	GYP SUM	GYP SUM	8'-0"	
115	RESTROOM	LUXURY VINYL TILE	TCB	CERAMIC TILE/GYP SUM	GYP SUM	8'-0"	
116	IT	LUXURY VINYL TILE	VINYL	GYP SUM	EXPOSED STRUCTURAL		
117	STORAGE 2	LUXURY VINYL TILE	VINYL	GYP SUM	ACT	8'-0"	
118	BREAK	LUXURY VINYL TILE	VINYL	GYP SUM	ACT	8'-0"	
119	HALL	CARPET	WOOD	GYP SUM	GYP SUM	10'-0"	
120	WORKROOM	CARPET	WOOD	GYP SUM	GYP SUM	10'-0"	
121	LOCKER	LUXURY VINYL TILE	VINYL	GYP SUM	GYP SUM	10'-0"	
122	STORAGE	CARPET	WOOD	GYP SUM	ACT	8'-0"	
123	REALTY OPEN OFFICE	CARPET	WOOD	GYP SUM	EXPOSED STRUCTURAL		
124	HALL	CARPET	WOOD	GYP SUM	GYP SUM	8'-0"	
125	RESTROOM	LUXURY VINYL TILE	TCB	CERAMIC TILE/GYP SUM	GYP SUM	8'-0"	
126	JAN. CLS.	LUXURY VINYL TILE	VINYL	GYP SUM	GYP SUM	8'-0"	
127	STORAGE 1	LUXURY VINYL TILE	VINYL	GYP SUM	ACT	8'-0"	
128	TEAM RM	CARPET	WOOD	GYP SUM	ACT	8'-0"	
129	OFFICE	CARPET	WOOD	GYP SUM	GYP SUM	8'-0"	
130	OFFICE	CARPET	WOOD	GYP SUM	GYP SUM	8'-0"	
131	OFFICE	CARPET	WOOD	GYP SUM	GYP SUM	8'-0"	



FINISH LEGEND

	LUXURY VINYL TILE
	SEALED CONCRETE
	CARPET


1 ROOM FINISH FLOOR PLAN
1/8" = 1'-0"



C:\REVIT_2020_PROJECT_FILES\HURON_USFS_9822.rvt



HURON WMD					SUB-SHEET	
ROOM FINISH FLOOR PLAN					A800	
MULTIPURPOSE BUILDING AND VISITOR CENTER						
DESIGNED CH	DRAWN CH	CHECKED CMC	DATE 2022.4.29	DRAWING NO.	SHEET 37 OF 74	

C:\REVIT_2020_PROJECT_FILES\HURON_USFS_9822.rvt



1 FURNITURE PLAN
1/8" = 1'-0"

FOR REFERENCE ONLY



HURON WMD				SUB-SHEET	
FURNITURE PLAN				A801	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED CH	DRAWN CH	CHECKED CMC	DATE 2022.4.29	DRAWING NO.	SHEET 38 OF 74

STRUCTURAL GENERAL NOTES


- APPLICABLE SPECIFICATIONS AND CODES CONSTRUCTION AND DESIGN SHALL BE IN ACCORDANCE WITH THE INTERNATIONAL BUILDING CODE (IBC), 2018 EDITION, AND WITH THE LATEST EDITION OF THE APPLICABLE SPECIFICATIONS AND REQUIREMENTS NOTED AS FOLLOWS.
- SPECIAL INSPECTION
 - SOILS - TABLE 1705.6 OF THE IBC
 - PERIODIC INSPECTION OF FOUNDATION SOIL BEARING CAPACITY, DEPTH, FILL MATERIALS CLASSIFICATION AND SUBGRADE PREPARATION AND COMPACTION.
 - FULL TIME INSPECTION OF ENGINEERED FILL PLACEMENT AND COMPACTION.
 - CONCRETE - TABLE 1705.3 OF THE IBC
 - PERIODIC INSPECTION OF REINFORCEMENT BEFORE CONCRETE IS PLACED.
 - FULL TIME INSPECTION OF ANCHOR RODS AND OTHER EMBEDDED ITEMS AS IDENTIFIED HEREIN.
 - FULL TIME INSPECTION DURING PLACEMENT OF CONCRETE INCLUDING THE TAKING OF TEST SPECIMENS, SLUMP AND AIR CONTENT MEASUREMENT. INSPECTION AND TESTING SHALL BE LIMITED TO STRUCTURAL REINFORCED CONCRETE WITH TESTING FREQUENCY IN ACCORDANCE WITH THE PROJECT TECHNICAL SPECIFICATIONS.
 - STEEL - AISC 360 FOR STRUCTURAL STEEL, IBC SECTION 1705.2 FOR STEEL CONSTRUCTION OTHER THAN STRUCTURAL STEEL (COLD-FORMED STEEL, REBAR, ETC.)
 - FULL TIME INSPECTION FOR HIGH-STRENGTH BOLTING FOR SLIP CRITICAL CONNECTIONS PER AISC SPECIFICATION FOR STRUCTURAL JOINTS USING ASTM A325 OR A490 BOLTS.
 - PERIODIC INSPECTION FOR HIGH STRENGTH BOLTING FOR BEARING TYPE CONNECTIONS PER AISC SPECIFICATION FOR STRUCTURAL JOINTS USING ASTM A325 OR A490 BOLTS.
 - FULL TIME INSPECTION OF COMPLETE AND PARTIAL PENETRATION GROVE WELDS, MULTI-PASS FILLET WELDS AND SINGLE PASS FILLET WELDS GREATER THAN 5/16" IN ACCORDANCE WITH AWS D1.1.
 - PERIODIC INSPECTION OF FRAME JOINT DETAILS FOR COMPLIANCE WITH THE PLANS AND SPECIFICATIONS
 - WOOD
 - PERIODIC INSPECTION OF DIAPHRAGMS AND SHEAR WALLS FOR COMPLIANCE WITH PLANS AND SPECIFICATION REQUIREMENTS. INCLUDED IS THE SHEATHING TYPE AND THICKNESS; VERIFICATION OF FRAMING MEMBERS OF CONSTRUCTED ASSEMBLIES WITHIN THE FIELD AND AT BOUNDARY ELEMENTS; FASTENER TYPE, DIAMETER AND LENGTH; FASTENER SPACING AT INTERMEDIATE SUPPORTS AND AT BOUNDARY ELEMENTS.
 - PERIODIC INSPECTION OF HOLD DOWNS AND OTHER LATERAL FORCE RESISTING HARDWARE FOR CORRECT TYPE, FASTENING AND LOCATION.
- DESIGN LOADS
 - DESIGN LOADS AND LOAD APPLICATIONS SHALL BE IN ACCORDANCE WITH IBC.
 - UNIFORM FLOOR LIVE LOADS
 - ALL FLOOR AREAS, UNLESS OTHERWISE INDICATED --- 50 PSF + 10 PSF PARTITION
 - STAIRS, LANDINGS, CORRIDORS ----- 100 PSF
 - STORAGE ROOMS ----- 125 PSF
 - MECHANICAL ROOM ----- 150 PSF
 - FLOOR LIVE LOAD REDUCTIONS APPLIED IN ACCORDANCE WITH IBC.
 - ROOF LOADS
 - MINIMUM ROOF LIVE LOAD ----- 20 PSF
 - MINIMUM ROOF SNOW LOAD ----- 28 PSF
 - DRIFT SURCHARGE LOADS IN ACCORDANCE WITH ASCE 7.
 - BASIC GROUND SNOW LOAD ----- 40 PSF
 - IMPORTANCE FACTOR ----- I = 1.00
 - WIND LOADS IN ACCORDANCE WITH CHAPTER 26 OF ASCE 7
 - OCCUPANCY OR RISK CATEGORY ----- II
 - BASIC WIND SPEED (3-SEC GUST) ----- 113 MPH
 - EXPOSURE CATEGORY ----- C
 - SEISMIC LOADS
 - IMPORTANCE FACTOR ----- I = 1.00
 - MAPPED SPECTRAL RESPONSE S_s ----- 0.15
 - MAPPED SPECTRAL RESPONSE S_1 ----- 0.034
 - SITE CLASS ----- D
 - SPECTRAL RESPONSE COEFFICIENT S_{DS} ----- 0.16
 - SPECTRAL RESPONSE COEFFICIENT S_{D1} ----- 0.054
 - SEISMIC DESIGN CATEGORY ----- A
 - BASIC SEISMIC-FORCE-RESISTING SYSTEM ---- STRUCTURAL INSULATED PANEL SHEAR WALLS
 - DESIGN BASE SHEAR ----- 6.20 KIPS
 - SEISMIC RESPONSE COEFFICIENT C_s ----- 0.025
 - RESPONSE MODIFICATION FACTOR R ----- 6.5
 - ANALYSIS PROCEDURE USED ---- EQUIV. LATERAL FORCE SPECIAL LOADS
 - SPECIAL LOADS
 - MECHANICAL EQUIPMENT LOADS ----- ACTUAL OPERATING LOADS
 - CEILING FRAMING LIVE LOAD ----- 10 PSF
 - PARTITIONS AND INTERIOR WALLS LIVE LOAD ----- 5 PSF LATERAL
 - ADDITIONAL LOADS REFERENCED ON THE DRAWINGS.
 - BUILDING CONSTRUCTION TYPE - TYPE VB NR FRAMING

- CONSTRUCTION LOADS


STRUCTURES HAVE BEEN DESIGNED FOR DEAD LOADS AND THE DESIGN LOADS NOTED ABOVE. PROVIDE TEMPORARY BRACING, SHORING OR OTHER SUPPLEMENTAL SUPPORT DURING CONSTRUCTION AS NECESSARY TO PROTECT THE STRUCTURES FROM EXCESSIVE CONSTRUCTION LOADS.
- FOUNDATIONS
 - FOUNDATION DESIGN CRITERIA
 - MAXIMUM ALLOWABLE SOIL BEARING PRESSURE ----- 1,500 PSF
 - LATERAL SOIL PRESSURE ----- 60 PCF EQUIV. FLUID PRESSURE
 - DESIGN FROST DEPTH BELOW EXTERIOR GRADE ----- 42 INCH
 - AVOID EXCESSIVE WETTING OR DRYING OF THE FOUNDATION EXCAVATIONS DURING CONSTRUCTION.
 - BACKFILL ON WALLS WITH FILL ON BOTH SIDES SHALL BE COMPACTED IN EQUAL LIFTS EACH SIDE OF WALL. WALLS BACKFILLED FROM ONE SIDE ONLY SHALL HAVE ALL SUPPORTING SLABS, PERMANENT FRAMING OR TEMPORARY BRACING IN PLACE PRIOR TO PLACEMENT OF BACKFILL.
- CONCRETE
 - CONCRETE CONSTRUCTION SHALL CONFORM TO THE AMERICAN CONCRETE INSTITUTE BUILDING CODE REQUIREMENTS FOR REINFORCED CONCRETE (ACI 318)
 - DETAILING, FABRICATION AND PLACEMENT OF REINFORCEMENT SHALL CONFORM TO DETAILS AND DETAILING OF CONCRETE REINFORCEMENT (ACI 315)
 - MATERIALS
 - CONCRETE
 - STRUCTURAL CAST-IN-PLACE ----- $f_c = 4,000$ PSF
 - EXTERIOR WALKS, CURBS, RAMPS ----- $f_c = 3,000$ PSF
 - REINFORCING MATERIALS
 - REINFORCING BARS ----- ASTM A615, GRADE 60
 - WELDED WIRE FABRIC ----- ASTM A1064, GADE 70
 - ALL BENT REINFORCING BARS SHALL BE SHOP FABRICATED ONLY. REBENDING OR WELDING OF REINFORCEMENT SHALL NOT BE PERMITTED UNLESS AUTHORIZED BY ENGINEER.
 - END HOOKS IN REINFORCING BARS, SHOWN ON THE DRAWINGS BUT NOT DIMENSIONED, SHALL CONFORM TO ACI 318
 - CONCRETE COVER OVER REINFORCEMENT SHALL BE 2" CLEAR, EXCEPT FOR THE FOLLOWING, UNLESS OTHERWISE NOTED.
 - CONCRETE PLACED AGAINST AND PERMANENTLY IN CONTACT WITH EARTH ----- 3" CLEAR
 - CONCRETE NOT EXPOSED TO WEATHER OR IN CONTACT WITH EARTH OR WATER
 - BEAMS, COLUMNS ----- 1 1/2" CLEAR
 - WALLS ----- 1 1/2" CLEAR
 - SLABS ----- 3/4" CLEAR
 - REINFORCEMENT SPLICES NOT PERMITTED EXCEPT AS DETAILED OR AUTHORIZED BY THE ENGINEER. LAP REINFORCING BARS THE FOLLOWING MINIMUMS AT ALL SPLICES, CORNERS AND INTERSECTIONS, UNLESS OTHERWISE INDICATED. TOP BARS ARE HORIZONTAL BARS WITH MORE THAN 12" OF CONCRETE CAST BELOW THE BAR.

BAR SIZE	REG BARS	TOP BARS
#3	1' - 3"	1'-7"
#4	1' - 7"	2'-1"
#5	2' - 0"	2'-7"
 - LAP WELDED WIRE FABRIC ONE FULL MESH AT SPLICES.
 - STAGGER ADJACENT REINFORCEMENT LAP SPLICES IN WALLS 18" MINIMUM.
 - PROVIDE BAR SUPPORTS TO PROPERLY SECURE AND SUPPORT REINFORCING BARS AND WELDED WIRE FABRIC AT POSITIONS SHOWN ON THE DRAWINGS. IN ADDITION TO NORMAL ACCESSORIES PROVIDE #5 STANDEES AT 36" O.C. TO SUPPORT TOP REINFORCEMENT IN BASE SLABS, AND #3 U OR Z SHAPE SPACERS AT 72" O.C. EACH WAY IN WALLS WITH TWO CURTAINS OF REINFORCEMENT.
 - DOWELS, PIPES AND OTHER INSTALLED MATERIALS AND ACCESSORIES SHALL BE HELD SECURELY IN POSITION DURING CONCRETE PLACEMENT.
 - REINFORCING BARS AND ACCESSORIES SHALL NOT BE IN CONTACT WITH ANY PIPE, PIPE FLANGE OR METAL PART EMBEDDED IN CONCRETE. PROVIDE 2" CLEARANCE IN ALL CASES UNLESS OTHERWISE INDICATED. NO EMBEDDED ITEM SHALL BE SUSPENDED FROM, SUPPORTED BY, OR BRACED IN PLACE FROM THE STRUCTURAL REINFORCEMENT.
 - LOCATE CONSTRUCTION JOINTS WHERE SHOWN ON THE DRAWINGS OR AS AUTHORIZED THE ENGINEER. SLAB, JOISTS AND BEAMS SHALL NOT HAVE JOINTS IN A HORIZONTAL PLANE EXCEPT WHERE DETAILED ON DRAWINGS.
 - THOROUGHLY CLEAN BY SANDBLASTING ALL KEYWAYS AND CONSTRUCTION JOINTS PRIOR TO PLACING CONCRETE IN ADJACENT POUR.
 - BEGIN SPACING OF BARS WHICH PARALLEL CONSTRUCTION AND EXPANSION JOINTS 2" CLEAR EACH SIDE OF JOINT.
 - UNLESS OTHERWISE SHOWN, PLACE 2 - #5 (1 EACH FACE) WITH 2'-0" PROJECTIONS AROUND ALL OPENINGS IN CONCRETE WALLS OR SLABS.
 - PROVIDE AN ADDITIONAL 100 LINEAL FEET EACH OF #4 AND #5 REINFORCING BARS FOR USE AS DIRECTED DURING CONSTRUCTION.
 - CHAMFER ALL EXPOSED CONCRETE EDGES 3/4" UNLESS OTHERWISE INDICATED.
- SLABS ON GRADE
 - SLAB ON GRADE CONTROL JOINTS ARE DENOTED "CJ" ON DRAWINGS. SLAB ON GRADE CONSTRUCTION JOINTS ARE DENOTED "CONST JT." AT CONTRACTOR'S OPTION CONSTRUCTION JOINTS MAY BE SUBSTITUTED FOR CONTROL JOINTS.
 - LOCATE WELDED WIRE FABRIC 1 1/2" CLEAR FROM TOP OF SLAB.
 - PROVIDE 1 - #4 X 4'-0" PARALLEL TO EDGE OF SLAB OPPOSITE THE END OF ALL DISCONTINUED SLAB JOINTS, AND 1 - #4 X 4'-0" DIAGONAL BAR AT ALL REINFRANT CORNERS. PLACE BARS MID-DEPTH IN SLAB AND 2" CLEAR FROM EDGE OR CORNER.
 - SLOPE BOTTOM SURFACE OF SLABS AS NECESSARY TO MAINTAIN MINIMUM THICKNESS NOTED ON DRAWINGS FOR ALL SLABS WITH SLOPING TOP SURFACE OR DEPRESSION FOR TILE.

- STRUCTURAL STEEL
 - STRUCTURAL STEEL CONSTRUCTION SHALL CONFORM TO THE AMERICAN INSTITUTE OF STEEL CONSTRUCTION (AISC) SPECIFICATION FOR THE DESIGN, FABRICATION AND ERECTION OF STRUCTURAL STEEL BUILDINGS.
 - MATERIAL
 - STRUCTURAL STEEL W-SHAPES ----- ASTM A992, GRADE 50
 - STRUCTURAL STEEL PLATES, BARS, ANGLES, AND CHANNELS ----- ASTM A36
 - HOLLOW STRUCTURAL STEEL ----- ASTM A500, GRADE B
 - STEEL PIPE ----- ASTM A53, GRADE B
 - HIGH-STRENGTH BOLTS ----- ASTM A325
 - ANCHOR RODS ----- ASTM F1554, GRADE 36
 - HEADED ANCHOR STUDS (HAS) ----- ASTM A108, TYPE B
 - ALL STRUCTURAL STEEL BOLTED CONNECTIONS SHALL BE SNUG-TIGHTENED, 3/4" DIAMETER A325 - N BOLTS WITH STANDARD HOLTS, UNLESS OTHERWISE NOTED.
 - ALL WELDING SHALL CONFORM TO AMERICAN WELDING SOCIETY STRUCTURAL WELDING CODE - STEEL (AWS D1.1) AND SHALL BE PERFORMED BY WELDERS QUALIFIED BY THE APPROPRIATE AWS TEST FOR THE WELDING PERFORMED.
 - ALL STRUCTURAL STEEL DESIGNATED (AESS) ON DRAWINGS SHALL CONFORM TO AISC SPECIFICATIONS FOR ARCHITECTURALLY EXPOSED STRUCTURAL STEEL.
 - WOOD FRAMING
 - WOOD CONSTRUCTION SHALL CONFORM TO IBC
 - MATERIALS
 - STRUCTURAL LUMBER ----- DOUGLAS FIR-LARCH
 - 2" TO 4" THICK X 4" WIDE ----- STANDARD GRADE
 - 2" TO 4" THICK X 5" AND WIDER ----- NO.2 GRADE
 - PLYWOOD SHEATHING ----- APA RATED SHEATHING
 - FLOOR SHEATHING ----- 48/24 EXPOSURE 1
 - WALL SHEATHING ----- 24/0 EXPOSURE 1
 - ROOF SHEATHING ----- 40/20 EXPOSURE 1
 - STRUCTURAL GLUE-LAMINATED TIMBER
 - COMBINATION SYMBOL ----- DF 1.6 L2
 - CONDITION OF USE ----- DRY (MOISTURE CONTENT IN SERVICE LESS THAN 16%)
 - APPEARANCE GRADE ----- ARCHITECTURAL
 - MICRO LAM TIMBERS ----- TRUS JOIST CORP. OR EQUAL
 - MINIMUM THICKNESS ----- 1 3/4"
 - ALLOWABLE BENDING STRESS, $F_b = 2,600$ PSI
 - ALLOWABLE SHEAR STRESS, $F_v = 285$ PSI
 - ELASTIC MODULUS, $E = 2,000,000$ PSI
 - PREFABRICATED WOOD TRUSSES SHALL CONFORM TO THE TRUSS PLATE INSTITUTE DESIGN SPECIFICATIONS FOR METAL PLATE CONNECTED WOOD TRUSSES. TRUSSES SHALL BE DESIGNED BY MANUFACTURER TO SUPPORT ALL SUPERIMPOSED DEAD LOADS AND THE DESIGN LOADS NOTED HEREIN.
 - TRUSS CHORD MATERIALS TO BE HEM FIR NO. 1 OR BETTER
 - TRUSS GIRDER CHORDS TO BE DOUG FIR NO. 2 OR BETTER. MINIMUM CROSS SECTIONAL SIZES:
 - TOP CHORD ----- 2X6
 - WEB PANES ----- 2X4
 - BOTTOM CHORD ----- 2X10
- EQUIPMENT INSTALLATION
 - ALL OPENINGS SHOWN SHALL BE VERIFIED, AND ALL STRUCTURAL DIMENSIONS AND DETAILS PERTAINING TO EQUIPMENT INSTALLATION SHALL BE COORDINATED BY THE CONTRACTOR WITH THE ACTUAL EQUIPMENT FURNISHED.
 - EQUIPMENT SUPPORTS, ANCHORAGES AND OPENINGS NOT SHOWN ON THE STRUCTURAL DRAWINGS, BUT REQUIRED BY OTHER CONTRACT DRAWINGS, SHALL BE PROVIDED PRIOR TO PLACING CONCRETE.
- ARCHITECTURAL ELEVATION 0'-0" = CIVIL/STRUCTURAL ELEVATION 1324.00




STRUCTURAL ABBREVIATIONS					
A.B.	-ANCHOR BOLT	FAB.	-FABRICATE	PL	-PLATE
A/C	-AIR CONDITIONER	F.D.	-FLOOR DRAIN	PL PENETR.	-PENETRATION
ADJ.	-ADJACENT	FIN.	-FINISH	PERIM.	-PERIMETER
A.F.F.	-ABOVE FINISHED FLOOR	FLR.	-FLOOR	PERP.	-PERPENDICULAR
A.F.G.	-ABOVE FINISHED GRADE	FDN.	-FOUNDATION	PRIM.	-PRELIMINARY
AGGR.	-AGGREGATE	FRMG.	-FRAMING	PROJ.	-PROJECTION
AHU	-AIR HANDLING UNIT	FT.	-FOOT	PSF	-POUNDS PER SQUARE FOOT
ANCH.	-ANCHOR	FTG.	-FOOTING	PSI	-POUNDS PER SQUARE INCH
APPD	-APPROVED	GA.	-GAGE (OR GAUGE)	PT.	-POINT
APPROX.	-APPROXIMATE	GALV.	-GALVANIZED	QTY.	-QUANTITY
ARCHL.	-ARCHITECTURAL	G.L.	-GLULAM	R	-RADIUS
@	-AT	GR.	-GRADE BEAM	RD	-ROOF DRAIN
&	-AND	GYP.	-GYPSUM	REF.	-REFERENCE (REFER TO)
BCX	-BOTTOM CHORD EXTENSION	GWV	-GROSS VEHICLE WEIGHT	REIN.	-REINFORCEMENT
BLDG.	-BUILDING	H.S.	-HEADED STUD	REM.	-REMAINDER
BLK.	-BLOCK	HDR.	-HEADER	REQD.	-REQUIRED
BLKG.	-BLOCKING	HGR.	-HANGER	REQMT.	-REQUIREMENT
BM.	-BEAM	HORIZ.	-HORIZONTAL	RTU.	-ROOF TOP UNIT
B.O.W.	-BOTTOM OF WALL	HT.	-HEIGHT	S.	-SOUTH
BP	-BASE PLATE	I.F.	-INSIDE FACE	SCHED.	-SCHEDULE
BRG.	-BEARING	IN.	-INCH	SECT.	-SECTION
BSMT.	-BASEMENT	INFO.	-INFORMATION	SHIT.	-SHEET
CLR.	-CLEAR	INT.	-INTERIOR	SIMILAR	-SIMILAR
CMU	-CONCRETE MASONRY UNIT	INTERM.	-INTERMEDIATE	SJ	-SAWN JOINT (CONTROL JOINT)
COL.	-COLUMN	JST.	-JOIST	SP.	-SPACE
CONC.	-CONCRETE	JT.	-JOINT	SPEC.	-SPECIFICATIONS
CONN.	-CONNECTION	K.	-KIP (1000 LBS)	SO.	-SQUARE
CONST JT.	-CONSTRUCTION JOINT	KSF	-KIPS PER SQUARE FOOT	STD.	-STANDARD
CONT.	-CONTINUOUS	KSI	-KIPS PER SQUARE INCH	STIFF.	-STIFFENER
CONTR.	-CONTRACTOR	LAT.	-LATERAL	STGR.	-STAGGERED
COORD.	-COORDINATE	LBS.	-POUNDS	STL.	-STEEL
CONTRD.	-CENTERED	LDGR.	-LEDGER	STIR.	-STIRRUP
D.B.	-DIAGONAL BRACE	LL	-LIVE LOAD	STRUCT.	-STRUCTURAL
DBL	-DOUBLE	LLH	-LONG LEG HORIZONTAL	SUPT.	-SUPPORT
DET.	-DETAIL	LLV	-LONG LEG VERTICAL	SYMM.	-SYMMETRICAL
DIA. OR ()	-DIAMETER	LONG.	-LONGITUDINAL	T & B	-TOP AND BOTTOM
DIA.	-DIAGONAL	MATL.	-MATERIAL	TCX	-TOP CHORD EXTENSION
DIM.	-DIMENSION	MAX.	-MAXIMUM	TEMP.	-TEMPERATURE
DIST.	-DISTANCE	MC	-MOMENT CONNECTION	T & G	-TONGUE AND GROOVE
DL	-DEAD LOAD	MCJ	-MASONRY CONTROL JOINT	THK.	-THICKNESS
DWG.	-DRAWING	MCHL.	-MECHANICAL	TJI	-TRUSS JOIST
DWL.	-DOWEL	MEZZ.	-MEZZANINE	T.O.B.	-TOP OF BEAM
E.	-EAST	MFR.	-MANUFACTURER	T.O.S.C.	-TOP OF STRUCTURAL CONCRETE
EA.	-EACH	MIN.	-MINIMUM	T.O.F.	-TOP OF FOOTING
E.F.	-EACH FACE	MISC.	-MISCELLANEOUS	T.O.S.	-TOP OF STEEL
EL.	-ELEVATION	M.L.	-MICRO-LAM BEAM	T.O.W.	-TOP OF WALL
ELEC.	-ELECTRICAL	MTL.	-METAL	TRANSV.	-TRANSVERSE
ENGR.	-ENGINEER	N.	-NORTH	TS	-TUBULAR STEEL
EPS	-EXPANDED POLY-STYRENE	NO. OR #	-NUMBER	TYP.	-TYPICAL
EQ.	-EQUIP.	NOM.	-NOMINAL	U.N.O.	-UNLESS NOTED OTHERWISE
EXIST.	-EXISTING	N.S.	-NON-SHRINK	VAR.	-VARIES
EXP.	-EXPANSION	N.T.S.	-NOT TO SCALE	VERT.	-VERTICAL
EXT.	-EXTERIOR	O.C.	-ON CENTER	W.	-WEST
E.W.	-EACH WAY	O.D.	-OVERFLOW DRAIN	W/	-WITH
		O.F.	-OUTSIDE FACE	WD.	-WOOD
		O.H.	-OPPOSITE HAND	WL	-WIND LOAD
		OPNG.	-OPENING	W/O	-WITHOUT
		OPP.	-OPPOSITE	W.P.	-WORK POINT
				WT.	-WEIGHT
				W.W.F.	-WELDED WIRE FABRIC
				X.B.	-X-BRACE



- NOTES:**
- 'AS' = ADDITIONAL BARS EQUAL IN TOTAL NUMBER TO REGULAR REINFORCEMENT CUT BY THE OPENING. PLACE ONE-HALF TOTAL BARS TO EACH SIDE OF OPENING & IN THE SAME TRANSVERSE POSITION AS THE REGULAR REINFORCEMENT.
 - 'AS' BAR SIZE TO BE SAME AS REGULAR REINFORCEMENT IN EACH DIRECTION.
 - THIS DETAIL APPLIES UNLESS ADDITIONAL REINFORCEMENT SPECIFICALLY INDICATED AT OPENINGS ON DRAWINGS.
 - ADDITIONAL BARS TO PLACED AT OF WALL OR SLAB WHERE ONE LAYER OF REINFORCING IS PROVIDED AND AT EACH FACE WHERE TWO LAYERS OF REINFORCING ARE PROVIDED.
 - ADDITIONAL HORIZONTAL AND VERTICAL BARS ARE NOT NECESSARY FOR HOLES 8 TO 11 INCHES. USE ONLY THE DIAGONAL BARS. FOR HOLES SMALLER THAN 8 INCHES DO NOT CUT BARS, SPREAD NORMAL REINFORCING AROUND HOLE (NO DIAGONALS NEEDED).



R:\d0394\3371R20_27085-01_Huron MP.RVC_BSM.rvt



- FOUNDATION PLAN NOTES:**
- REF. S101 FOR ADDITIONAL NOTES. REF. ARCHITECTURAL FOUNDATION PLAN FOR ADDITIONAL INFORMATION.
 - REF. STRUCTURAL INSULATED PANELS (SIP) SHOP DRAWINGS FOR ADDITIONAL INFORMATION THAT IS OUTSIDE THE SCOPE OF THESE DRAWINGS.
 - GUTTERS AND DOWNSPOUTS SHALL BE PROVIDED TO DIRECT WATER AWAY FROM THE FOUNDATION AT ALL TIMES. FINISHED GRADE SHALL SLOPE AWAY FROM THE BUILDING AT A MINIMUM OF 2% FOR A DISTANCE OF 10 FEET.
 - GENERAL CONTRACTOR TO COORDINATE ALL OPENING, PIPE SLEEVES, EMBEDDED ITEMS, HANDRAILS, GRATING, ETC. WITH OTHER CONTRACT DOCUMENTS.
 - CONTRACTOR SHALL COORDINATE ALL TOP OF WALL AND BEARING PLATE ELEVATIONS WITH THE ARCHITECTURAL DRAWINGS. THE GENERAL CONTRACTOR SHALL ASSUME RESPONSIBILITY FOR ANY DISCREPANCIES.
 - SEE SITE PLAN FOR ALL FINAL GRADE ELEVATIONS.
 - GENERAL CONTRACTOR SHALL SUBMIT A CONSTRUCTION JOINT LOCATION PLAN TO THE STRUCTURAL ENGINEER FOR REVIEW PRIOR TO CONCRETE PLACEMENT.
 - MAINTAIN STRUCTURAL SLAB THICKNESS AT ALL FLOOR SLOPES AND DEPRESSIONS.
 - "AB1" STANDS FOR ANCHOR BOLT FOR HOLDOWN. USE 5/8"Ø F1554, GR 36 ALL THREAD W/ DOUBLE NUT AND WASHER EMBED IN FOOTING (MAINTAIN 3" CLR FROM BOTTOM). CENTER OF ANCHOR SHOULD BE 4-3/8" FROM END OF WOOD SHEAR WALL.
 - HORIZONTAL RIGID INSULATION NOT SHOWN FOR CLARITY. SEE J/S501 FOR PLAN AND LAYOUT.

1 PLAN VIEW
S201 FOUNDATION PLAN


FOUNDATION SCHEDULE				
ID	DEPTH	LENGTH	WIDTH	REINF.
WF1.5	0'-10"***	CONT	1'-6"	(3) #4 LONG.
F2.0	1'-0"	2'-0"	2'-0"	(3) #4 EA WAY
F3.0	1'-0"	3'-0"	3'-0"	(4) #4 EA WAY

***NOTE: DEPTH IS APPLICABLE AT INTERIOR THICKENED SLAB. SEE A/S501 FOR EXTERIOR DEPTH.



R:\d0394337R20_27085-01_Huron MP & VC_BSM.rvt

HURON WMD		SUB-SHEET	
STRUCTURAL FOUNDATION PLAN			
MULTIPURPOSE BUILDING & VISITOR CENTER			
DESIGNED SK	DRAWN SK	CHECKED MM	DATE 2022.04.29
			SHEET 40 OF 74



- MAIN LEVEL WOOD PLAN NOTES:**
- REF. S101 FOR ADDITIONAL NOTES. REF. ARCHITECTURAL ROOF PLAN FOR ADDITIONAL INFORMATION.
 - GUTTERS AND DOWNSPOUTS SHALL BE PROVIDED TO DIRECT WATER AWAY FROM THE FOUNDATION AT ALL TIMES. FINISHED GRADE SHALL SLOPE AWAY FROM THE BUILDING AT A MINIMUM OF 2% FOR A DISTANCE OF 10 FEET.
 - COORDINATE SIZE AND LOCATION OF OPENINGS IN FLOOR FRAMING WITH THE ARCHITECTURAL DRAWINGS.
 - CONTRACTOR SHALL COORDINATE ALL TOP OF WALL AND BEARING PLATE ELEVATIONS WITH THE ARCHITECTURAL DRAWINGS.
 - ALL NAILERS, LEDGERS, AND BEARING PLATES THAT ARE EXPOSED TO MOISTURE OR COME INTO CONTACT WITH THE CONCRETE SHALL BE PRESSURE TREATED LUMBER OF THE SIZE INDICATED ON THE STRUCTURAL DRAWINGS.
 - INDICATES THE LOCATION OF STRUCTURAL BEARING WALL.
 - INDICATES THE LOCATION OF SHEAR WALL. DASHED LINE INDICATES 1/2" PLYWOOD OR OSB (REF ARCH). PANEL EDGES TO BE FULLY BLOCKED AND ATTACHED WITH 10d COMMON NAILS AT 6" O.C. AT PANEL EDGES (EN) AND 12" O.C. FIELD NAILING (FN).
 - INDICATES STRUCTURAL INSULATED PANEL (SIP), DESIGNED BY OTHERS.




1 PLAN VIEW
S301 MAIN LEVEL FRAMING PLAN



R:\d0394337R20_27085-01_Huron MP & VC_BSM.rvt

HURON WMD		SUB-SHEET	
MAIN LEVEL FRAMING PLAN		S301	
MULTIPURPOSE BUILDING & VISITOR CENTER			
DESIGNED SK	DRAWN SK	CHECKED MM	DATE 2022.04.29
			SHEET 41 OF 74



- ROOF FRAMING CONSTRUCTION NOTES:**
1. REF. S101 FOR ADDITIONAL NOTES. REF. ARCHITECTURAL ROOF PLAN FOR ADDITIONAL INFORMATION.
 2. GUTTERS AND DOWNSPOUTS SHALL BE PROVIDED TO DIRECT WATER AWAY FROM THE FOUNDATION AT ALL TIMES. FINISHED GRADE SHALL SLOPE AWAY FROM THE BUILDING AT A MINIMUM OF 2% FOR A DISTANCE OF 10 FEET.
 3. COORDINATE SIZE AND LOCATION OF OPENINGS IN FLOOR FRAMING WITH THE ARCHITECTURAL DRAWINGS.
 4. CONTRACTOR SHALL COORDINATE ALL TOP OF WALL AND BEARING PLATE ELEVATIONS WITH THE ARCHITECTURAL DRAWINGS.
 5. ALL NAILERS, LEDGERS, AND BEARING PLATES THAT ARE EXPOSED TO MOISTURE OR COME INTO CONTACT WITH THE CONCRETE SHALL BE PRESSURE TREATED LUMBER OF THE SIZE INDICATED ON THE STRUCTURAL DRAWINGS.
 6. ----- INDICATES BEARING WALL BELOW. SEE S301 FOR ADDITIONAL INFO ON WALL TYPES
 7. ROOF DIAPHRAGM SHALL BE STRUCTURAL INSULATED PANEL (SIP) DESIGNED AND FASTENED BY OTHERS.


NOTES:
 1. ROOF DIAPHRAGM TO BE 8-1/4" STRUCTURAL INSULATED PANELS (SIP) DESIGNED BY OTHERS.

1 PLAN VIEW
 S401 ROOF FRAMING PLAN




R:\d0394\337R20_27085-01_Huron.MP&V.C_BSM.rvt


HURON WMD				SUB-SHEET	
ROOF FRAMING PLAN				S401	
MULTIPURPOSE BUILDING & VISITOR CENTER					
DESIGNED SK	DRAWN SK	CHECKED MM	DATE 2022.04.29	SHEET 42 OF 74	




A SECTION S501 TURNED-DOWN EDGE DETAIL




B SECTION S501 DOOR OPENING CONNECTION




C SECTION S501 EXTERIOR COLUMN CONNECTION




D SECTION S501 THICKENED SLAB DETAIL




E SECTION S501 ROOF TRUSS BEARING ON SIP PANEL




F SECTION S501 GABLE-END TRUSS DETAIL




G SECTION S501 ROOF GABLE DETAIL



H SECTION S501 INTERIOR BEARING WALL DETAIL




I SECTION S501 INTERIOR BEARING WALL DETAIL - GABLE ROOF



J PLAN VIEW S501 HORIZONTAL RIGID INSULATION LAYOUT


NOTES:
 1) HORIZONTAL RIGID INSULATION (HRI) IS DIMENSIONED, BUT SEE A/S501 FOR PLACEMENT
 2) HRI NEEDS TO HAVE A MINIMUM R-VALUE OF 8.6. THE MINIMUM VALUE ARE FOR PROTECTION AGAINST FROST DAMAGE. REF ARCH DWGS FOR ENERGY CONSERVATION REQUIREMENTS.
 3) HRI SHALL BE EXTRUDED POLYSTYRENE INSULATION.
 4) EXTERIOR SIDEWALK NOT SHOWN FOR CLARITY.



L SECTION S501 RADON COLLECTION PIT




R:\d0394337\R20_27085-01_Huron MP & VC_BSM.txd




NOTE:
SEE ROOF FRAMING PLAN
FOR TRUSS SPAN LENGTH


E SECTION
S502 EXPOSED EXTERIOR TRUSS




4 SECTION
S502 SHEATHED TRUSS CONN



L SECTION
S502 EXTERIOR TRUSS BEARING DETAIL



I SECTION
S502 RAFTER TO DROPPED BEAM CONNECTION




J SECTION
S502 TYPICAL HEADER DETAIL

HEADER SCHEDULE			
"W" OPENING	TYPE	TRIMMERS	KINGS
<4'-0"	(2)-2x6	1	1
4'-0" - 6'-0"	(2)-2x8	1	1
6'-0" - 8'-0"	(3)-2x10	2	2


NOTE: USE THESE SIZES WHEN NOTHING IS NOTED ON PLAN




R:\d0394337\R20_27085-01_Huron MP & VC_BSM.rvt




PLAN NORTH




A SECTION S503 GENERATOR PAD




D SECTION S503 FLAG POLE FOUNDATION




PLAN NORTH



B SECTION S503 PROPANE PAD



PLAN NORTH



C SECTION S503 BIN PAD



R:\d0394337R20_27085-01_Huron MP & VC_BSM.rvt

HURON WMD				SUB-SHEET	
STRUCTURAL SECTIONS & DETAILS				S503	
MULTIPURPOSE BUILDING & VISITOR CENTER					
DESIGNED SK	DRAWN SK	CHECKED MM	DATE 2022.04.29	SHEET 45 OF 74	

OUTDOOR PACKAGED AHU SCHEDULE (R-410A)

PLAN CODE	MANUF.	MODEL	SUPPLY FAN				DX COOLING DATA			GAS-FIRED HEAT EXCHANGER						EXHAUST FAN				ELECTRICAL			FRESH AIR CFM MIN	FILTER	COMMENTS	
			CFM MAX	ESP	RPM	HP	TOT./SENS. MBH	EAT DB/WB	LAT DB/WB	INPUT MBH	OUTPUT MBH	EAT DB	LAT DB	AFUE	TURN-D-OWN	APD, IN W.C.	CFM MAX	ESP	RPM	HP	MCA/MOCP	V				PHASE
AHU-1	AAON	RN-016-8-0-EB-09-34B	6400	3.5"	1959	10	195/171	78/63	52.5/50.9	270	219	24.3	97.8	80%	9:1	0.21	6400	1.0"	1760	5	118/125	208	3	1200	MERV8/13	OUTDOOR AHU

- NOTES:**
- PROVIDE UNIT WITH THE FOLLOWING, UNLESS OTHERWISE NOTED: FACTORY DISCONNECT, 100% O.A. ECONOMIZER, HEAD PRESSURE CONTROL PACKAGE, MODULATING GAS VALVE HEATING- MODULATING SCROLL COMPRESSOR COOLING, SUBBASE, HAILGUARDS, SERVICE LIGHTS, UV LIGHT KIT, AND ALL AVAILABLE STANDARD FEATURES AND COMPONENTS. SEE 237416.13 PARAGRAPH 2.14 FOR MORE INFORMATION.
 - PROVIDE WITH MODULATING COMPRESSORS AND GAS BURNER FOR CAPACITY CONTROL.
 - PROVIDE WITH FACTORY MOUNTED AND WIRED VAV CONTROLLER (AAON VCCX2 OR EQUAL WITH BACNET INTERFACE. COORDINATE POINT INTEGRATION.), REMOTE CONTROLLER SCREEN, AND VARIABLE SPEED DRIVES. PROVIDE UNIT WITH FULL OPERATION REMOTE CONTROLLER.
 - SEE 4/M301 FOR INSTALLATION DETAIL.
 - PROVIDE UNIT WITH 30" PLENUM CURB WITH BOTTOM SUPPLY AND RETURN CONNECTIONS.

VFD APPLICATION

EQUIPMENT	MOTOR	HP	SUPPLIED BY
AHU-1	SUPPLY FAN	10	AHU MANUFACTURER
AHU-1	EXHAUST FAN	5	AHU MANUFACTURER
HWP-1	PUMP MOTOR	2	T.C.
HWP-2	PUMP MOTOR	2	T.C.

- NOTES:**
- T.C. PROVIDED VFDs TO INCLUDE FACTORY BYPASS AND DISCONNECT. POWER BY E.C.

GLYCOL NOTES

THE HOT WATER SYSTEM SHALL BE CHARGED WITH A 35% SOLUTION OF GLYCOL. REFER TO THE PROJECT SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS.

ACCESS DOORS

PROVIDE DUCT ACCESS DOORS FOR ALL MOTORIZED DAMPERS AND LOUVERS TO ALLOW FOR ADEQUATE MAINTENANCE ACCESS

SITE ELEVATION

THE ELEVATION AT HURON HEADQUARTERS AND VISITOR CENTER, IS APPROXIMATELY 1280 FEET ABOVE SEA LEVEL. MAKE ALL EQUIPMENT SELECTIONS WITH THIS ELEVATION DERATE IN MIND.

EXPOSED DUCTWORK AND PIPING NOTE

- EXPOSED DUCTWORK AND TO BE DOUBLE-WALL SPIRAL WITH 1.5" INSULATION AND PAINTABLE FINISH. PAINTING BY G.C. COLOR SELECTION BY ARCH.
- ANY PIPING TO VIEW SHALL BE JACKETED WITH A PAINTABLE PVC JACKET.

EXCEPTIONS: MECHANICAL ROOM, JANITOR CLOSETS.

UNDERGROUND DUCTWORK NOTE

- UNDERGROUND DUCTWORK SHALL BE BLUE DUCT OR EQUIVALENT. INSTALL AND FUSE DUCTWORK WITH MANUFACTURER'S RECOMMENDED SYSTEM AND INSTALLATION INSTRUCTIONS.
- UNDERGROUND DUCTWORK TO BE PRESSURE TESTED TO INSURE NO INFILTRATION OF DUST/MOISTURE AFTER SYSTEM IS INSTALLED.

CONTROL NOTES

- TEMPERATURE CONTROL CONTRACTOR TO PROVIDE BOX AND CONDUIT TO ACCESSIBLE CEILING SPACE FOR EACH THERMOSTAT.
- PROVIDE A DDC CONTROL SYSTEM WITH WEB BASED INTERFACE FOR HVAC SYSTEM CONTROL.
- TEMPERATURE CONTROL CONTRACTOR TO PROVIDE AND WIRE RADIANT FLOOR SLAB TEMPERATURE SENSORS FOR RADIANT FLOOR SLAB TEMPERATURE SENSORS FOR RADIANT FLOOR HEAT SYSTEM OPERATION.

DUCTWORK CONSTRUCTION SCHEDULE

INSULATED DUCTWORK INCLUDES:

- ALL INTERIOR SUPPLY DUCTWORK
- ALL EXHAUST DUCTWORK FROM THE BACKDRAFT DAMPER TO THE BUILDING EXTERIOR.

UNINSULATED/UNLINED DUCTWORK INCLUDES:

- ALL OTHER INTERIOR EXHAUST DUCTWORK
- ALL INTERIOR RETURN DUCTWORK

LINED DUCTWORK INCLUDES:

- ALL TRANSFER DUCTWORK

NOTE: INSULATED FLEXIBLE DUCTWORK MAY BE USED AT THE CONTRACTOR'S OPTION FOR A MAXIMUM OF 5 FT. LENGTH TO EACH DIFFUSER/REGISTER/ GRILLE.

MECHANICAL SHEET LIST

M001	MECHANICAL COVER SHEET
M002	MECHANICAL SCHEDULES
M003	MECHANICAL SCHEDULES
M004	MECHANICAL SCHEDULES
M100	UNDERFLOOR MECHANICAL HVAC PLAN
M101	FIRST FLOOR MECHANICAL HVAC PLAN
M102	FIRST FLOOR MECHANICAL PIPING PLAN
M103	ROOF MECHANICAL PLAN
M104	MECHANICAL ZONE PLAN
M201	MECHANICAL SECTIONS AND ENLARGED PLANS
M301	MECHANICAL DETAILS
M302	MECHANICAL DETAILS
M303	MECHANICAL DETAILS
M304	MECHANICAL DETAILS

MECHANICAL SYMBOLS LEGEND

AIR TERMINALS, EQUIPMENT & SPECIALTIES

	NEW EQUIPMENT		EQUIPMENT TAG
	EXISTING TO REMAIN		TYPE OF EQUIPMENT
	SUPPLY AIR TERMINAL (NEW, EXIST., DEMO.)		EQUIPMENT NUMBER (REFER TO SCHEDULE)
	RETURN AIR TERMINAL (NEW, EXIST., DEMO.)		DIFFUSER/GRILLE TAG
	EXHAUST AIR TERMINAL (NEW, EXIST., DEMO.)		AIR TERMINAL CFM (REFER TO SCHEDULE)
	LINEAR SLOT AIR TERMINAL		WALL LOUVER
	PUMP		SIDEWALL AIR TERMINAL
	P.O.D.C. - POINT OF DISCONNECTION		T'STAT. (ELEC./PNEU.)
	P.O.C. - POINT OF CONNECTION		SWITCH

DUCTWORK & ACCESSORIES

	NEW DUCTWORK		INSIDE CLEAR DUCT SIZE: FIRST FIGURE INDICATED IS SIDE OF DUCT SHOWN
	EXISTING DUCTWORK TO REMAIN		DUCTWORK END CAP
	DUCT BREAK		FLEXIBLE DUCTWORK
	RISE IN DUCTWORK		SQUARE ELBOW UP SUPPLY/RETURN/EXH.
	FALL IN DUCTWORK		SQUARE ELBOW DN SUPPLY/RETURN/EXH.
	FIRE DAMPER		ROUND ELBOW UP SUPPLY/RETURN/EXH.
	SMOKE DAMPER		ROUND ELBOW DN SUPPLY/RETURN/EXH.
	FIRE/SMOKE DAMPER		SQUARE DIFFUSERS SUPPLY/RETURN/EXH.
	BACKDRAFT DAMPER		ROUND DIFFUSERS FULL / HALF
	MANUAL VOLUME DAMPER		INDICATED AIR FLOW SUPPLY / RETURN
	MOTORIZED DAMPER		DUCT REDUCER

DUCTWORK SHADING

	SUPPLY AIR		EXHAUST AIR
	RETURN AIR		OUTSIDE AIR

HVAC/HYDRONIC PIPING

	HWS	HOT WATER SUPPLY		CD	CONDENSATE DRAIN
	HWR	HOT WATER RETURN			

THIS IS A STANDARDIZED SYMBOLS LEGEND, ALL SYMBOLS SHOWN MAY NOT APPEAR ON OR WITHIN THIS SET OF CONTRACT DOCUMENTS.

ACE INC
 ASSOCIATED • CONSTRUCTION • ENGINEERING
 2040 HARNISH BLVD.
 BILLINGS, MT 59102
 406-245-0136
 ACE JOB 21BL5442



HURON FISH AND WILDLIFE					SUB-SHEET
MECHANICAL COVER SHEET					M001
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED AS	DRAWN TA	CHECKED TM	DATE 2022.04.29	DRAWING NO. 29320.07	SHEET 46 OF 74

GRILLE - REGISTER - DIFFUSER SCHEDULE

PLAN CODE	MANUFACTURER	MODEL NUMBER	FUNCTION	FACE SIZE	NECK SIZE	MATERIAL	FINISH	CFM	VOLUME DAMPER	REMARKS
CD-2	PRICE	SMCD	CEILING SUPPLY	12"x12"	6"	ALUMINUM	WHITE	SEE PLANS	IN DUCT	4-WAY THROW, MODULAR CORE WITH TOOL FREE RECONFIGURATION
CD-3	PRICE	SMCD	CEILING SUPPLY	12"x12"	8"	ALUMINUM	WHITE	SEE PLANS	IN DUCT	4-WAY THROW, MODULAR CORE WITH TOOL FREE RECONFIGURATION
RG-2	PRICE	PDDR	CEILING RETURN	12"x12"	6"	ALUMINUM	WHITE	SEE PLANS	IN DUCT	ARCHITECTURAL PERFORATED FACE RETURN GRILLE
RG-3	PRICE	PDDR	CEILING RETURN	12"x12"	8"	ALUMINUM	WHITE	SEE PLANS	IN DUCT	ARCHITECTURAL PERFORATED FACE RETURN GRILLE
RG-4	PRICE	PDDR	CEILING RELIEF	18"x18"	--	ALUMINUM	WHITE	SEE PLANS	--	ARCHITECTURAL PERFORATED FACE RELIEF GRILLE
DL-1	PRICE	HCD	SUPPLY DRUM LOUVER	6"x18"	--	ALUMINUM	WHITE	SEE PLANS	OBD IN GRILLE	DRUM LOUVER. BLADES TO BE FIELD ADJUSTED.
SSG-2	PRICE	20/30	SIDEWALL SUPPLY	12"x8"	--	ALUMINUM	WHITE	SEE PLANS	OBD IN GRILLE	SIDEWALL SUPPLY GRILLE. ADJUSTABLE BLADES WITH 3/4" BLADE SPACING.
SRG-1	PRICE	60/70	SIDEWALL RETURN	12"x8"	--	ALUMINUM	WHITE	SEE PLANS	OBD IN GRILLE	SIDEWALL RETURN GRILLE, 3/4" BLADE SPACING
SRG-2	PRICE	60/70	SIDEWALL RETURN	24"x10"	--	ALUMINUM	WHITE	SEE PLANS	OBD IN GRILLE	SIDEWALL RETURN GRILLE, 3/4" BLADE SPACING
SRG-3	PRICE	530	SIDEWALL RETURN	30"x36"	--	STEEL	WHITE	SEE PLANS	OBD IN GRILLE	SIDEWALL RETURN GRILLE, 3/4" BLADE SPACING
SRG-4	PRICE	530	SIDEWALL RETURN	32"x48"	--	STEEL	WHITE	SEE PLANS	OBD IN GRILLE	SIDEWALL RETURN GRILLE, 3/4" BLADE SPACING

NOTES:

1. PROVIDE ALL DUCT TRANSITIONS TO AND FROM GRILLES/REGISTERS/DIFFUSERS AS REQUIRED.
2. ALL GRILLE AND REGISTER COLORS TO BE COORDINATED WITH ARCHITECT.
3. CONTRACTOR TO VERIFY EXACT BUILDING CONSTRUCTION, CEILING, AND FLOOR TYPES AND PROVIDE THE CORRECT FRAMES FOR ALL AIR DIFFUSION PRODUCTS AS REQUIRED.
4. PROVIDE MANUAL VOLUME DAMPERS FOR CONNECTION TO ALL G/R/D'S. SEE DETAIL 2/M302.
5. SEE DRAWING FOR FURTHER G/R/D REQUIREMENTS.

CONDENSING BOILER SCHEDULE (35% PROPYLENE GLYCOL)

PLAN CODE	MANUFACTURER	MODEL NUMBER	BOILER TURNDOWN	MBH INPUT	MAX MBH OUTPUT	DESIGN GPM	BOILER MIN FLOW	EWT/LWT	W.P.D.	FLUE SIZE	C.A. SIZE	POWER	REMARKS
B-1, B-2	LOCHINVAR	FTXL400	10:1	399	364	36.4	10	130/150	3.5	4" CPVC	4" CPVC	120V 1 PHASE	FLOOR MOUNTED FIRE-TUBE BOILER SEE 1/M304 FOR DETAIL.

NOTES:

1. FURNISH WITH INTEGRAL BOILER CONTROL PANEL WITH BACNET INTERFACE FOR CONNECTION TO BMS. COORDINATE POINT INTEGRATION.
2. PROVIDE LP GAS KIT, 50 PSI RELIEF VALVE, DIRECT VENT SEALED COMBUSTION, CONCENTRIC VENT KIT, 10 YEAR LIMITED WARRANTY, CONDENSATE NEUTRALIZATION KIT.
3. LOW AND HIGH PRESSURE GAS SWITCH WITH MANUAL RESET AND LOW WATER CUTOFF WITH MANUAL RESET & TEST. G.C. TO PROVIDE HOUSEKEEPING PAD FOR BOILER.
4. PROVIDE A SPARE IGNITER.
5. PROVIDE BOILER WITH MANUFACTURER PROVIDED BOILER CIRCULATION PUMP.

PUMP SCHEDULE

PLAN CODE	MANUFACTURER	FUNCTION	MODEL NUMBER	IMP. DIA	RPM	GPM	FT OF HD	ELECTRICAL DATA			EFF	REMARKS
								HP	VOLT	PH		
HWP-1,2	TACO	HEATING WATER SYSTEM PUMPS	1619	7.15"	1760	36	60	2	120	1	41%	HEATING HOT WATER SYSTEM PUMPS
BP-1,2	GRUNDFOS	BOILER CIRCULATOR PUMPS	UPMXL 25-124	N/A	N/A	19	15	120W	120	1	---	PROVIDE WITH EACH BOILER FROM MANUFACTURER
ZP-1 THRU ZP-10	TACO	RADIANT ZONE CIRCULATOR PUMPS	0011	---	3250	SEE FLOOR HEAT SYSTEM SCHEDULE	31	1/8	120	1	---	RADIANT ZONE CIRCULATOR PUMPS

NOTES:

1. PROVIDE GAUGES ACROSS PUMPS FOR BALANCING PURPOSES.
2. SEE 1/M303 FOR PUMP DETAIL.

AIR SEPARATOR SCHEDULE

PLAN CODE	MANUFACTURER	MODEL NUMBER	GPM	PIPE SIZE	REMARKS
AS-1	TACO	4903	36	2.5"	AIR/DIRT SEPARATOR

EXPANSION TANK SCHEDULE

PLAN CODE	MANUFACTURER	MODEL NUMBER	TOTAL VOLUME	ACCEPTANCE VOLUME	PRECHARGE PRESSURE
ET-1	TACO	CA-90	23	23	15 PSI



BIM 360/15442 - USFW HURON - VISITOR CENTER/21BL5442-MECHANICAL_R20.MT

HURON FISH AND WILDLIFE					SUB-SHEET
MECHANICAL SCHEDULES					M002
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED AS	DRAWN TA	CHECKED TM	DATE 2022.04.29	DRAWING NO. 29320.07	SHEET 47 OF 74

RADIANT ZONE SCHEDULE

PLAN CODE	MANUFACTURER	TUBE SPACING	SUPPLY TEMP. MAX	EWT	DELTA T	FT. OF HEAD	GPM	HEADER SIZE	TUBE SIZE	TUBE SPACING	# OF CIRC.	APPROX. CIRC. LENGTHS	MBH OUTPUT	ZONE SQ. FT	SPACES SERVED	REMARKS
RZ-1	REHAU	6" O.C.	120	115	20	1.8	5.4	1"	5/8"	8" O.C.	10	<300 FT	54	2209	3	300' MAX CIRC. LENGTH
RZ-2	REHAU	6" O.C.	120	115	20	1.2	1.8	1"	5/8"	8" O.C.	4	<300 FT	18	759	8	300' MAX CIRC. LENGTH
RZ-3	REHAU	6" O.C.	120	115	20	1.7	4.8	1"	5/8"	8" O.C.	9	<300 FT	48	2000	3	300' MAX CIRC. LENGTH
RZ-4	REHAU	6" O.C.	120	115	20	1.5	1.5	1"	5/8"	8" O.C.	3	<300 FT	15	608	6	300' MAX CIRC. LENGTH
RZ-5	REHAU	6" O.C.	120	115	20	0.6	0.75	1"	5/8"	8" O.C.	2	<300 FT	7	302	1	300' MAX CIRC. LENGTH
RZ-6	REHAU	6" O.C.	120	115	20	1.4	2.9	1"	5/8"	8" O.C.	6	<300 FT	29	1173	6	300' MAX CIRC. LENGTH
RZ-7	REHAU	6" O.C.	120	115	20	0.4	0.6	1"	5/8"	8" O.C.	2	<300 FT	6	249	1	300' MAX CIRC. LENGTH
RZ-8	REHAU	6" O.C.	120	115	20	0.8	1.2	1"	5/8"	8" O.C.	3	<300 FT	12	489	1	300' MAX CIRC. LENGTH
RZ-9	REHAU	6" O.C.	120	115	20	0.3	0.5	1"	5/8"	8" O.C.	1	<300 FT	2.7	111	1	300' MAX CIRC. LENGTH
RZ-10	REHAU	6" O.C.	120	115	20	1.0	1.3	1"	5/8"	8" O.C.	3	<300 FT	13.2	503	1	300' MAX CIRC. LENGTH

- NOTES:**
- PROVIDE DDC CONTROL OF PUMPS, ETC. PER T.C. SEQUENCE.
 - VERIFY EXACT LOCATION OF RADIANT MANIFOLD LOCATIONS WITH G.C. PRIOR TO INSTALL.
 - PROVIDE RADIANT MANIFOLD WITH CIRCUIT BALANCE VALVES.
 - PROVIDE AND INSTALL WALL CABINET MANIFOLDS (MODEL REHAU-284) FOR RZ-1 AND RZ-2. SEE HYDRONIC PLAN FOR LOCATION. COORDINATE SIZE WITH MANIFOLD. CABINET TO BE PREPPED FOR PAINT BY G.C.

AUTOMATIC GLYCOL FEEDER SCHEDULE

PLAN CODE	MANUFACTURER	MODEL NUMBER	GALLON CAPACITY	PRESSURE RANGE	MAKEUP CAPACITY	ELECTRICAL DATA		REMARKS
						VOLT	HP	
AGF-1	WESSELS	G-18	18	12-60 PSIG	1.0 GPM	120	1/3	SEE NOTES

- NOTES:**
- PROVIDE UNIT WITH FULLY AUTOMATED SYSTEM INCLUDING LOW LEVEL CUTOFF AND ALARM, ISOLATION VALVES, STRAINER, PRESSURE TANK WITH PRESSURE CONTROL, PRESSURE REDUCING VALVE AND GAUGE.
 - PROVIDE UNIT WITH LID DESIGNED TO ACCOMMODATE RELIEF VALVE PIPING. PROVIDE MAGNETIC STARTER, 115V MOTOR AND CONTROLS WITH CORD AND PLUG. WIRE TO DDC SYSTEM FOR MONITORING.

CABINET UNIT HEATER SCHEDULE

PLAN CODE	MANUFACTURER	MODEL NUMBER	STYLE	LOCATION	PERFORMANCE							ELECTRICAL DATA				
					AIR SIDE			HEATING SIDE				HP	VOLT	FLA	PH	
					CFM/HIGH SPEED	EAT °F	LAT °F	MIN MBH	GPM	EWT °F	LWT °F					P.D.
CUH-1	TRANE	FFB0201AAYA	FLOOR-MOUNTED	VESTIBULE	200	60	104	8.8	0.5	150	120	0.71 FT HD	1/10	120	2.75	1

- NOTES:**
- UNITS TO BE PROVIDED WITH INTEGRAL UNIT MOUNTED DISCONNECT, SUSPENSION OR MOUNTING HARDWARE, WALL GASKET, T.C. TO PROVIDE CONTROL VALVES AND THERMOSTAT/SENSOR. PROVIDE STANDARD COLOR SELECTION CHART FOR ARCHITECTURAL SELECTION. SEE DETAIL 5/M302 FOR CABINET UNIT HEATER DETAIL.
 - PROVIDE AND INSTALL PER MANUFACTURER'S INSTRUCTIONS. PROVIDE WITH VALVES AND ACCESSORIES PER DETAIL 5/M302.



HURON FISH AND WILDLIFE					M003
MECHANICAL SCHEDULES					
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED AS	DRAWN TA	CHECKED TM	DATE 2022.04.29	DRAWING NO. 29320.07	SHEET 48 OF 74

VARIABLE AIR VOLUME UNIT SCHEDULE

PLAN CODE	MFR	MODEL NUMBER	INLET SIZE (IN. DIA)	100% CFM	MIN CFM	HEATING CAPACITY (MBH)	HOT WATER COIL (35% GLYCOL)								MAX TOTAL S.P. @ 100% CFM IN. H2O	CONTROL VALVE	REMARKS
							AIR SIDE				WATER SIDE						
							CFM	E.A.T.	L.A.T.	ROWS	GPM	E.W.T.	L.W.T.	FLUID P.D. (FT)			
VAV 1	PRICE	SDV5000	14"	1210	529	25.8	529	55	101	2	2.25	150	127	< 10'	0.3"	2-WAY	SEE NOTES
VAV 2	PRICE	SDV5000	12"	770	385	18.6	385	55	100.6	2	2.0	150	131	< 10'	0.3"	2-WAY	SEE NOTES
VAV 3	PRICE	SDV5000	14"	1450	650	32.8	650	55	100.4	2	3.5	150	130	< 10'	0.3"	2-WAY	SEE NOTES
VAV 4	PRICE	SDV5000	10"	410	214	10.9	214	55	102.8	2	1.0	150	128	< 10'	0.3"	2-WAY	SEE NOTES
VAV 5	PRICE	SDV5000	6"	160	124	6.2	125	55	120	2	0.75	150	130	< 10'	0.3"	2-WAY	SEE NOTES
VAV 6	PRICE	SDV5000	14"	1270	642	31.9	642	55	101.8	2	3.5	150	131	< 10'	0.3"	2-WAY	SEE NOTES
VAV 7	PRICE	SDV5000	6"	160	46	2.4	46	55	101	1	0.75	150	144	< 10'	0.3"	3-WAY	SEE NOTES
VAV 8	PRICE	SDV5000	7"	250	115	6.0	115	55	103	2	0.75	150	134	< 10'	0.3"	2-WAY	SEE NOTES
VAV 9	PRICE	SDV5000	4"	100	40	1.3	20	55	109	1	0.5	150	140.7	< 10'	0.3"	3-WAY	SEE NOTES
VAV 10	PRICE	SDV5000	8"	360	179	8.8	179	55	101	2	1.0	150	140	< 10'	0.3"	2-WAY	SEE NOTES
VAV 11	PRICE	SDV5000	6"	200	0	NO HEAT	NO HEAT	NO HEAT	NO HEAT	NO HEAT	NO HEAT	NO HEAT	NO HEAT	NO HEAT	0.3"	2-WAY	SEE NOTES

- NOTES:
- ENTERING STATIC PRESSURE = 1" W.C.
 - BOX SUPPLIER TO PROVIDE FACTORY INSTALLED MULTI-POINT AVERAGING SENSORS. MECHANICAL CONTRACTOR TO PROVIDE BOXES WITH HANGING BRACKETS, AND PROVIDE DUCT TRANSITIONS TO AND FROM BOXES AS REQUIRED. TEMPERATURE CONTROL SUBCONTRACTOR TO FURNISH ALL DIGITAL VAV BOX CONTROLLERS, ACTUATORS ETC. TO THE BOX MANUFACTURER FOR INSTALLATION. COST OF CONTROLLERS AND SHIPPING SHALL BE BURDEN OF T.C. CONTRACTOR. COST OF THE INSTALLATION SHALL BE BY THE BOX MANUFACTURER.
 - SOUND DISCHARGE LEVELS TO BE <20 N.C. AT 1" INLET STATIC PRESSURE, UNLESS OTHERWISE NOTED.
 - ALL COILS TO BE 2 ROW UNLESS OTHERWISE NOTED.
 - SEE DETAILS 1&2 ON M301 FOR PIPING REQUIREMENTS AND 6/M302 FOR INSTALLATION REQUIREMENTS.
 - MECHANICAL CONTRACTOR TO VERIFY BOX ORIENTATION PRIOR TO ORDERING TO MAINTAIN CONTROL PANEL ACCESS AFTER INSTALLATION.

EXHAUST FAN SCHEDULE

PLAN CODE	MANUFACTURER	MODEL NUMBER	CFM	ESP	RPM	DRIVE TYPE	ELECTRICAL DATA				STATIC EFFICIENCY	SONES	WEIGHT	CONTROL NOTES	AREA SERVED	REMARKS
							HP	VOLT	FLA	PH						
EF-1	PANASONIC	FV-0511VF1	75	0.6	1350	DIRECT	13W	115	0.3	1	N/A	1.5	10 LBS	WIRED TO LIGHTING WALL SWITCH	REST ROOM 125	SEE NOTES 1,2,3,5.
EF-2	PANASONIC	FV-0511VF1	75	0.6	1350	DIRECT	13W	115	0.3	1	N/A	1.5	10 LBS	WIRED TO LIGHTING WALL SWITCH	JAN CLOSET 126	SEE NOTES 1,2,3,5.
EF-3	PANASONIC	FV-0511VF1	75	0.6	1350	DIRECT	13W	115	0.3	1	N/A	1.5	10 LBS	WIRED TO LIGHTING WALL SWITCH	REST ROOM 115	SEE NOTES 1,2,3,5.
EF-4	FANTECH	RN 4EC-4	200	1.5	2450	DIRECT	169W	115	2.1	1	N/A	N/A	7.8 LBS	SEE NOTE 4	RADON PIT	IN-LINE EXHAUST FAN. SEE NOTES 1,5.
EF-5	PANASONIC	FV-0511VF1	75	0.375	1350	DIRECT	13W	115	0.3	1	N/A	1.5	10 LBS	WIRED TO LIGHTING WALL SWITCH	REST ROOM 104	SEE NOTES 1,2,3,5.
EF-6	PANASONIC	FV-0511VF1	75	0.375	1350	DIRECT	13W	115	0.3	1	N/A	1.5	10 LBS	WIRED TO LIGHTING WALL SWITCH	REST ROOM 103	SEE NOTES 1,2,3,5.
EF-7	PANASONIC	FV-0511VF1	75	0.375	1350	DIRECT	13W	115	0.3	1	N/A	1.5	10 LBS	WIRED TO LIGHTING WALL SWITCH	JAN CLOSET 102	SEE NOTES 1,2,3,5.
EF-8	COOK	GC-186	160	0.4	1100	DIRECT	86W	115	0.8	1	38%	5.5	13 LBS	SEE NOTE 4.	160 MECH/ELEC	SEE NOTES 1,2,3,5.


- NOTES:
- PROVIDE ALL FANS WITH BACKDRAFT DAMPER.
 - SEE 3/M302 FOR CEILING MOUNTED EXHAUST FAN DETAIL.
 - PROVIDE ALL DIRECT DRIVE FANS WITH FACTORY WIRED SPEED CONTROLLER AND FACTORY DISCONNECT.
 - FAN TO RUN CONTINUOUSLY.
 - SEE PLANS FOR TERMINATION REQUIREMENTS.



HURON FISH AND WILDLIFE					SUB-SHEET	
MECHANICAL SCHEDULES					M004	
MULTIPURPOSE BUILDING AND VISITOR CENTER						
DESIGNED AS	DRAWN TA	CHECKED TM	DATE 2022.04.29	DRAWING NO. 29320.07	SHEET 49 OF 74	

MECHANICAL GENERAL NOTES	
A	MECHANICAL CONTRACTOR SHALL CUT ALL FLOORS, WALLS, CEILINGS, AND ROOF AS REQUIRED TO PERFORM THE WORK DEPICTED IN THESE CONTRACT DOCUMENTS AND SPECIFICATIONS. GENERAL CONTRACTOR SHALL PATCH ALL ASSOCIATED FLOORS, WALLS, CEILINGS, AND ROOF AS REQUIRED TO THE SATISFACTION OF THE ARCHITECT/ENGINEER.
B	COORDINATE EXACT LOCATION OF DIFFUSERS AND GRILLES WITH REFLECTED CEILING PLAN AND LIGHTING LAYOUT.
C	FLEX DUCT RUN OUTS SHALL BE LIMITED TO 5'-0".
D	COORDINATE HVAC AND PLUMBING EQUIPMENT WITH ALL OTHER TRADES AS REQUIRED.
E	ALL CEILING DIFFUSERS TO BE 4-WAY UNLESS OTHERWISE NOTED.
F	DUCT PENETRATIONS THROUGH ROOF TO BE COORDINATED WITH JOIST LAYOUT.
G	PROVIDE FLUSH CUP CONCEALED OPERATORS ON ALL HAND DAMPERS LOCATED ABOVE HARD CEILINGS.
H	ALL DUCT DIMENSIONS SHOWN ON PLANS ARE CLEAR INTERIOR DIMENSIONS.
I	VERIFY EXACT LOCATION OF T-STATS WITH ARCHITECT PRIOR TO INSTALLATION.
J	SEAL ALL MECHANICAL PENETRATIONS THROUGH FIRE RATED ASSEMBLIES WITH UL-APPROVED FIRE RATED SYSTEM.

MECHANICAL KEYNOTES	
1	SEE 5/M301 FOR PLENUM RETURN DUCT TRANSFER INSTALLATION. (TYP.)
2	UNDERGROUND DUCTWORK UP FROM BELOW. TRANSITION MATERIALS AS REQUIRED.
3	TEMPERATURE CONTROL PANEL. 120V BY E.C. DO NOT ROUTE MECHANICAL SYSTEMS OVER.
4	ELECTRICAL GEAR, DO NOT ROUTE MECHANICAL SYSTEMS OVER.
5	INLINE RADON FAN. SEE 4/M201 FOR BUILDING SECTION. DUCT TO ROOF CAP.
6	EXHAUST DUCT UP TO ROOF CAP. SEE M103 FOR CONTINUATION.
7	3.5"x10" EXHAUST DUCT IN WALL FROM MICROWAVE VENT CONNECTION, TRANSITION TO 6" ROUND DUCT ABOVE WALL AND TERMINATE TO ROOF CAP.
8	SIDEWALL RETURN TRANSFER TO OPEN AREA TO RETURN TO AHU. (TYP.) DUCT OPENING TO PLENUM ON TOP OF DUCT.
9	SIDEWALL RETURN GRILLE IN WALL.
10	EXHAUST TO WALL CAP TERMINATION. MATCH DUCT SIZE (TYP.)



1 FIRST FLOOR MECHANICAL HVAC PLAN
 1/8" = 1'-0"

ACE INC
 ASSOCIATED • CONSTRUCTION • ENGINEERING
 2040 HARNISH BLVD.
 BILLINGS, MT 59102
 406-245-0136
 ACE JOB 21BL5442





HURON FISH AND WILDLIFE					SUB-SHEET
FIRST FLOOR MECHANICAL HVAC PLAN					M101
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED AS	DRAWN TA	CHECKED TM	DATE 2022.04.29	DRAWING NO. 29320.07	SHEET 51 OF 74

BIM 360//6442 - USFW HURON - VISITOR CENTER/21BL5442-MECHANICAL_R20.M

MECHANICAL PIPING GENERAL NOTES	
1	MECHANICAL CONTRACTOR SHALL CUT ALL FLOORS, WALLS, CEILINGS AND ROOF AS REQUIRED TO PERFORM THE WORK DEPICTED IN THESE CONTRACT DOCUMENTS AND SPECIFICATIONS. GENERAL CONTRACTOR SHALL PATCH ALL ASSOCIATED FLOORS, WALLS, CEILINGS, AND ROOF AS REQUIRED TO THE SATISFACTION OF THE ARCHITECT/ENGINEER.
2	SEAL ALL MECHANICAL PENETRATIONS THROUGH FIRE RATED ASSEMBLIES WITH UL-APPROVED FIRE RATED SYSTEM.
3	HYDRONIC VALVES 2" AND SMALLER TO BE BALL VALVES. HYDRONIC VALVES LARGER THAN 2" TO BE LUG STYLE BUTTERFLY VALVES.
4	LOCATE ALL VALVES ABOVE ACCESSIBLE CEILINGS OR PROVIDE ACCESS PANEL IN CEILING FOR VALVE ACCESS. ACCESS PANELS SHALL BE RATED WHERE REQUIRED.
5	COORDINATE HVAC AND PLUMBING ROUTING AND EQUIPMENT WITH ALL OTHER TRADES AS REQUIRED.
6	VERIFY EXACT LOCATION OF THERMOSTATS WITH ARCHITECT PRIOR TO INSTALLATION.
7	THERMOSTATS TO BE LOCATED AT 48" A.F.F.

MECHANICAL KEYNOTES	
1	THERMOSTAT INTERFACE MOUNTED OUTSIDE PRIVATE OFFICE ZONE IN ACCESSIBLE PUBLIC LOCATION FOR ADJUSTABILITY. WIRE TO REMOTE BLANK SENSOR LOCATED IN PRIVATE OFFICE SHOWN.
2	TEMPERATURE CONTROL PANEL. 120V BY E.C. DO NOT ROUTE MECHANICAL SYSTEMS OVER.
3	PIPE DOWN TO RADIANT FLOOR HEATING MANIFOLD. PROVIDE MANIFOLD WITH MANUFACTURER'S PROVIDED ACCESS PANEL FOR IN WALL INSTALLATION. SEE 4/M303 FOR PIPING DETAIL. LOCATE PIPING ACCESSORIES IN ACCESSIBLE CEILING SPACE. COORDINATE ACCESS PANEL AND MANIFOLD LOCATION WITH CASEWORK AND FURNITURE LAYOUTS.
4	PIPE DOWN TO RADIANT FLOOR HEATING MANIFOLD. SEE 4/M303 FOR PIPING DETAIL. LOCATE PIPING ACCESSORIES IN ACCESSIBLE CEILING SPACE. LOCATE MANIFOLD IN MECHANICAL ROOM.
5	VFDs FOR HWP-1,2 DO NOT ROUTE MECHANICAL/PLUMBING SYSTEMS OVER. MAINTAIN CODE REQUIRED CLEARANCES.
6	SEE 5/M302 FOR FLOOR MOUNTED CABINET UNIT HEATER DETAIL.
7	ELECTRICAL GEAR, DO NOT ROUTE MECHANICAL SYSTEMS OVER.
8	PIPE 3/4" OUTLET FROM AGF-1 TO TOP CONNECTION OF AS-1.



1
M102
1/8" = 1'-0"

FIRST FLOOR MECHANICAL PIPING PLAN

2
M102
1/4" = 1'-0"

ENLARGED MECHANICAL ROOM PLAN


ACE INC.
 ASSOCIATED • CONSTRUCTION • ENGINEERING
 2040 HARNISH BLVD.
 BILLINGS, MT 59102
 406-245-0136
 ACE JOB 21BL5442



HURON FISH AND WILDLIFE					SUB-SHEET
FIRST FLOOR MECHANICAL PIPING PLAN					M102
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED AS	DRAWN TA	CHECKED TM	DATE 2022.04.29	DRAWING NO. 29320.07	SHEET 52 OF 74

BIM 360/15442 - USFW HURON - VISITOR CENTER/21BL5442-MECHANICAL_R20.m

BIM 360/16442 - USFW HURON - VISITOR CENTER/21BL5442-MECHANICAL_R20.MT



1
ROOF MECHANICAL PLAN
 M103 1/8" = 1'-0"

MECHANICAL GENERAL NOTES	
A	MECHANICAL CONTRACTOR SHALL CUT ALL FLOORS, WALLS, CEILINGS, AND ROOF AS REQUIRED TO PERFORM THE WORK DEPICTED IN THESE CONTRACT DOCUMENTS AND SPECIFICATIONS. GENERAL CONTRACTOR SHALL PATCH ALL ASSOCIATED FLOORS, WALLS, CEILINGS, AND ROOF AS REQUIRED TO THE SATISFACTION OF THE ARCHITECT/ENGINEER.
B	COORDINATE EXACT LOCATION OF DIFFUSERS AND GRILLES WITH REFLECTED CEILING PLAN AND LIGHTING LAYOUT.
C	FLEX DUCT RUN OUTS SHALL BE LIMITED TO 5'-0".
D	COORDINATE HVAC AND PLUMBING EQUIPMENT WITH ALL OTHER TRADES AS REQUIRED.
E	ALL CEILING DIFFUSERS TO BE 4-WAY UNLESS OTHERWISE NOTED.
F	DUCT PENETRATIONS THROUGH ROOF TO BE COORDINATED WITH JOIST LAYOUT.
G	PROVIDE FLUSH CUP CONCEALED OPERATORS ON ALL HAND DAMPERS LOCATED ABOVE HARD CEILINGS.
H	ALL DUCT DIMENSIONS SHOWN ON PLANS ARE CLEAR INTERIOR DIMENSIONS.
I	VERIFY EXACT LOCATION OF T-STATS WITH ARCHITECT PRIOR TO INSTALLATION.
J	SEAL ALL MECHANICAL PENETRATIONS THROUGH FIRE RATED ASSEMBLIES WITH UL-APPROVED FIRE RATED SYSTEM.


MECHANICAL KEYNOTES	
1	EXHAUST ROOF CAP. SEE M101 FOR DUCT SIZES.

ACE INC
 ASSOCIATED • CONSTRUCTION • ENGINEERING
 2040 HARNISH BLVD.
 BILLINGS, MT 59102
 406-245-0136
 ACE JOB 21BL5442




HURON FISH AND WILDLIFE					SUB-SHEET	
ROOF MECHANICAL PLAN					M103	
MULTIPURPOSE BUILDING AND VISITOR CENTER						
DESIGNED AS	DRAWN TA	CHECKED TM	DATE 2022.04.29	DRAWING NO. 29320.07	SHEET 53 OF 74	

BIM 360//6442 - USFW HURON - VISITOR CENTER/21BL5442-MECHANICAL_R20.M



- ZONE 1
- ZONE 2
- ZONE 3
- ZONE 4
- ZONE 5
- ZONE 6
- ZONE 7
- ZONE 8
- ZONE 9
- ZONE 10
- ZONE 11




MECHANICAL ZONE PLAN


1
M104
1/8" = 1'-0"




HURON FISH AND WILDLIFE					SUB-SHEET	
MECHANICAL ZONE PLAN					M104	
MULTIPURPOSE BUILDING AND VISITOR CENTER						
DESIGNED AS	DRAWN TA	CHECKED TM	DATE 2022.04.29	DRAWING NO. 29320.07	SHEET 54 OF 74	




1 MECHANICAL SECTION 1 - LOOKING SOUTH
M201 1/8" = 1'-0"



2 MECHANICAL SECTION 2 - LOOKING WEST
M201 1/8" = 1'-0"



3 MECHANICAL SECTION 3 - LOOKING WEST
M201 1/8" = 1'-0"



4 MECHANICAL SECTION 4 - LOOKING WEST
M201 1/8" = 1'-0"

ACE INC.
ASSOCIATED • CONSTRUCTION • ENGINEERING
2040 HARNISH BLVD.
BILLINGS, MT 59102
406-245-0136
ACE JOB 21BL5442




**HURON FISH AND WILDLIFE
MECHANICAL SECTIONS AND ENLARGED
PLANS**

SUB-SHEET


M201

DESIGNED AS	DRAWN TA	CHECKED TM	DATE 2022.04.29	DRAWING NO. 29320.07
----------------	-------------	---------------	--------------------	-------------------------


SHEET
55 OF 74




1 2-WAY COIL DETAIL
NOT TO SCALE




2 3-WAY COIL DETAIL
NOT TO SCALE



3 AHU CONDENSATE DRAIN TRAP DETAIL
NOT TO SCALE



4 AHU-1 DETAIL
NOT TO SCALE




5 RETURN AIR PLENUM TRANSFER DETAIL
NOT TO SCALE

- NOTES:
1. TRANSFER DUCT LOCATION AND SIZES ARE SHOWN ON THE MECHANICAL DRAWINGS.
 2. TRANSFER DUCT SHALL BE FABRICATED OF GALVANIZED STEEL DUCT AND LINED WITH 1" ACOUSTICAL LINING (A.L.)
 3. TRANSFER DUCT AND GRILLE SHALL BE INDEPENDENTLY SUPPORTED FROM THE CEILING SYSTEM.
 4. TRANSFER DUCT TO BE MOUNTED ABOVE THE ADJACENT CEILING ELEVATIONS.


ACE INC
ASSOCIATED • CONSTRUCTION • ENGINEERING
2040 HARNISH BLVD.
BILLINGS, MT 59102
406-245-0136
ACE JOB 21BL5442



HURON FISH AND WILDLIFE					SUB-SHEET
MECHANICAL DETAILS					M301
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED AS	DRAWN TA	CHECKED TM	DATE 2022.04.29	DRAWING NO. 29320.07	SHEET 56 OF 74




1 BOILER DETAIL
NOT TO SCALE




NOTES:
1) CONNECT 2 NO. 12 GA. GRILLE SUPPORT WIRES @ DIAGONAL CORNERS OF EACH CEILING GRILLE. MAX. CEILING GRILLE WT. 55#. SEE SPEC. 230548 FOR MORE INFORMATION.
2) EXCLUDE GRILLES LESS THAN 20LBS OR LESS FROM THIS REQUIREMENT WHERE IMPORTANCE FACTOR 1P = 1.0


2 CEILING GRILLE SUPPORT DETAIL
NOT TO SCALE




3 CEILING MOUNTED EXHAUST FAN
NOT TO SCALE



4 CONCENTRIC ROOF TERMINATION
NOT TO SCALE



5 FLOOR MOUNTED CABINET UNIT HEATER DETAIL
NOT TO SCALE




NOTE:
CONTRACTOR HAS THE OPTION TO PROVIDE A HARD DUCT CONNECTION TO THE VAV BOX OR PROVIDE A FLEXIBLE CONNECTOR AS SHOWN IN THE DETAIL. CONTRACTOR SHALL MINIMIZE THE NUMBER AND DEGREE OF DUCT OFFSETS TO THE VAV BOX IF A HARD DUCT CONNECTION IS UTILIZED. CONTRACTOR SHALL UTILIZE THE SAME CONNECTION METHOD FOR ALL VAV'S IN THE PROJECT.

6 VAV BOX DETAIL
NOT TO SCALE


BIM 360/15442 - USFW HURON - VISITOR CENTER/21BL5442-MECHANICAL_R20.M

ACE INC
ASSOCIATED • CONSTRUCTION • ENGINEERING
2040 HARNISH BLVD.
BILLINGS, MT 59102
406-245-0136
ACE JOB 21BL5442


HURON FISH AND WILDLIFE					SUB-SHEET
MECHANICAL DETAILS					M302
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED AS	DRAWN TA	CHECKED TM	DATE 2022.04.29	DRAWING NO. 29320.07	SHEET 57 OF 74




1 INLINE PUMP DETAIL
NOT TO SCALE



2 PIPE HANGER DETAILS
NOT TO SCALE





3 RADIANT FLOOR DETAIL
NOT TO SCALE



4 RADIANT FLOOR SYSTEM SCHEMATIC
NOT TO SCALE

BIM 360/15442 - USFW HURON - VISITOR CENTER/21BL5442-MECHANICAL_R20.MT

 ACE INC <small>ASSOCIATED • CONSTRUCTION • ENGINEERING</small> 2040 HARNISH BLVD. BILLINGS, MT 59102 406-245-0136 ACE JOB 21BL5442	
---	---

HURON FISH AND WILDLIFE					SUB-SHEET
MECHANICAL DETAILS					M303
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED AS	DRAWN TA	CHECKED TM	DATE 2022.04.29	DRAWING NO. 29320.07	SHEET 58 OF 74

GENERAL MECHANICAL NOTES:


- 1) PROVIDE BOILER WITH INTEGRAL HIGH LIMIT TEMPERATURE CONTROL WITH MANUAL RESET, FLOW SWITCH, AND LOW-WATER FUEL CUT-OFF WITH MANUAL RESET, HIGH AND LOW GAS PRESSURE SWITCHES WITH MANUAL RESET.
- 2) BOILERS ARE 100% CAPACITY. PUMPS ARE 100% CAPACITY.
- 3) INSTALL ALL EQUIPMENT PER MANUFACTURER INSTALLATION INSTRUCTIONS.
- 4) PIPE A 2.5 GALLON CHEMICAL POT FEEDER FROM SUCTION TO DISCHARGE OF HWP-1 AND HWP-2. MOUNT A MAXIMUM OF 48" A.F.F.
- 6) LOCATE WATER INLET AND OUTLET FITTINGS AND ALL PIPING AWAY FROM BOILER TO ALLOW FOR REMOVAL OF ACCESS PANELS.

GENERAL VALVING NOTES:

- 2) ALL VALVES TO BE BALL VALVES.


GENERAL PIPING NOTES:

- 1) ALL TRANSITIONS FROM GROOVED PIPE TO FLANGE SHALL BE WELDED FLANGE.



1 HYDRONIC HEATING SYSTEM SCHEMATIC
NOT TO SCALE

- 1 UNDERSLAB BLUE DUCT OR EQUIVALENT PRODUCT INTENDED TO BE DIRECTLY BURIED, SUBMIT ANY PROPOSED ALTERNATIVES FOR APPROVAL.
- 2 COMPACTED FILL
- 3 FINISHED GRADE, SEE CIVIL DRAWINGS
- 4 4"-6" SUB BED



NOTE:
A TRENCH SHALL BE DEEP ENOUGH TO BURY THE DUCT. THE DUCT CAN REST ON THE SAND BEDDING. THE DUCT TRENCH SHALL BE FILLED WITH SAND BEDDING TO THE BOTTOM OF THE SLAB. BACKFILL SHALL BE TAMPED EVENLY AROUND BOTH SIDES OF THE DUCT. FLOOR SLAB CAN THEN BE POURED OVER THE DUCT MAKING A COMPLETE SLAB.

2 UNDERGROUND DUCTWORK DETAIL
NOT TO SCALE

ACE INC
ASSOCIATED • CONSTRUCTION • ENGINEERING
2040 HARNISH BLVD.
BILLINGS, MT 59102
406-245-0136
ACE JOB 21BL5442

REGISTERED PROFESSIONAL ENGINEER
TODD A. MELING
4/29/2022
SOUTH DAKOTA

HURON FISH AND WILDLIFE					SUB-SHEET
MECHANICAL DETAILS					M304
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED AS	DRAWN TA	CHECKED TM	DATE 2022.04.29	DRAWING NO. 29320.07	SHEET 59 OF 74


BIM 360/15442 - USFW HURON - VISITOR CENTER/21BL5442-MECHANICAL_R20.M

ELECTRICAL LEGEND

LIGHTING DEVICES

	LAY-IN OR RECESSED LIGHTING FIXTURE
	SURFACE MOUNTED LIGHTING FIXTURE
	DIRECT/ INDIRECT LIGHTING PENDANT MOUNTED FIXTURE.
	SURFACE MOUNTED OR CHAIN HUNG STRIP FIXTURE
	WALL BRACKET LIGHTING FIXTURE
	RECESSED DOWN LIGHT, HALF MOON INDICATES WALL WASH TRIM AND DIRECTION.
	SURFACE MOUNTED CYLINDER FIXTURE
	WALL MOUNTED FIXTURE
	WALL SCONCE FIXTURE
	FILLED CENTER OR SLASH INDICATES FIXTURE IS AN EMERGENCY DEVICE WITH EMERGENCY BATTERY PACK OR CONNECTED TO EMERGENCY POWER.
	EXIT SIGN, BRACKET INDICATES WALL MOUNTING, NUMBER OF FACES AND DIRECTION INDICATED BY FILLED AREAS.
	REMOTE DOUBLE HEAD EGRESS FIXTURE
	SITE GROUND MOUNTED FLOOD FIXTURE
	DOUBLE HEAD WALL MOUNTED BATTERY PACK POWERED EGRESS FIXTURE.
	SQUARE HEAD POLE MOUNTED SITE LIGHT FIXTURE.
	ROUND HEAD POLE MOUNTED SITE LIGHT FIXTURE.

INTERIOR MOUNTING HEIGHTS



FIRE ALARM DEVICES

	MANUAL PULL STATION
	AUDIO/VISUAL HORN/STROBE DEVICE
	VISUAL STROBE DEVICE
	AUDIO SPEAKER DEVICE
	CEILING MOUNTED AUDIO/VISUAL SPEAKER/STROBE DEVICE
	CEILING MOUNTED AUDIO SPEAKER DEVICE
	MAGNETIC DOOR HOLDER
	SMOKE DETECTOR
	HEAT DETECTOR
	CARBON MONOXIDE DETECTOR
	DUCT SMOKE DETECTOR
	FIRE SMOKE DAMPER
	FIRE ALARM CONTROL PANEL
	FIRE ALARM REMOTE ANNUNCIATOR
	ADDRESSABLE INTERFACE DEVICE BY EC FOR FIRE/SMOKE DAMPERS

COMMUNICATION DEVICES

	COMBINATION VOICE/ DATA DEVICE JACKS, BOX INDICATES FLOOR MOUNTING
	VOICE DEVICE JACK, BOX INDICATES FLOOR MOUNTING
	CABLE TV JACK
	INTERCOM JACK
	CEILING MOUNTED SPEAKER
	WALL MOUNTED SPEAKER
	WALL MOUNTED VOLUME CONTROLLER

SECURITY SYSTEM DEVICES

	CLOSED CIRCUIT CAMERA
	CEILING MOUNTED MOTION SENSOR
	CORNER MOUNTED MOTION SENSOR
	WALL MOUNTED MOTION SENSOR
	KEY PAD
	REQUEST TO EXIT SENSOR

MISCELLANEOUS LEGEND

W/	WITH ABOVE COUNTER	AFF	ABOVE FINISHED FLOOR
AC	ELECTRICAL CONTRACTOR	AFG	ABOVE FINISHED GRADE
EC	EXISTING	WM	WIRE MOLD
(E)	RELOCATED	GC	GENERAL CONTRACTOR
(R)	NEW DEVICE	GND	GROUND
(N)	CONDUIT	UG	UNDER GROUND
C	BELOW FINISHED GRADE	BOD	BOTTOM OF DEVICE
BFG	UNDER COUNTER	TOD	TOP OF DEVICE
UC	WEATHER PROOF	COD	CENTER OF DEVICE
WP	MECHANICAL CONTRACTOR	BOF	BOTTOM OF FIXTURE
MC		PC	PLUMBING CONTRACTOR
①	REFER TO ELECTRICAL NOTES		
	HOMERUN TO ELECTRICAL PANEL		
	NORMAL CIRCUIT CONCEALED IN WALL OR EXPOSED		
	UNDERGROUND OR BURIED CIRCUIT		

POWER DEVICES

SINGLE POLE SWITCH, SUBSCRIPT INDICATES TYPE:	
P	PILOT LIGHT
2	2 POLE
MC	MOMENTARY CONTACT
3	3-WAY
4	4-WAY
K	KEYED
D	DIMMER
LV	LOW VOLTAGE
T	TIMER, 1 HOUR TIMER, MOTOR RATED FOR EXHAUST FANS
OS	OCCUPANCY SENSOR
DUPLX RECEPTACLE SUBSCRIPT INDICATES TYPE:	
WP	WEATHERPROOF
GFCI	GROUND FAULT CIRCUIT INTERRUPTER
AC	ABOVE COUNTER
IG	ISOLATED GROUND
TR	TAMPER RESISTANT
WR	WEATHER RESISTANT
	FILLED CENTER INDICATES GFCI DEVICE
DOUBLE DUPLEX RECEPTACLE, SUBSCRIPT ABOVE INDICATE TYPE	
	DUPLX RECEPTACLE IN FLOOR BOX
	DOUBLE DUPLEX RECEPTACLE IN FLOOR BOX
	SIMPLEX RECEPTACLE
	DUPLEX RECEPTACLE, CEILING MOUNTED. DEVICE AND COVER SHALL MATCH CEILING FINISH
	SWITCHED DUPLEX RECEPTACLE, BOX INDICATES DEVICE LOCATED IN FLOOR BOX
	208V SINGLE PHASE RECEPTACLE, CONFIGURATION NOTED ON PLANS
	208V THREE PHASE RECEPTACLE, CONFIGURATION NOTED ON PLANS
	SIMPLEX RECEPTACLE IN FLOOR BOX
	MUSHROOM HEAD PUSH BUTTON
	PHOTO CELL
	WALL MOUNTED CLOCK HANGER/ POWER RECEPTACLE
	CORNER WALL MOUNTED OCCUPANCY SENSOR
	CEILING MOUNTED OCCUPANCY SENSOR, STYLE 1
	CEILING MOUNTED OCCUPANCY SENSOR, STYLE 2
	CEILING MOUNTED OCCUPANCY SENSOR, STYLE 3
	OCCUPANCY SENSOR POWER PACK, BOX INDICATES WALL MOUNTING
	SPECIAL PURPOSE CONNECTION, BRACKET INDICATES WALL MOUNTING, BOX INDICATES FLOOR MOUNTING
	JUNCTION BOX, BRACKET INDICATES WALL MOUNTING, BOX INDICATES FLOOR MOUNTING
	MOTOR CONNECTION
	RELAY
	NON-FUSED DISCONNECT SWITCH
	FUSED DISCONNECT SWITCH
	COMBINATION STARTER/DISCONNECT SWITCH
	CONTACTOR
	MOTOR THERMAL SWITCH
	AQUASTAT BY PLUMBING CONTRACTOR, WIRED BY EC.
	VARIABLE FREQUENCY DRIVE
	CO2 DETECTOR BY MC, ROUGH-IN BY EC
	THERMOSTAT BY MC, ROUGH-IN BY EC
	PAD MOUNTED UTILITY TRANSFORMER
	ELECTRICAL PANEL - SEE PANEL SCHEDULES FOR MOUNTING CONFIGURATION

ELECTRICAL ABBREVIATIONS

A	AMP(S)	LTS	LIGHTS
ACCU	AIR CONDITIONING CONDENSING UNIT	LW	LIGHT WHITE
ACU	AIR CONDITIONING UNIT	MC	MECHANICAL CONTRACTOR
ADJ	ADJUSTABLE	MOC	MOMENTARY CONTACT
ADMIN	ADMINISTRATION	MCB	MAIN CIRCUIT BREAKER
AFF	ABOVE FINISH FLOOR	MDP	MAIN DISTRIBUTION PANEL
AHU	AIR HANDLING UNIT	MECH	MECHANICAL
AL	ALUMINUM	MIN	MINIMUM
AMP	AMPERE(S)	MLO	MAIN LUGS ONLY
APPL	APPLIANCE	MTD	MOUNTED
APPROX	APPROXIMATE	MFA	MINIMUM FEEDER AMPACITY
ATS	AUTOMATIC TRANSFER SWITCH	MFG	MANUFACTURER
BLDG	BUILDING	MTS	MOTOR THERMAL SWITCH
BRK	BREAKER	NIC	NOT IN CONTRACT NUMBER
BTU/HR	BRITISH THERMAL UNIT/HOUR	NO	
C	CONDUIT	OCF	OVERCURRENT PROTECTION OWNER-FURNISHED, CONTRACTOR INSTALLED
CB	CIRCUIT BREAKER	PNL	PANEL PREPARATION
CCT	CIRCUIT CLOSED CIRCUIT TELEVISION	PROD	PRODUCE PROVIDE & INSTALL
CUH	CABINET UNIT HEATER	P/I	
CFM	CUBIC FEET PER MINUTE	RA	REMOTE ANNUNCIATOR
COM	COMMUNICATION	RAF	RETURN AIR FAN
COMM	COMMERCIAL	RECP	RECEPTACLE
COMP	COMPRESSOR	RECP	RECEPTACLE
COND	CONDENSER	REF	REFRIGERATOR
CONTR	CONTRACTOR	REFR	REFRIGERANT
CU	COPPER	REQD	REQUIRED
CTV	CABLE TELEVISION	RM	ROOM
CW	COOL WHITE	RMS	ROOM(S)
CWP	COLD WATER PUMP	RR	RESTROOMS
DIA	DIAMETER	RS	RAPID START
DISC	DISCONNECT	SDP	SUB DISTRIBUTION PANEL
DWG	DRAWING	SER	SERVICE
EC	ELECTRICAL CONTRACTOR	SE	SUPPLY FAN
EF	EXHAUST FAN	SHT	SHEET
ELEC	ELECTRIC	SN	SOLID NEUTRAL
EMD	ESTIMATED MAXIMUM DEMAND	SP	SWITCH, PILOT SPECIFICATIONS
EMER	EMERGENCY	SPST	SWITCH, SINGLE POLE-SINGLE THROW
ENGR	ENGINEER	STD	STANDARD
ETC	ETCETERA	STL	STEEL
EWC	ELECTRIC WATER COOLER	STOR	STORAGE
EXT	EXTERIOR	SW	SWITCH
FA	FIRE ALARM	TBD	TELEPHONE BACK BOARD
FAC	FACILITY	TV	TELEVISION TYPICAL
FACP	FIRE ALARM CONTROL PANEL	UG	UNDERGROUND
FIX	FIXTURE	UGE	UNDERGROUND ELECTRICAL
FLA	FULL LOAD AMPS	UHT	UNDERGROUND TELEPHONE UNIT HEATER
FT	FOOT	UH	
GC	GENERAL CONTRACTOR	V	VOLT(S)
GFCI	GROUND FAULT CIRCUIT INTERRUPTER	VA	VOLT AMPERES
GFI	GROUND FAULT INTERRUPTER	VEST	VESTIBULE
HP	HORSEPOWER	W	WIRE
HPS	HIGH PRESSURE SODIUM	W	WATT(S)
HID	HIGH INTENSITY DISCHARGE	W/	WITH
HT	HEIGHT	WM	WATT MISER
HTRS	HEATERS	XFMR	TRANSFORMER
HW	HOT WATER		
HWH	HOT WATER HEATER		
HWP	HOT WATER PUMP		
HZ	HERTZ		
INC	INCORPORATED		
J-BOX	JUNCTION BOX		
KHZ	KILOHERTZ		
KIT	KITCHEN		
KVA	KILOVOLT AMPERE(S)		
KW	KILOWATT(S)		

ELECTRICAL SHEET LIST

E001	ELECTRICAL COVER SHEET
E002	ELECTRICAL SCHEDULES
E003	ELECTRICAL SCHEDULES
E101	ELECTRICAL POWER AND SPECIAL SYSTEMS PLAN
E102	ELECTRICAL LIGHTING PLAN
E301	ELECTRICAL DETAILS
E302	ELECTRICAL DETAILS
E5101	ELECTRICAL SITE PLAN

ACE INC
ASSOCIATED • CONSTRUCTION • ENGINEERING
2040 HARNISH BLVD.
BILLINGS, MT 59102
406-245-0136
ACE JOB 21BL5442



Panel: G1L

Location: MECHANICAL 106
 Supply From: ATS
 Mounting: Surface
 Enclosure: 1

Volts: 120/208 Wye
 Phases: 3
 Wires: 4

A.I.C. Rating: 22,000
 Mains Type: Main Circuit Breaker
 Mains Rating: 400 A
 Bus Rating: 400 A

Notes: PROVIDE WITH 350A/3P, 22KAIR MAIN CIRCUIT BREAKER.

CKT	Circuit Description	Tripp	Poles	A	B	C	Poles	Tripp	Circuit Description	CKT		
1	RM107 CONFERENCE RCPTS	20 A	1	1440	10900			3	125 A	AIR HANDLING UNIT AHU-1	2	
3	RM108 ADMIN RCPTS	20 A	1		720	10900					4	
5	RM111,112 OFFICE RCPTS	20 A	1			720	10900				6	
7	RM113 LE OFFICE RCPTS	20 A	1	360	900			3	20 A	RM106 HEATING WATER SYS PUMP HWP-1	8	
9	RM110 REFUGE OPEN OFFICE RCPTS (SE)	20 A	1		720	900					10	
11	RM110 REFUGE OPEN OFFICE RCPTS (NE)	20 A	1			720	900				12	
13	RM110 REFUGE OPEN OFF RCPTS (S CENT)	20 A	1	720	900			3	20 A	RM106 HEATING WATER SYS PUMP HWP-2	14	
15	RM110 REFUGE OPEN OFF RCPTS (N CENT)	20 A	1		720	900					16	
17	RM110 REFUGE OPEN OFFICE RCPTS (SW)	20 A	1			720	900				18	
19	RM110 REFUGE OPEN OFFICE RCPTS (NW)	20 A	1	720	416			1	20 A	RM106 DDC PANEL	20	
21	RM118 BREAK RCPTS	20 A	1		1500	1630		1	20 A	RM106 BOILER B-1, BOILER PUMP BP-1	22	
23	RM120 WORKROOM RCPTS	20 A	1			720	1630		1	20 A	RM106 BOILER B-2, BOILER PUMP BP-2	24
25	RM129 OFFICE RCPTS	20 A	1	720	338			1	20 A	RM106 EXHAUST FANS EF-4, EF-8	26	
27	RM131 OFFICE RCPTS	20 A	1		720	830		1	20 A	RM 106 AGF-1	28	
29	RM123 REALTY OPEN OFFICE RCPTS (SE)	20 A	1			720	0	1	20 A	SPARE	30	
31	RM123 REALTY OPEN OFFICE RCPTS (NE)	20 A	1	720	1967			3	30 A	VAPORIZER VAP-1	32	
33	RM123 REALTY OPEN OFF RCPTS (S CENT)	20 A	1		720	1967					34	
35	RM123 REALTY OPEN OFF RCPTS (N CENT)	20 A	1			720	1967				36	
37	RM123 REALTY OPEN OFFICE RCPTS (SW)	20 A	1	720	267			3	20 A	SEWER LIFT STATION PUMP (PUMP-1)	38	
39	RM123 REALTY OPEN OFFICE RCPTS (NW)	20 A	1		720	267					40	
41	RM116 IT RACK RCPTS	20 A	1			1080	267				42	
43	RM116 IT RACK RCPT	30 A	1	180	0			1	20 A	SPARE	44	
45	RM116 FIRE ALARM CONTRL PANEL FACP	20 A	1		360	0		1	20 A	SPARE	46	
47	RM106 ZP-5, ZP-6 RM107 ZP-10	20 A	1			1290	2500	2	30 A	ENGINE/GENERATOR PANEL	48	
49	RM112 ZP-4, RM109 ZP-3, ZP-9	20 A	1	1290	2500						50	
51	RM126 ZP-2, ZP-8	20 A	1		860	0		1	20 A	SPARE	52	
53	RM120 ZP-7, RM 122 ZP-1	20 A	1			860	0	1	20 A	SPARE	54	
55	SPARE	20 A	1	0	0			1	20 A	SPARE	56	
57	SPARE	20 A	1		0	0		1	20 A	SPARE	58	
59	SPARE	20 A	1			0	0	1	20 A	SPARE	60	
61	RM106, 107, 114, 116, 118, 124 LIGHTING	20 A	1	517	0			1	20 A	SPARE	62	
63	RM100, 101, 105, 121, 110, 119, 123 LIGHTING	20 A	1		471	0		1	20 A	SPARE	64	
65	EXTERIOR BLDG LIGHTS	20 A	1			312	0	1	20 A	SPARE	66	
67	SPARE	20 A	1	0	0			1	20 A	SPARE	68	
69	SPARE	20 A	1		0	0		1	20 A	SPARE	70	
71	SPARE	20 A	1			0	0	1	20 A	SPARE	72	
				Total Load:	25575 VA	24905 VA	26926 VA					
				Total Amps:	214 A	208 A	225 A					

Legends:

NOTE 1: PROVIDE RED HANDLE LOCKABLE BREAKER FOR MCCB SHOWN. LABEL PER NFPA 72 REQUIREMENTS. NOTE 2: PROVIDE 3#1/0,#6G, 1/2" C FOR CKT G1L-2,4,6 AHU-1.

Load Classification	Connected Load	Demand Factor	Estimated Demand	Panel Totals
Motor	52699 VA	115.51%	60874 VA	
Other	0 VA	0.00%	0 VA	Total Conn. Load: 77405 VA
Receptacle	22870 VA	71.86%	16435 VA	Total Est. Demand: 79145 VA
Power	536 VA	100.00%	536 VA	Total Conn.: 215 A
Lighting	1300 VA	100.00%	1300 VA	Total Est. Demand: 220 A

Notes:

GENERAL REQUIREMENTS: PROVIDE NFPA 70-2020 ART 110.21(B) COMPLIANT HAZARD MARKINGS (ARC FLASH AND SHOCK HAZARD) IN ACCORDANCE WITH SPEC SECTION 262416 3.25 REQUIREMENTS. THE HAZARD MARKINGS MAY BE EITHER FIELD OR FACTORY APPLIED. PROVIDE FIELD MARKINGS, PHENOLIC LABEL WHITE TEXT ON BLACK BACKGROUND, OF AVAILABLE SHORT CIRCUIT CURRENT IN COMPLIANCE WITH NFPA 70-2020 ART 110.24 AND IN ACCORDANCE WITH SPEC SECTION 262416 3.2R REQUIREMENTS. PROVIDE PHENOLIC LABEL (WHITE TEXT ON BLACK BACKGROUND) WITH PANELBOARD NAME AND ELECTRICAL CHARACTERISTICS (208Y/120V, 400A, 3PH4W) ON FRONT OF PANELBOARD.

Panel: N1L

Location: MECHANICAL 106
 Supply From: UT1
 Mounting: Surface
 Enclosure: 1

Volts: 120/208 Wye
 Phases: 3
 Wires: 4

A.I.C. Rating: 65,000
 Mains Type: Main Circuit Breaker
 Mains Rating: 400 A
 Bus Rating: 400 A

Notes: PROVIDE WITH 400A/3P, ELECTRONIC TRIP LSIG 65KAIR MAIN CIRCUIT BREAKER.

CKT	Circuit Description	Tripp	Poles	A	B	C	Poles	Tripp	Circuit Description	CKT	
1	RM100 VEST,101 HALL,102 JANITOR RCPTS	20 A	1	690	26926			3	350 A	ATS	2
3	RM104 RESTRM RCPT + DRYER + IR SENSOR	20 A	1		1750	25575					4
5	RM103 RESTRM RCPT + DRYER + IR SENSOR	20 A	1			1750	24905				6
7	RM105 VISITOR CONTACT RCPTS (N)	20 A	1	900	1500			1	20 A	RM118 BREAK SMALL APPLIANCE CKT 1	8
9	RM105 VISITOR CONTACT RCPTS (W)	20 A	1		720	1500		1	20 A	RM118 BREAK SMALL APPLIANCE CKT 2	10
11	RM105 VISITOR CONTACT RCPTS (S)	20 A	1			1080	1200	1	20 A	RM118 BREAK MICROWAVE	12
13	RM105 VISITOR CONTACT FLOORBOX RCPTS	20 A	1	720	2000			2	50 A	RM118 BREAK RANGE	14
15	RM106 MECH/ELECT RCPTS	20 A	1			720	2000				16
17	RM107 CONFERENCE RM RCPTS	20 A	1			900	180	1	20 A	RM118 BREAK GARBAGE DISPOSAL	18
19	RM107 CONFERENCE RM RCPTS	20 A	1	360	1440			1	20 A	RM118 BREAK WALL RCPTS (S)	20
21	RM111 OFFICE RCPTS	20 A	1		540	540		1	20 A	RM118 BREAK WALL RCPTS (NE)	22
23	RM112 OFFICE RCPTS	20 A	1			540	1750	1	20 A	RM115 RESTRM RCPT + DRYER + IR SENSOR	24
25	RM113 LE OFFICE RCPTS	20 A	1	540	1750			1	20 A	RM125 RESTRM RCPT + DRYER + IR SENSOR	26
27	RM108 ADMIN RCPTS	20 A	1		900	1260		1	20 A	RM128 TEAM RM,129 OFFICE RCPTS	28
29	RM109 STORAGE 3 RCPTS	20 A	1			900	1080	1	20 A	RM130 OFFICE,131 OFFICE RCPTS	30
31	RM114 HALL,110 OPEN OFF HALL RCPTS	20 A	1	540	540			1	20 A	EXTERIOR RCPTS (E) (SE)	32
33	RM110 REFUGE OPEN OFFICE RCPTS (SE)	20 A	1		720	360		1	20 A	EXTERIOR RCPTS (W) (S)	34
35	RM110 REFUGE OPEN OFFICE RCPTS (NE)	20 A	1			900	540	1	20 A	EXTERIOR RCPTS (N)	36
37	RM110 REFUGE OPEN OFF RCPTS (S CENT)	20 A	1	720	1116			1	20 A	RM 118,120-122,125-131 LIGHTING	38
39	RM110 REFUGE OPEN OFF RCPTS (N CENT)	20 A	1		900	1093		1	20 A	RM 107,111-113,115,117 LIGHTING	40
41	RM110 REFUGE OPEN OFFICE RCPTS (SW)	20 A	1			720	87	1	20 A	FLAG POLE LIGHTING	42
43	RM110 REFUGE OPEN OFFICE RCPTS (NW)	20 A	1	900	652			1	20 A	PARKING LOT LIGHTING	44
45	RM117 STORAGE 2 RCPTS	20 A	1		540	900		1	20 A	RM123 REALTY OPEN OFFICE LIGHTING	46
47	RM121 LOCKER RCPTS	20 A	1			360	900	1	20 A	RM110 REFUGE OPEN OFFICE LIGHTING	48
49	RM120 WORKROOM RCPTS (N)	20 A	1	900	590			1	20 A	RM105 VISITOR CONTACT LIGHTING	50
51	RM120 WORKROOM RCPTS (S)	20 A	1		720	0		1	20 A	SPARE	52
53	RM122 STORAGE RCPTS	20 A	1			720	0	1	20 A	SPARE	54
55	RM119 HALL RCPTS	20 A	1	360	0			1	20 A	SPARE	56
57	RM127 STORAGE 1,126 JANITOR RCPTS	20 A	1		720	0		1	20 A	SPARE	58
59	RM124 HALL,123 OPEN OFF HALL RCPTS	20 A	1			540	0	1	20 A	SPARE	60
61	RM123 REALTY OPEN OFFICE RCPTS (SE)	20 A	1	720	0			1	20 A	SPARE	62
63	RM123 REALTY OPEN OFFICE RCPTS (NE)	20 A	1		1080	0		1	20 A	SPARE	64
65	RM123 REALTY OPEN OFF RCPTS (S CENT)	20 A	1			720	0	1	20 A	SPARE	66
67	RM123 REALTY OPEN OFF RCPTS (N CENT)	20 A	1	900	0			1	20 A	SPARE	68
69	RM123 REALTY OPEN OFFICE RCPTS (SW)	20 A	1		720	0		1	20 A	SPARE	70
71	RM123 REALTY OPEN OFFICE RCPTS (NW)	20 A	1			1080	0	1	20 A	SPARE	72
				Total Load:	44761 VA	43258 VA	40852 VA				
				Total Amps:	376 A	364 A	340 A				


Legends:

NOTE 1: PROVIDE 3#6,#10G,3/4" C FOR CKT N1L-14,16 RANGE.

Load Classification	Connected Load	Demand Factor	Estimated Demand	Panel Totals
Kitchen Equipment - Non-Dwelling Unit	4380 VA	65.00%	2847 VA	
Motor	53029 VA	115.42%	61204 VA	Total Conn. Load: 128870 VA
Other	0 VA	0.00%	0 VA	Total Est. Demand: 111508 VA
Receptacle	58010 VA	58.62%	34005 VA	Total Conn.: 358 A
Power	6816 VA	100.00%	6816 VA	Total Est. Demand: 310 A
Lighting	6636 VA	100.00%	6636 VA	

Notes:

GENERAL REQUIREMENTS: PROVIDE NFPA 70-2020 ART 110.21(B) COMPLIANT HAZARD MARKINGS (ARC FLASH AND SHOCK HAZARD) IN ACCORDANCE WITH SPEC SECTION 262416 3.25 REQUIREMENTS. THE HAZARD MARKINGS MAY BE EITHER FIELD OR FACTORY APPLIED. PROVIDE FIELD MARKINGS, PHENOLIC LABEL WHITE TEXT ON BLACK BACKGROUND, OF AVAILABLE SHORT CIRCUIT CURRENT IN COMPLIANCE WITH NFPA 70-2020 ART 110.24 AND IN ACCORDANCE WITH SPEC SECTION 262416 3.2R REQUIREMENTS. PROVIDE PHENOLIC LABEL (WHITE TEXT ON BLACK BACKGROUND) WITH PANELBOARD NAME AND ELECTRICAL CHARACTERISTICS (208Y/120V, 400A, 3PH4W) ON FRONT OF PANELBOARD.



FEEDER AMPS	CONDUIT AND FEEDER	FEEDING THESE DEVICES
350	2-2" C EA W/ 3#2/0,#2/0N,#3G	ATS, G1L
400	2-2" C EA W/ 3#3/0,#3/0N,#3G	N1L
400	2-2" C EA W/ 3#3/0,#3/0N	CT CABINET

SIZING METHOD: COPPER, 60°C #12 THROUGH #1, 75°C 1/0 AND ABOVE

GENERAL ELECTRICAL NOTES:

A. ELECTRICAL CONTRACTOR SHALL COORDINATE ALL UTILITY REQUIREMENTS, FINAL LOCATIONS AND LOAD INFORMATION WITH ELECTRIC UTILITY.

KEY ELECTRICAL NOTES:

- ① PROVIDE INTEGRAL SURGE PROTECTION IN PANELBOARD, REFER TO SPECIFICATIONS FOR REQUIREMENTS.
- ② PROVIDE CONCRETE PAD OR VAULT PER ELECTRIC UTILITY COMPANY STANDARDS AND REQUIREMENTS. REFER TO SITE PLAN FOR TRANSFORMER LOCATION.
- ③ PROVIDE CONCRETE PAD FOR ENGINE/GENERATOR IN COMPLIANCE WITH ENGINE/GENERATOR MANUFACTURER REQUIREMENTS.

ACE INC
 ASSOCIATED • CONSTRUCTION • ENGINEERING
 2040 HARNISH BLVD.
 BILLINGS, MT 59102
 406-245-0136
 ACE JOB 21BL5442

LUMINAIRE SCHEDULE

FIXT TYPE LETTR	MANUFACTURER	MODEL NUMBER	MOUNTING	COLOR TEMP	LUMENS	Voltage	WATTS	DESCRIPTION
A	LITHONIA OR EQUAL	ZBTL4-60LHE-ADSM-EZ1-LP835	REC/LAY-IN	3500K	5815	120 V	43	
A2	LITHONIA OR EQUAL	ZBTL4-60LHE-ADSM-EZ1-LP835-DGA	REC/FLANGE	3500K	5815	120 V	43	
AA	LITHONIA OR APPROVED SUBSTITUTION	DSX1LED-P6-50K-T4M-MVOLT-SPA-SF-DBLXD	POLE	5000K	18635		163	
AE	LITHONIA OR EQUAL	ZBTL4-60LHE-ADSM-EZ1-LP835-EL14LSD	REC/FLANGE	3500K	5815	120 V	43	
B	LITHONIA OR EQUAL	ZGTL-4-60L-RW-A12125-EZ1-LP835	REC/LAY-IN	3500K	6218		49	
B2	LITHONIA OR EQUAL	ZGTL-F-4-60L-RW-A12125-EZ1-LP835	REC/FLANGE	3500K	6218		49	
B2E	LITHONIA OR EQUAL	ZGTL-F-4-60L-RW-A12125-EZ1-LP835-EL14L	REC/FLANGE	3500K	6218		49	
BB	HYDREL OR APPROVED SUBSTITUTION	M9720C-8-LED-P1-50K-MVOLT-NSP-FLC-345-RG-STR	IN-GRADE	5000K	3133	120 V	29	
C	GOTHAM OR EQUAL	EVO6-35/25-AR-MWD-LS-MVOLT-GZ10	CEIL/REC	3500K	2537	120 V	25	
CC	LITHONIA OR APPROVED SUBSTITUTION	DSXW1LED-10C-530-50K-TFTM-MVOLT-DBDXD	WALL/SURFACE	5000K	2212		20	
D	EUREKA OR APPROVED SUBSTITUTION	3545-24-LED-SHO-35-80-120V-DV-WI-WHE-WH	WALL/SURFACE	3500K	2411		24	
DD	LITHONIA OR APPROVED SUBSTITUTION	DSXW1LED-20C-530-50K-TFTM-MVOLT-DBDXD	WALL/SURFACE	5000K	4394		36	
DDE	LITHONIA OR APPROVED SUBSTITUTION	DSXW1LED-20C-530-50K-TFTM-MVOLT-DBDXD-ELC W	WALL/SURFACE	5000K	4394		36	
E3	LITHONIA OR EQUAL	ECRG-HO-SQ-M6	UNIVERSAL	4000K			5	DIE-CAST SINGLE FACE LED EXIT SIGN W/ EM SELF DIAGNOSTIC BATTERY PACK
E3A	LITHONIA OR EQUAL	ERE-GY-T-SQ-WP	WALL/SURFACE	4000K		120 V	1	
F	LITHONIA OR EQUAL	ZL1N-L48-7000LM-FST-MVOLT-50K-80CRI-WH-HC36	CHAIN-HUNG	5000K	7035		52	
FE	LITHONIA OR EQUAL	ZL1N-L48-7000LM-FST-120-50K-80CRI-E7W-WH-HC36	CHAIN-HUNG	5000K	7035		52	
G	PEERLESS OR APPROVED SUBSTITUTION	BRM9L-LSL-4FT-M514-80CRI-35K-ID1200LMF-40/60-MINI-ZT-MVOLT-SCT-F2/MCSJ/72A-C210	SUSPENDED CABLE	3500K	4800		45	
H	JUNO OR EQUAL	LUCES-24IN-SWW6-90CRI-WH-M6UCES-24IN-SWW6-90CRI-WH-M6	SURFACE	3500K	825		11	2' LED UNDERCABINET LIGHTING. WHITE HOUSING. COLOR TEMPERATURE SWITCH SELECTABLE, 90CRI
J	JUNO OR EQUAL	T254L-G2-35K-90CRI-PDIM-SP-WH	CEIL/TRACK	3500K	1252		15	

NOTE:
FOR TYPE AA LUMINAIRE, PROVIDE POLE LITHONIA SSS-30-6G-DM19A5-VD-DBLXD OR APPROVED SUBSTITUTION.

GENERAL REQUIREMENTS:

- LUMINAIRE TYPES DEFINED WITH A MANUFACTURER'S SERIES FOLLOWED BY "OR EQUAL" DO NOT REQUIRE PRIOR APPROVAL FOR SUBSTITUTED PRODUCTS TO BID. HOWEVER, THIS DOES NOT ALLEVIATE THE SUBSTITUTED PRODUCT FROM MEETING OR EXCEEDING THE QUALITIES AND STANDARDS SET FORTH OF THE LISTED MANUFACTURER AND SERIES.
- LUMINAIRE TYPES DEFINED WITH A MANUFACTURER'S SERIES FOLLOWED BY "OR APPROVED SUBSTITUTION" REQUIRE PRIOR APPROVAL FOR SUBSTITUTED PRODUCTS TO BID. HOWEVER, THIS DOES NOT ALLEVIATE THE SUBSTITUTED PRODUCT FROM MEETING OR EXCEEDING THE QUALITIES AND STANDARDS SET FORTH OF THE LISTED MANUFACTURER AND SERIES.

STARTER, DISCONNECT, AND CONTROL SCHEDULE

UNIT NO	MOTOR			STARTER			CONTROL		DISCONNECT		REMARKS/NOTES
	HP	VOLT PHASE	LOCATION	NEMA SIZE	TYPE	LOCATION	TYPE	LOCATION	SWITCH SIZE	FUSE SIZE	
VAP-1	5.9 kW	208/3	PROPANE TANKS	N/A	N/A	N/A	PRESSURE	AT UNIT	30A/3P	(3) 25AF	NOTE 1,4,6,7
DWH-1	205 VA	120/1	MECH/ELEC 106	FRACTIONAL	MTS	AT UNIT	THERMOSTAT	AT UNIT	30A/1P	N/A	
AHU-1	118 MCA	200/3	OUTSIDE BLDG	----- WITH UNIT ----->			TC	AT UNIT	N/A	N/A	NOTE 1
PUMP-1	1/2	200/3	OUTSIDE BLDG	----- WITH UNIT ----->			FLOAT	AT UNIT	30A/1P	N/A	NOTE 1, 7
B-1	1.2 kW	120/1	MECH/ELEC 106	----- WITH UNIT ----->			THERMOSTAT	AT UNIT	N/A	N/A	NOTE 1
B-2	1.2 kW	120/1	MECH/ELEC 106	----- WITH UNIT ----->			THERMOSTAT	AT UNIT	N/A	N/A	NOTE 1
BP-1	.12 kW	115/1	MECH/ELEC 106	FRACTIONAL	MTS	AT WALL	B-1	AT UNIT	N/A	N/A	NOTE 1,2
BP-2	.12 kW	115/1	MECH/ELEC 106	FRACTIONAL	MTS	AT WALL	B-2	AT UNIT	N/A	N/A	NOTE 1,2
HWP-1	2	200/3	MECH/ELEC 106	N/A	VFD	AT WALL	B-1, B-2	AT UNIT	N/A	N/A	NOTE 1,2
HWP-2	2	200/3	MECH/ELEC 106	N/A	VFD	AT WALL	B-1, B-2	AT UNIT	N/A	N/A	NOTE 1,2
ZP-1	1/8	115/1	LOCKER 121	FRACTIONAL	MTS	AT UNIT	TC (RZ-1)	AT UNIT	30A/1P	N/A	NOTE 3
ZP-2	1/8	115/1	RESTROOM 125	FRACTIONAL	MTS	AT UNIT	TC (RZ-2)	AT UNIT	30A/1P	N/A	NOTE 3
ZP-3	1/8	115/1	STORAGE 109	FRACTIONAL	MTS	AT UNIT	TC (RZ-3)	AT UNIT	30A/1P	N/A	NOTE 3
ZP-4	1/8	115/1	OFFICE 112	FRACTIONAL	MTS	AT UNIT	TC (RZ-4)	AT UNIT	30A/1P	N/A	NOTE 3
ZP-5	1/8	115/1	MECH/ELEC 106	FRACTIONAL	MTS	AT UNIT	TC (RZ-5)	AT UNIT	30A/1P	N/A	NOTE 3
ZP-6	1/8	115/1	MECH/ELEC 106	FRACTIONAL	MTS	AT UNIT	TC (RZ-6)	AT UNIT	30A/1P	N/A	NOTE 3
ZP-7	1/8	115/1	WORKROOM 120	FRACTIONAL	MTS	AT UNIT	TC (RZ-7)	AT UNIT	30A/1P	N/A	NOTE 3
ZP-8	1/8	115/1	JANITOR 126	FRACTIONAL	MTS	AT UNIT	TC (RZ-8)	AT UNIT	30A/1P	N/A	NOTE 3
ZP-9	1/8	115/1	STORAGE 109	FRACTIONAL	MTS	AT UNIT	TC (RZ-9)	AT UNIT	30A/1P	N/A	NOTE 3
ZP-10	1/8	115/1	CONFERENCE 107	FRACTIONAL	MTS	AT UNIT	TC (RZ-10)	AT UNIT	30A/1P	N/A	NOTE 3
AGF-1	1/3	115/1	MECH/ELEC 106	----- WITH UNIT ----->			THERMOSTAT	AT UNIT	RCPT	N/A	NOTE 5
EF-1	.0345 kW	115/1	RESTROOM 125	----- WITH UNIT ----->			OC	AT ROOM	N/A	N/A	NOTE 1
EF-2	.0345 kW	115/1	JANITOR 126	----- WITH UNIT ----->			WALL SWITCH	AT ROOM	N/A	N/A	NOTE 1
EF-3	.0345 kW	115/1	RESTROOM 115	----- WITH UNIT ----->			OC	AT ROOM	N/A	N/A	NOTE 1
EF-4	.242 kW	115/1	MECH/ELEC 106	FRACTIONAL	MTS	AT WALL	WALL SWITCH	AT ROOM	N/A	N/A	NOTE 3
EF-5	.0345 kW	115/1	RESTROOM 104	----- WITH UNIT ----->			OC	AT ROOM	N/A	N/A	NOTE 1
EF-6	.0345 kW	115/1	RESTROOM 103	----- WITH UNIT ----->			OC	AT ROOM	N/A	N/A	NOTE 1
EF-7	.0345 kW	115/1	JANITOR 102	----- WITH UNIT ----->			WALL SWITCH	AT ROOM	N/A	N/A	NOTE 1
EF-8	.096 kW	115/1	MECH/ELEC 106	FRACTIONAL	MTS	AT WALL	WALL SWITCH	AT ROOM	N/A	N/A	NOTE 3
CUH-1	.33 kW	120/1	VEST 100	N/A	N/A	N/A	THERMOSTAT	AT UNIT	N/A	N/A	NOTE 1

NOTE 1: SINGLE-POINT OF CONNECTION. ALL STARTERS, DISCONNECTS, THERMAL OVERLOADS, ETC ARE INTEGRAL WITH EQUIPMENT BY DIVISION 22/23.
 NOTE 2: EQUIPMENT COMES WITH VFD BY DIVISION 22/23. VFD HAS INTEGRAL BYPASS STARTER AND DISCONNECT.
 NOTE 3: EQUIPMENT COMES WITH INTEGRAL MOTOR STARTER.
 NOTE 4: FUSE PER MANUFACTURER'S RECOMMENDATIONS.
 NOTE 5: EQUIPMENT COMES WITH POWER SUPPLY CORD WITH NEMA 5-20P.
 NOTE 6: CLASS I, DIV 1 EQUIPMENT BY DIVISION 22/23. CONNECT TO EXPLOSION PROOF BOX PROVIDED AT BASE OF EQUIPMENT.
 NOTE 7: HEAVY-DUTY FUSED DISCONNECT SWITCH IS NEMA 3R RATED WITH LOCKING PROVISIONS.

KEY:
 B= HAND-OFF-AUTO SELECTOR SWITCH
 FT = CONTROL XFMR 120V FUSED
 FVNR= FULL VOLTAGE NON-REVERSING STARTER
 VFD= VARIABLE FREQUENCY DRIVE
 MCA= MINIMUM CIRCUIT AMPACITY
 G= GREEN "OFF" PILOT LIGHT
 SPC= SINGLE POINT CONNECTION
 FVR= FULL VOLTAGE REVERSING STARTER
 MTS= MANUAL MOTOR STARTER WITH OVERLOAD PROTECTION & LOCK-OFF GUARD (MOTOR THERMAL SWITCH)
 TC= TEMPERATURE CONTROL
 R= RED "ON" PILOT LIGHT
 OC= OCCUPANCY SENSOR
 RVS= REDUCED VOLTAGE STARTER

PROVIDE ALL MOTORS OVER 5 HP WITH SOLID STATE OVERLOADS.
 COORDINATE EXACT REQUIREMENTS WITH MECHANICAL SHOP DRAWINGS PRIOR TO ORDERING EQUIPMENT OR RUNNING FEEDERS.
 PROVIDE ALL STARTERS WITH 2 N.O. & 2 N.C. AUXILIARY INTERLOCKING RELAYS, NEMA SIZE 1 UNLESS OTHERWISE NOTED.

BIM 360//6442 - USFW HURON - VISITOR CENTER/21BL6442-ELECTRICAL_R20.MXD



ACE INC
 ASSOCIATED • CONSTRUCTION • ENGINEERING
 2040 HARNISH BLVD.
 BILLINGS, MT 59102
 406-245-0136
 ACE JOB 21BL5442




REGISTERED PROFESSIONAL ENGINEER
 CHRISTOPHER B. GREEN
 4/29/2022
 SOUTH DAKOTA

HURON WMD					SUB-SHEET
ELECTRICAL SCHEDULES					E003
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED CG	DRAWN CG	CHECKED PK	DATE 2022.04.29	DRAWING NO.	SHEET 62 OF 74

ELECTRICAL GENERAL NOTES	
A	THE FIRE ALARM SYSTEM WIRING SHALL BE INSTALLED IN CONDUIT. DRAWINGS FOR THE FIRE ALARM SYSTEMS ARE DIAGRAMMATIC ONLY. EXACT WIRING REQUIREMENTS SHALL BE PROVIDED BY THE FA SYSTEM MANUFACTURER. REFERENCE DETAIL 5/E302 AND SPEC SECTION 283111 FOR ADDITIONAL REQUIREMENTS. FIRE ALARM DEVICES SHOULD BE MOUNTED CENTERED ABOVE SWITCHES WHENEVER POSSIBLE.
B	ALL LIMITED VOLTAGE TECHNOLOGY SYSTEM CABLING LOCATED WITHIN THE CEILING SPACE SHALL BE PLENUM RATED UNLESS IT IS COMPLETELY INSTALLED IN CONDUIT. ALL FIRE ALARM CABLING SHALL BE IN A FULL CONDUIT SYSTEM, NO EXCEPTIONS.
C	ALL ACCESS CONTROL SYSTEM DEVICES, CABLING, TERMINATION AND TESTING SHALL BE INSTALLED AS PART OF A SEPARATE PROJECT ADMINISTERED BY THE OWNER. EC SHALL PROVIDE ROUGH-IN AT LOCATIONS SHOWN AND PROVIDE 120VAC POWER AT LOCATIONS SHOWN. REFERENCE SPEC SECTION 270507 FOR ADDITIONAL REQUIREMENTS.
D	ALL VIDEO SURVEILLANCE SYSTEM DEVICES, CABLING, TERMINATION AND TESTING SHALL BE INSTALLED AS PART OF A SEPARATE PROJECT ADMINISTERED BY THE OWNER. REFERENCE SPEC SECTION 270507 FOR ADDITIONAL REQUIREMENTS.
E	FOR COMMUNICATIONS, AND TELEVISION SYSTEMS CONDUIT/CONDUCTORS, REFERENCE DETAIL 2/E301 FOR TYPICAL ROOM DETAILS AND REQUIREMENTS.

ELECTRICAL GENERAL NOTES	
F	PROVIDE ALL COMMUNICATIONS OUTLETS PER DETAIL 1/E301 REQUIREMENTS.
G	ENSURE ALL EXTERIOR WALL PENETRATIONS HAVE A SLEEVE GROUDED INTO THE WALL AND THE CONDUIT ROUTED THROUGH THE SLEEVE IS CALLED INTO THE SLEEVE.
H	ALL EXTERIOR RECEPTACLES SHALL HAVE A WEATHERPROOF WHILE-IN-USE EXTRA DUTY COVER IN ACCORDANCE WITH SPECIFICATION SECTION 262726 2.5D REQUIREMENTS.
I	REFERENCE ARCHITECTURAL PLANS FOR ADDITIONAL INFORMATION ON DEVICE LOCATIONS, DIMENSIONS, ETC. CAREFULLY EXAMINE ARCHITECTURAL FLOOR PLANS, CEILING PLANS, ELEVATIONS, ETC. FOR INFORMATION THAT AFFECTS ELECTRICAL WORK. NOTIFY ARCHITECT/ENGINEER IMMEDIATELY OF ANY DISCREPANCIES BETWEEN ARCHITECTURAL AND ELECTRICAL PLANS.
J	FOR EACH DIV 23 THERMOSTAT OR TEMPERATURE SENSOR, PROVIDE FOUR SQUARE BOX WITH SINGLE GANG MUD RING AND 3/4" C (WITH 1/2" MULE TAPE) UP TO A LOCATION ABOVE THE ACCESSIBLE CEILING. SELECT SINGLE GANG MUD RING TYPE DEPENDING UPON SHEETROCK DEPTH. FIELD COORDINATE EXACT LOCATION WITH DIV 23. REFERENCE DETAIL 3/E301 FOR ADDITIONAL INFORMATION AND REQUIREMENTS.

ELECTRICAL KEYNOTES	
1	PROVIDE 2 1/8" DEEP, 4" SQUARE JUNCTION BOX WITH A SINGLE-GANG MUD RING ABOVE ACCESSIBLE CEILING FOR FUTURE WIRING ACCESS POINT (WAP). PROVIDE NUMBER OF DATA DROPS AND COMMUNICATIONS AS SHOWN. FIELD VERIFY EXACT LOCATION. PROVIDE ROUGH-IN AND 3/4" C TO NEAREST CORRIDOR LOCATION.
2	PROVIDE THREE-GANG FLOOR BOX IN COMPLIANCE WITH SPECIFICATIONS. PROVIDE TWO OPENINGS EACH WITH A GENERATOR POWER (RED) DUPLEX RECEPTACLE. PROVIDE ONE OPENING WITH 1 VOICE AND 1 DATA OUTLET. PROVIDE 3/4" C FOR EACH POWER OPENING FROM FLOOR BOX TO EMPTY JUNCTION BOX IN WALL. ROUTE CONDUIT IN FLOOR SLAB AND THEN UP WALL AND STUBBED TO CEILING SPACE. PROVIDE 1" C FOR VOICE/DATA OPENING FROM FLOOR BOX TO EMPTY JUNCTION BOX IN WALL. ROUTE CONDUIT IN FLOOR SLAB AND THEN UP WALL AND STUBBED TO CEILING SPACE. FIELD COORDINATE FINAL FLOOR BOX LOCATION WITH FINAL LOCATIONS OF ALL ROOM FURNITURE PRIOR TO INSTALLATION.
3	PROVIDE TWO-GANG FLOOR BOX IN COMPLIANCE WITH SPECIFICATIONS. PROVIDE ONE OPENING WITH A NORMAL POWER (LIGHT ALMOND) DUPLEX RECEPTACLE. PROVIDE ONE OPENING FOR FUTURE CABLING. PROVIDE 3/4" C FOR POWER OPENING FROM FLOOR BOX TO EMPTY JUNCTION BOX IN WALL. ROUTE CONDUIT IN FLOOR SLAB AND THEN UP WALL AND STUBBED TO CEILING SPACE. PROVIDE 1" C FOR FUTURE CABLING OPENING FROM FLOOR BOX TO EMPTY JUNCTION BOX IN WALL. ROUTE CONDUIT IN FLOOR SLAB AND THEN UP WALL AND STUBBED TO CEILING SPACE. FIELD COORDINATE FINAL FLOOR BOX LOCATION WITH FINAL LOCATIONS OF ALL ROOM FURNITURE PRIOR TO INSTALLATION.
4	PROVIDE TWO-GANG FLOOR BOX IN COMPLIANCE WITH SPECIFICATIONS. PROVIDE TWO OPENINGS EACH WITH A NORMAL POWER (LIGHT ALMOND) DUPLEX RECEPTACLE. PROVIDE 3/4" C FOR POWER OPENING FROM FLOOR BOX TO EMPTY JUNCTION BOX IN WALL. ROUTE CONDUIT IN FLOOR SLAB AND THEN UP WALL AND STUBBED TO CEILING SPACE. PROVIDE 1" C FOR FUTURE CABLING OPENING FROM FLOOR BOX TO EMPTY JUNCTION BOX IN WALL. ROUTE CONDUIT IN FLOOR SLAB AND THEN UP WALL AND STUBBED TO CEILING SPACE. FIELD COORDINATE FINAL FLOOR BOX LOCATION WITH FINAL LOCATIONS OF ALL ROOM FURNITURE PRIOR TO INSTALLATION.
5	FOR FUTURE EXTERIOR OFOI VSS CAMERA, PROVIDE WEATHERPROOF 2 1/8" DEEP, 4" SQUARE JUNCTION BOX WITH A SINGLE-GANG MUD RING RECESSED IN EXTERIOR WALL. PROVIDE TWO DATA DROPS AT LOCATION SHOWN. FIELD VERIFY EXACT LOCATION WITH OWNER AND GC. PROVIDE ROUGH-IN AND 3/4" C TO NEAREST CORRIDOR LOCATION. REFERENCE SPEC SECTION 270507 FOR ADDITIONAL REQUIREMENTS.
6	PROVIDE ROUGH-IN AT DOUBLE-DOOR AND CONDUIT AS REQUIRED FOR FUTURE OFOI ACCESS CONTROL SYSTEM DEVICES AND ADA DOOR OPERATOR AND ADA PUSH PLATES. FIELD COORDINATE WORK WITH GC AND OWNER. REFERENCE DETAIL 6/E301, SPEC SECTION 270507 AND DIVISION 08 FOR ADDITIONAL REQUIREMENTS. COORDINATE WORK WITH DIVISION 08 AND PROVIDE ALL INTERCONNECTING CONDUIT REQUIRED BY DIVISION 08.
7	PROVIDE ROUGH-IN AT SINGLE-DOOR AND CONDUIT AS REQUIRED FOR FUTURE OFOI ACCESS CONTROL SYSTEM DEVICES. FIELD COORDINATE WORK WITH GC AND OWNER. REFERENCE DETAIL 6/E301, SPEC SECTION 270507 AND DIVISION 08 FOR ADDITIONAL REQUIREMENTS. COORDINATE WORK WITH DIVISION 08 AND PROVIDE ALL INTERCONNECTING CONDUIT REQUIRED BY DIVISION 08.
8	CONNECTION TO ELECTRIC WATER COOLER. COORDINATE EXACT LOCATION WITH EQUIPMENT INSTALLATION.
9	PROVIDE 3/4" PLYWOOD PAINTED WITH GRAY FIRE RETARDANT PAINT ON BOTH SIDES LINING THE TELECOMMUNICATIONS ROOM TO A HEIGHT OF 8 FEET.
10	INSTALL FIRE ALARM CONTROL PANEL (FACP) AND DIGITAL ALARM COMMUNICATOR TRANSMITTER (DACT). PROVIDE TO DACT, DUAL TELEPHONE LINES WITH VOLTAGE DETECTION PER SPEC SECTION 283111 REQUIREMENTS.
11	PROVIDE SPECIFICATION GRADE, DEAD FRONT 120V, 20A GFCI DEVICE IN A 1-GANG BOX MOUNTED IN READILY ACCESSIBLE LOCATION ABOVE COUNTER. DEVICE IS CONNECTED UPSTREAM OF REFRIGERATOR RECEPTACLE.
12	RECEPTACLE FOR FULL-HEIGHT REFRIGERATOR. FIELD COORDINATE EXACT MOUNTING HEIGHT AND LOCATION WITH EQUIPMENT INSTALLATION.
13	PROVIDE RECEPTACLE FOR GARBAGE DISPOSER. COORDINATE EXACT LOCATION WITH EQUIPMENT INSTALLATION. PROVIDE 20A/1P MOMENTARY CONTACT SWITCH MOUNTED ABOVE COUNTER TO CONTROL RECEPTACLE. SWITCH IS CONNECTED UPSTREAM OF RECEPTACLE.
14	PROVIDE 'TMGB' GROUND BAR IN ACCORDANCE WITH DETAILS 4/E301 AND 5/E301.
15	PROVIDE #6AWG INSULATED COPPER GROUNDING CONDUCTOR (BONDING JUMPER) FROM 'TMGB' GROUND BAR TO IT RACK AS SHOWN.
16	CONNECTION FOR DDC PANEL. COORDINATE EXACT LOCATION WITH DIVISION 23 CONTRACTOR.
17	PROVIDE NEMA 5-20R GFCI RECEPTACLE OR HARD CONNECTION FOR LAVATORY OR SINK INFRARED SENSOR AS REQUIRED. COORDINATE EXACT REQUIREMENTS AND LOCATION WITH EQUIPMENT INSTALLATION.
18	PROVIDE ROUGH-IN FOR GC FURNISHED ELECTRIC HAND DRYER AT MOUNTING HEIGHT NOTED ON ARCHITECTURAL ELEVATIONS AND SPECIFICATION SECTION 102813. GC TO PROVIDE STRUCTURAL SUPPORT AND INSTALLATION OF ELECTRIC HAND DRYER. FIELD COORDINATE EXACT LOCATION AND REQUIREMENTS WITH EQUIPMENT INSTALLATION. PROVIDE MTS MOUNTED ABOVE ACCESS PANEL IN HARD CEILING AS SHOWN.
19	PROVIDE WALL ROUGH-IN FOR DOORBELL PUSHBUTTON AT RECEPTION AREA AND WALL ROUGH-IN FOR DOORBELL CHIME AT OFFICE AREA. PROVIDE 1/2" C (WITH 1/2" MULE TAPE) FROM DOORBELL PUSHBUTTON TO DOORBELL CHIME AS SHOWN FOR DOORBELL CONDUCTORS. FURNISH AND INSTALL TRADITIONAL RESIDENTIAL TYPE DOORBELL SYSTEM. PROVIDE 120VAC POWER CONNECTION, JUNCTION BOXES AND 2#12,#12G,3/4" C AS REQUIRED.
20	PROVIDE 2#12,#12G,3/4" C AS REQUIRED TO CONNECT EXHAUST FAN TO ROOM LIGHTING CIRCUIT.
21	LIGHTING CONTACTOR AND 24 HOUR TIMELOCK. REFERENCE DETAIL 3/E302.
22	PROVIDE 2#10,#10G,3/4" C TO SINGLE RECEPTACLE NEMA L5-30R FOR IT RACK.
23	PROVIDE 120V, 20A EMERGENCY POWER CIRCUIT FROM GIL FOR BOILER EMERGENCY SHUTDOWN PER DETAIL 1/E302 REQUIREMENTS. PROVIDE ALL PUSHBUTTONS, ELECTRICAL CONNECTIONS AND 2#12,#12G,3/4" C AS REQUIRED FOR A FULLY FUNCTIONING SYSTEM.



1 ELECTRICAL POWER AND SPECIAL SYSTEMS PLAN
E101 1/8" = 1'-0"


ACE INC
ASSOCIATED • CONSTRUCTION • ENGINEERING
2040 HARNISH BLVD.
BILLINGS, MT 59102
406-245-0136
ACE JOB 21815442



HURON WMD ELECTRICAL POWER AND SPECIAL SYSTEMS PLAN MULTIPURPOSE BUILDING AND VISITOR CENTER					SUB-SHEET E101
DESIGNED CG	DRAWN CG	CHECKED PK	DATE 2022.04.29	DRAWING NO.	SHEET 63 OF 74

BIM 360//6442 - USFW HURON - VISITOR CENTER/21815442-ELECTRICAL_R20.MXD

BIM 360/15442 - USFW HURON - VISITOR CENTER/21BL5442-ELECTRICAL_R20.MXD



ELECTRICAL LIGHTING GENERAL NOTES	
A	VERIFY THE EXACT LOCATION OF ALL LUMINAIRES WITH THE GENERAL CONTRACTOR PRIOR TO ROUGH-IN.
B	ENSURE ALL EXTERIOR WALL PENETRATIONS HAVE A SLEEVE GROUTED INTO THE WALL AND THE CONDUIT ROUTED THROUGH THE SLEEVE IS CAULKED INTO THE SLEEVE.
C	ALL CABLING LOCATED WITHIN THE CEILING SPACE SHALL BE PLENUM RATED UNLESS IT IS COMPLETELY INSTALLED IN CONDUIT. THIS INCLUDES, BUT IS NOT LIMITED TO: OCCUPANCY SENSOR/LIGHTING CONTROL CABLING.
D	FIRE SEAL ALL PENETRATIONS IN FIRE RATED WALLS. COORDINATE WITH ARCHITECT AND GC FOR LOCATIONS.
E	PROVIDE A COMPLETE WIRING SYSTEM CONSISTING OF PROPER QUANTITY OF SWITCH LEGS, NEUTRALS AND HOT CIRCUITS FOR A FUNCTIONAL INSTALLATION. ALL CIRCUITRY IS SHOWN FROM SWITCHES TO EACH CONTROLLED LUMINAIRE. EC SHALL MATCH SWITCH SUBSCRIPT TO ASSOCIATED LUMINAIRE AND CONNECT COMPLETE.
F	WHEN LIGHT SWITCHES ARE SHOWN LOCATED ON THE WALL THAT IS COMMON WITH THE END OF THE DOOR SWING INTO A SPACE. DO NOT LOCATE THE SWITCHES BEHIND THE DOOR, BUT RATHER A MINIMUM OF 6" FROM THE END OF THE SWING. VERIFY EXACT DOOR SWING PRIOR TO ROUGH-IN.
G	FOR ALL LUMINAIRES WITH AN EMERGENCY BALLAST/BATTERY PACK, PROVIDE HOT UNSWITCHED CONDUCTOR TO THE EMERGENCY BALLAST.
H	PROVIDE/INSTALL OCCUPANCY SENSORS AS SHOWN IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS. OCCUPANCY SENSORS SHALL BE INSTALLED TO REDUCE FALSE TRIPS.
I	PROVIDE/INSTALL DIMMERS COMPATIBLE WITH LED LUMINAIRES CONTROLLED. PROVIDE ALL CONDUIT/CONDUCTORS AS REQUIRED FROM LED DIMMER TO LED LUMINAIRES. ALL IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
J	CONNECT ALL OCCUPANCY SENSORS UPSTREAM OF ANY WALL SWITCHES SO THAT OCCUPANCY SENSOR RECEIVES CONTINUOUS UNSWITCHED POWER AND WALL SWITCH PROVIDES MANUAL/ LOCAL CONTROL. LUMINAIRES SHALL ONLY TURN ON IF SWITCHES ARE ON AND OCCUPANCY IS SENSED. EC SHALL WIRE ALL OCCUPANCY SENSOR SYSTEMS PER MANUFACTURER'S RECOMMENDATIONS.
K	PROVIDE ALL LOW VOLTAGE WIRING REQUIRED TO CONNECT OCCUPANCY SENSORS IN A SPACE TO THE POWER PACK ASSOCIATED WITH AN INDIVIDUAL AREA. WIRING NOT SHOWN FOR DRAWING CLARITY.
L	WHERE MULTIPLE OCCUPANCY SENSORS ARE IN A SINGLE ROOM, CONNECT SO THAT ANY SENSOR TRIPS ALL LUMINAIRES ON.


ELECTRICAL KEYNOTES	
1	PHOTOCELL TO BE LOCATED ON EXTERIOR OF BUILDING ON THE ROOF. ORIENT PHOTOCELL TO FACE NORTH.
2	PROVIDE 2#12, #12G, 1/2" C AS REQUIRED TO CONNECT TYPE E3 LUMINAIRE TO TYPE E3A REMOTE HEADS.
3	CONNECT EXTERIOR BUILDING LIGHTING CIRCUIT TO PANELBOARD GIL THRU LIGHTING CONTACTOR. REFERENCE DETAIL 3/E302.
4	PROVIDE SENSORSWITCH #WSD-V-A-LT OR APPROVED EQUAL PIR WALL SWITCH.
5	PROVIDE 0-10VDC DIMMING CONTROL TO LED LUMINAIRES. PROVIDE DUAL ON/OFF/DIM PUSH-BUTTON WALLPUSH IN LOCATION AS SHOWN, AND ALL REQUIRED CONTROLS AND CONDUIT/CONDUCTORS.
6	COORDINATE EXACT LOCATION OF LUMINAIRES IN THIS ROOM WITH MECHANICAL EQUIPMENT, DUCTWORK AND PIPING.



ACE INC
ASSOCIATED • CONSTRUCTION • ENGINEERING
2040 HARNISH BLVD.
BILLINGS, MT 59102
406-245-0136
ACE JOB 21BL5442




HURON WMD					SUB-SHEET	
ELECTRICAL LIGHTING PLAN					E102	
MULTIPURPOSE BUILDING AND VISITOR CENTER						
DESIGNED CG	DRAWN CG	CHECKED PK	DATE 2022.04.29	DRAWING NO.	SHEET 64 OF 74	



- NOTES:
1. ▽ = (1) DATA (1) PHONE JACK.
 2. SEE SPEC. SECTION 271021 FOR PLATE AND JACK REQUIREMENTS.
 3. DATA JACKS TO BE BLUE COLOR, PHONE JACKS TO BE WHITE.
 4. PLATES ARE LABELED AS SHOWN, COLOR WHITE NUMBER PLATES CLOCKWISE FROM THE DOOR.
 5. LABEL ALL DATA CABLES AT BOTH ENDS WITH "ROOM # - PLATE # - JACK #".
 6. RJ45 DATA JACK TO BE PROVIDED WITH CATEGORY 6 CABLE. RJ45 TELEPHONE JACK TO BE PROVIDED WITH CATEGORY 6 CABLE.



1 COMMUNICATIONS OUTLET
E301 NOT TO SCALE




2 TYPICAL ROOM WIRING AND CONDUIT DIAGRAM
E301 NOT TO SCALE

- W - TELEPHONE OUTLET, WALL-MOUNTED
 TV - TELEVISION OUTLET
 V³ - COMPUTER OUTLET. NUMBER INDICATES QUANTITY OF JACKS, NO NUMBER EQUALS 1 JACK.
 V³ - COMBINATION COMPUTER/TELEPHONE OUTLET, NUMBER INDICATES QUANTITY OF JACKS, NO NUMBER EQUALS 2 JACK.
- NOTES:
1. INSTALL CABLING, CONDUIT, TERMINATIONS, JACKS, DEVICES, AND PLATES. INSTALL BLANK PLATES ON ALL OUTLETS NOTED AS FUTURE.
 2. UTILIZE MINIMUM 2 1/8" DEEP, 4 INCH SQUARE BOXES WITH A SINGLE GANG MUD RING, SEE SECTION 260537. BOX MUST MEET LATEST VERSION OF TIA-569 STANDARD AND MANUFACTURER RECOMMENDATIONS.
 3. J-HOOK SYSTEM WILL BE USED FOR DATA WIRING, TELEPHONE WIRING, AND CATV WIRING. ALL FIRE ALARM AND ACCESS CONTROL SYSTEM WIRING TO BE IN CONDUIT.
 4. STUB CONDUIT FROM OUTLET CONTINUOUS TO J-HOOKS, ROUTE CONDUIT ACROSS CORRIDOR WHERE J-HOOKS ARE ON THE OPPOSITE SIDE OR IN THE CENTER. WHERE J-HOOKS IS INSTALLED IN OPEN OFFICE AREA, ROUTE CONDUIT DIRECTLY TO J-HOOKS.
 5. INSTALL A SEPARATE CABLE TO EACH DATA OUTLET, EACH TELEPHONE OUTLET, AND EACH CATV OUTLET FROM THE DATA PATCH PANELS, TELEPHONE PUNCH BLOCKS, AND CATV TERMINATION BOARD IN IT RM 116.
 6. CABLE/WIRE IDENTIFICATION: WIRE MARKERS SHALL BE PERMANENT SELF-ADHESIVE MACHINE TYPED-ON TAPE WITH CLEAR ADHESIVE OVER-WRAP, ON EACH WIRE AT EACH TERMINATION. WIRE MARKERS SHALL RETAIN THEIR MARKINGS AFTER CLEANING. IDENTIFYING NUMBERS AND LETTERS ON THE WIRE MARKERS SHALL CORRESPOND TO THOSE ON THE DETAILS AND WIRING DIAGRAMS. IDENTIFICATION SHALL ALSO INCLUDE ROOM NUMBER AND JACK NUMBER. REFERENCE SPECIFICATIONS FOR ADDITIONAL INFORMATION AND REQUIREMENTS.

3 LOW VOLTAGE RACEWAY DETAIL
E301 NOT TO SCALE




4 TELEPHONE MAIN GROUND BAR DETAIL
E301 NOT TO SCALE




5 TELEPHONE GROUNDING DETAIL AND NOTES
E301 NOT TO SCALE

1. INSULATED #6AWG IN 3/4" C ROUTED UNDERGROUND
2. INCLUDE - NON-METALLIC LABEL "WARNING IF THIS CONNECTOR ON CABLE IS LOOSE OR MUST BE REMOVED PLEASE CALL THE BUILDING MANAGER." AT ALL GROUND BARS.
3. RUN CONDUCTOR FROM GROUND TO TELEPHONE TERMINAL CABINET.
4. ALL CONNECTORS TO GROUND BARS SHALL BE 2-HOLE COMPRESSION TYPE.
5. GROUNDING BARS:
 - ELECTROLYTIC COPPER
 - MOUNTED ON FIBERGLASS INSULATORS
 - NEMA BOLT HOLE SIZING AND SPACING
6. ALL BONDING CONDUCTORS SHALL BE CONTINUOUS AND ROUTED IN THE SHORTEST POSSIBLE STRAIGHT LINE PATH.
7. ROUTE INSULATED #6AWG FROM EACH TMGB TO NEAREST VERTICAL STRUCTURAL STEEL MEMBER AND CADWELD
8. ROUTE CONDUCTOR FROM TMGB TO EACH DATA RACK AND CONNECT TO EACH DATA RACK.
9. ALL TELECOMMUNICATIONS CLOSETS WITH MULTIPLE WIRE MANAGEMENT RACKS WILL HAVE BONDING JUMPER INSTALLED AS SHOWN.

6 CARD READER ROUGH-IN DETAIL
E301 NOT TO SCALE




7 OCCUPANCY SENSOR DETAIL
E301 NOT TO SCALE




BIM 360/15442 - USFW HURON - VISITOR CENTER/21BL5442-ELECTRICAL_R20.MXD

2040 HARNISH BLVD.
BILLINGS, MT 59102
406-245-0136
ACE JOB 21BL5442


HURON WMD					SUB-SHEET
ELECTRICAL DETAILS					E301
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED CG	DRAWN CG	CHECKED PK	DATE 2022.04.29	DRAWING NO.	SHEET 65 OF 74




1 BOILER EMERGENCY SHUTDOWN
E302 NOT TO SCALE




2 POLE BASE DETAIL - RESTRAINED LOCATION
E302 NOT TO SCALE




3 EXTERIOR LIGHTING CONTROL DIAGRAM
E302 NOT TO SCALE



4 POWER CONDUITS TO LP TANK ISLAND
E302 NOT TO SCALE



5 FIRE ALARM RISER
E302 NOT TO SCALE



6 GROUNDING ELECTRODE DIAGRAM
E302 NOT TO SCALE

DETAIL GENERAL NOTES:
A. THE ELECTRICAL INSTALLATION TO THE LP TANK ISLAND SHALL COMPLY WITH NEC ARTICLE 500, AND 501. PROVIDE APPROVED SEALING FITTINGS AT ALL ENCLOSURES AND AT ALL HORIZONTAL AND VERTICAL VOUNDARIES AS DEFINED FOR HAZARDOUS AREAS.
DETAIL SPECIFIC NOTES: (#)
1. COORDINATE ENTRANCE OF CONDUITS INTO VAPORIZER WITH GENERAL CONTRACTOR AND FUELING SYSTEM INSTALLATION CONTRACTOR.

NOTES:
- ALL FIRE ALARM WIRING SHALL BE INSTALLED IN METAL CONDUIT UNLESS AN EXCEPTION IS GRANTED BY AHU.
- COORDINATE WIRE COUNTS WITH FA SYSTEM SUPPLIER.
- SEE FLOOR PLANS AND TYPICAL UNIT WIRING PLANS FOR QUANTITIES OF SIGNALING & INITIATING DEVICES.
- PROVIDE NECESSARY INTERLOCKING TO HVAC SYSTEMS.
- PROVIDE POWER TO DOOR HOLD OPENERS AS NEEDED.

BIM 360/15442 - USFW HURON - VISITOR CENTER/21BL5442-ELECTRICAL_R20.MXD

ASSOCIATED • CONSTRUCTION • ENGINEERING
2040 HARNISH BLVD.
BILLINGS, MT 59102
406-245-0136
ACE JOB 21BL5442

HURON WMD					SUB-SHEET
ELECTRICAL DETAILS					E302
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED CG	DRAWN CG	CHECKED PK	DATE 2022.04.29	DRAWING NO.	SHEET 66 OF 74

ELECTRICAL SITE PLAN SYMBOLS

THIS IS A COMPREHENSIVE SYMBOL SCHEDULE. NOT ALL SYMBOLS ARE APPLICABLE TO THESE DRAWINGS.

— PE —	PRIMARY POWER	— L —	LIGHTING
— SE —	SECONDARY POWER	— T —	TELECOMMUNICATIONS
— OHP —	OVERHEAD POWER	— C —	COMMUNICATIONS
⊘	UTILITY POWER POLE	— TV —	TELEVISION
□	UTILITY SECTIONALIZING CABINET	— FO —	FIBER OPTIC
— EUG —	UNDERGROUND ELECTRICAL POWER	— UG —	UNDERGROUND EMPTY CONDUIT

ELECTRICAL SITE PLAN NOTES


A	ALL COSTS FROM UTILITY COMPANIES (ELECTRIC, TELECOM) SHALL BE PAID DIRECTLY BY THE OWNER OUTSIDE OF THE PROJECT. COMPLY WITH ALL APPLICABLE UTILITY COMPANY STANDARDS FOR WORK PROVIDED OR INTERFACING WITH THE UTILITY COMPANIES DURING THIS PROJECT.
B	AN EFFORT HAS BEEN MADE TO DOCUMENT EXISTING DIVISION 26/27 UNDERGROUND UTILITIES. THESE UNDERGROUND UTILITIES ARE INDICATED IN A GENERAL LOCATION AND ARE NOT TO BE ASSUMED ACCURATE. CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND VERIFYING EXACT LOCATIONS AND TYPES OF ALL UNDERGROUND UTILITIES. CONTRACTOR SHALL REROUTE, EXTEND, AND/OR REPLACE UTILITIES AWAY FROM BUILDING SITE AND ASSOCIATED PROJECT SITE ALTERATION REQUIREMENTS. UTILITY EXTENSION, REPLACEMENT, ETC SHALL COMPLY WITH MATERIAL AND INSTALLATION REQUIREMENTS AS INDICATED IN CONTRACT DOCUMENTS.
C	COORDINATE TRENCHING FOR UTILITIES WITH CIVIL DRAWINGS AND GENERAL CONTRACTOR. REFERENCE CIVIL DRAWINGS FOR CONSTRUCTION PHASING DIAGRAMS.
D	FOR ALL LIGHTING CONDUITS SHOWN, PROVIDE A 1" SCH 40 PVC CONDUIT (WITH 1/2" MULE TAPE) IN TRENCH AT 18" BURIAL DEPTH) WITH THE EXCEPTION CONDUIT CROSSING UNDER ROADWAYS/DRIVEWAYS SHALL BE 24" BURIAL DEPTH AND A 1" SCH 80 PVC CONDUIT.
E	CONNECT ALL SITE LIGHTING CIRCUITS (POLE-MOUNTED AND IN-GRADE FLAGPOLE LIGHTING) TO PANELBOARD NIL THRU LIGHTING CONTACTOR. REFERENCE DETAIL 3/E302.

ELECTRICAL KEYNOTES

1	PROVIDE TRENCHING, BACKFILL AND CONDUIT AS SHOWN FOR UNDERGROUND CONDUIT/CONDUCTORS FOR VAPORIZER VAP-1. COORDINATE WORK AND EXACT REQUIREMENTS WITH GC. REFERENCE DETAIL 4/E302 FOR ADDITIONAL INFORMATION AND REQUIREMENTS. PROVIDE 3#8, #10G, 1" C FROM VAP-1 TO PANELBOARD G1L.
2	PROVIDE CONCRETE PAD FOR ENGINE/GENERATOR IN ACCORDANCE WITH STRUCTURAL DETAIL A/SS03 AND. COORDINATE AND COMPLY WITH ALL ENGINE/GENERATOR MANUFACTURER CONCRETE PAD REQUIREMENTS (FOLLOW TEMPLATE FOR EXACT UNDERGROUND CONDUIT STUB-UP LOCATIONS, ETC). REFERENCE SPECIFICATION SECTIONS 033000 AND 263213 2.8 FOR ADDITIONAL CONCRETE PAD REQUIREMENTS. FIELD COORDINATE ALL WORK WITH GC.
3	PROVIDE (2) 3" SCH 40 PVC CONDUITS WITH ROUTING AS SHOWN IN TRENCH (MIN 18" BURIAL DEPTH) FOR MAIN FEEDER FROM E/G TO AUTOMATIC TRANSFER SWITCH.
4	PROVIDE (1) 1" SCH 40 PVC CONDUIT (WITH 1/2" MULE TAPE) FOR AUTOMATIC TRANSFER SWITCH (ATS) CONTROL CABLING WITH ROUTING AS SHOWN. PROVIDE AND INSTALL RS485 (2 WIRE) CABLE OR OTHER CONTROL CABLE AS REQUIRED FROM THE GENERATOR CONTROLLER TO THE ATS WITH ROUTING AS SHOWN.
5	PROVIDE (1) 1" SCH 40 PVC CONDUIT (WITH 1/2" MULE TAPE) FOR GENERATOR ANNUNCIATOR PANEL (GAP) CABLING WITH ROUTING AS SHOWN. PROVIDE AND INSTALL GAP COMMUNICATIONS CABLING AS REQUIRED FROM THE GENERATOR CONTROLLER TO THE GAP WITH ROUTING AS SHOWN. INSTALL GAP CABLING FURNISHED WITH THE E/G.
6	POWER CONNECTION FOR SEWER LIFT STATION PUMP (PUMP-1). PROVIDE CIRCUIT CONSISTING OF 3#8, #10G, 1" C. FIELD VERIFY EXACT LOCATION AND ELECTRICAL REQUIREMENTS WITH GC PRIOR TO CONDUIT ROUTING AND CONNECTION. PROVIDE UNISTRUT STRUCTURE (VERTICAL AND HORIZONTAL CROSSMEMBERS, BACKBOARD, AND SUPPORTS) AS REQUIRED TO MOUNT PUMP-1 CONTROLLER, STARTER, DISCONNECT SWITCH, ETC. PROVIDE CONCRETE FOR FOOTINGS AS REQUIRED TO SECURE UNISTRUT STRUCTURE TO THE EARTH AND PROVIDE GROUND ROD AND CONNECT UNISTRUT STRUCTURE PER NEC REQUIREMENTS.
7	PROVIDE CONCRETE POLE BASE IN ACCORDANCE WITH DETAIL 2/E302 REQUIREMENTS.
8	PROVIDE HUBBELL QUAZITE #PG1324BA24 OR EQUAL UNDERGROUND PULL BOX WITH HUBBELL QUAZITE #PG1324HH0021 OR EQUAL COVER.
9	PROVIDE 30A/3P FUSED DISCONNECT SWITCH AT THIS LOCATION WITH UPSTREAM SEALOFFS AT BOTH THE BUILDING AND VAP-1 AS SHOWN ON DETAIL 4/E302. REFERENCE MOTOR STARTER SCHEDULE FOR DISCONNECT SWITCH TECHNICAL CHARACTERISTICS.
10	PROVIDE AND INSTALL METER SOCKET AND TRANSITION CABINET AT APPROXIMATE LOCATION SHOWN IN ACCORDANCE WITH NORTHWESTERN ENERGY (ELECTRIC UTILITY) REQUIREMENTS. FIELD COORDINATE ALL WORK WITH GC AND KIRBY WICKS 605-353-7609 AT NORTHWESTERN ENERGY.
11	PROVIDE AND INSTALL CONCRETE PAD AND CABLE WELL FOR NORTHWESTERN ENERGY TRANSFORMER IN ACCORDANCE WITH NORTHWESTERN ENERGY REQUIREMENTS. REFERENCE STANDARD 36-C-22 FOR 3-PHASE XFMR 150 KVA AND LESS. FIELD COORDINATE ALL WORK WITH GC AND KIRBY WICKS 605-353-7609 AT NORTHWESTERN ENERGY.
12	PROVIDE 3#8, #10G, 1" C FROM ENGINE/GENERATOR PANEL TO PANELBOARD G1L.
13	PROVIDE 2#8, #10G, 1" C FOR ENTIRE POLE-MOUNTED LIGHTING CIRCUIT TO PANELBOARD NIL.



ELECTRICAL SITE PLAN
 1" = 20'-0"




ACE INC
 ASSOCIATED • CONSTRUCTION • ENGINEERING
 2040 HARNISH BLVD.
 BILLINGS, MT 59102
 406-245-0136
 ACE JOB 21BL5442



BIM 360//6442 - USFW HURON - VISITOR CENTER/21BL5442-ELECTRICAL_R20.MT

HURON WMD					SUB-SHEET	
ELECTRICAL SITE PLAN					ES101	
MULTIPURPOSE BUILDING AND VISITOR CENTER						
DESIGNED CG	DRAWN CG	CHECKED PK	DATE 2022.04.29	DRAWING NO.	SHEET 67 OF 74	

PLUMBING FIXTURE SCHEDULE

PLAN CODE	ITEM	MANUF.	MODEL NUMBER	MATERIAL & FINISH	TRIM	ROUGH-IN SIZE					REMARKS
						CW	HW	SAN	VENT	A.S.S.E. 1070 TMV	
EWC-1	ELECTRIC WATER COOLER	ELKAY	EZ8WSLK	STAINLESS STEEL	BOTTLE FILLER EZWSR	1/2"	-	2"	2"	-	WATER COOLER WITH BOTTLE FILLING STATION. MOUNT TO CONFORM TO ALL A.N.S.I. & A.D.A. REQUIREMENTS.
FD-1	FLOOR DRAIN	SILOUX CHEIF	832-25D-NR-V	DURA COATED CAST IRON BODY	POLISHED NICKEL BRONZE TOP	-	-	2"	2"	-	PROVIDE WITH SHIM KIT #832-53, PROVIDE WITH TRAP PRIMER CONNECTION. SEE 1/P301 FOR DETAIL.
FS-1	FLOOR SINK	J.R. SMITH	3140Y-13	NICKEL BRONZE	-	-	-	3"	2"	-	PROVIDE WITH TRAP PRIMER CONNECTION, 3/4 GRATE. SEE 2/P301 FOR DETAIL.
HB-1	HOSE BIBB	WOODFORD	67	CHROME	"T" HANDLE KEY	3/4"	-	-	-	-	FREEZELESS, BACKFLOW PROTECTED HOSE BIBB.
LAV-1	WALL MOUNTED LAVATORY	AMERICAN STANDARD	LUCERNE #0356.421	VITREOUS CHINA	KOHLER K-7515-VS	1/2"	1/2"	2"	2"	X	PROVIDE ASSE 1070 COMPLIANT THERMOSTATIC MIXING VALVE, INSULATE HW, CW, SAN, & STOPS. INSTALL TO CONFORM TO ALL A.N.S.I. & A.D.A. REQUIREMENTS. PROVIDE FAUCET WITH 0.5 GPM AERATOR & COMMERCIAL CHAIR TYPE CARRIERS. TOUCHLESS FAUCET. 120V POWER BY E.C.
MS-1	MOP SINK	FIAT	MSB 2424	MOLDED-STONE	MOEN COMMERCIAL #8124	3/4"	3/4"	3"	2"	-	SERVICE SINK FAUCET SHALL HAVE VACUUM BREAKER, CHECKS, SERVICE STOPS, PAIL HOOK, TOP WALL BRACE & LEVER HANDLES, PROVIDE WITH FIAT HOSE & BRACKET #832-AA, MOP HANGER #830AA & WALL GUARDS MSG2424
S-1	DOUBLE COMPARTMENT SINK	ELKAY	LRAD332265PD	STAINLESS STEEL	KOHLER K-23766-VS	1/2"	1/2"	2"	2"	X	PROVIDE SINK WITH 4 HOLE CONFIGURATION, CENTER-REAR DRAIN IN BOTH BOWLS FOR DISPOSAL INSTALLATION, ASSE 1070 COMPLIANT THERMOSTATIC MIXING VALVE, INSULATE HW, CW, & STOPS AS REQ'D. INSTALL TO CONFORM TO ALL A.N.S.I. & A.D.A. REQUIREMENTS. PROVIDE FAUCET WITH 1.5 GPM AERATOR, TOUCHLESS FAUCET. 120V POWER BY E.C.
WB-1	ICEMAKER BOX	GUY GRAY	A89702	PLASTIC	-	1/2"	-	-	-	-	-
WC-1	WATER CLOSET, FT, H.C.	AMERICAN STANDARD	CADET #215AA709	VITREOUS CHINA	-	1/2"	-	4"	2"	-	12" ROUGH-IN. PROVIDE W/ BEMIS 16555SCT HEAVY DUTY OPEN FRONT SEAT LESS COVER. WATER CLOSET UTILIZES BATTERY POWERED TOUCHLESS FLUSH.

- NOTES:
- PROVIDE ALL FIXTURES WITH APPROPRIATE COMMERCIAL CARRIERS, CAST P-TRAPS, GRID STRAINERS, QUARTER TURN BALL STOPS AND MIXING VALVES FOR A COMPLETE INSTALLATION. REFER TO ARCHITECTURAL DRAWINGS FOR MOUNTING HEIGHTS.
 - VERIFY FLOOR FINISH THICKNESS BEFORE SETTING ANY FIXTURE.
 - ALL LAVATORIES AND SINKS TO BE PROVIDED WITH THERMOSTATIC MIXING VALVES TO TEMPER HOT WATER TO 110°F, MIXING VALVE SHALL CONFORM TO ASSE 1070.
 - PROVIDE FLUSH MOUNTED LOCKABLE ACCESS PANELS AS NEEDED FOR PLUMBING ACCESSORY ACCESS. COORDINATE LOCATION WITH ARCHITECT AND G.C. PRIOR TO ACCESSORY AND ACCESS DOOR INSTALLATION. REFER TO ARCHITECTURAL SPECIFICATIONS FOR ACCESS DOOR REQUIREMENTS.

DOMESTIC HOT WATER HEATER SCHEDULE

PLAN CODE	MANUF.	MODEL NUMBER	MBH INPUT @ SEA LEVEL	MBH OUTPUT @ SEA LEVEL	THERMAL EFF.	MAXIMUM FLOW RATE	FUEL SOURCE	ELECTRICAL	PHYSICAL SIZE	REMARKS
DWH-1	RINNAI	RUR199IP	199	183	92%	9.8 GPM	LPG	120V/205W	18.3" x 10.1" x 31.2"	SEE NOTES

- NOTES:
- INTAKE AND VENTING SHALL BE OF THE SEALED-COMBUSTION DIRECT-VENT METHOD. FOLLOW MANUFACTURER'S INSTALLATION GUIDELINES.
 - PROVIDE AND INSTALL A GAS SHUT-OFF VALVE AND 6" DIRT LEG ON THE GAS LINE SERVING THE WATER HEATER, SEE 5/P301.
 - REFER TO DETAIL 3/P302 FOR ADDITIONAL INSTALLATION REQUIREMENTS.
 - PROVIDE WITH CONDENSATE NEUTRALIZER. INSTALL ON CONDENSATE DRAIN LINE FOR WATER HEATER (DWH-1).
 - WATER HEATER PROVIDED WITH INTEGRATED RECIRCULATION PUMP.

POTABLE WATER EXPANSION TANK SCHEDULE

PLAN CODE	MANUF.	MODEL NUMBER	ACCEPTANCE VOLUME	TANK VOLUME	PIPE SIZE	REMARKS
PET-1	WATTS	PLT-5	1.26	2.1	3/4"	SEE NOTES.

- NOTES:
- REFER TO DETAIL 3/P302 FOR EXPANSION TANK LOCATION.
 - EXPANSION TANK AND ALL ASSOCIATED COMPONENTS SHALL BE CERTIFIED FOR POTABLE WATER USE.

ELECTRIC PROPANE VAPORIZER

PLAN CODE	MANUF.	MODEL	CAPACITY	VOLT	POWER	PH	SIZE (L X W X H)	REMARKS
V-1	ALGAS	TORREX TX50	2200 MBH	208	5.9 KW, 16.4A	3	19" x 19" x 54"	SEE 1/P302

- NOTES:
- PROVIDE WITH VALVE AND STRAINER KIT, WALL MOUNTING KIT.
 - VAPORIZER TO BE DESIGNED FOR INSTALLATION ON OR NEAR PROPANE TANK, EXPLOSION PROOF ENCLOSURE.









PROPANE FUEL LOAD SUMMARY









ITEM		INPUT DEMAND	DEMAND UNITS
TAG	DESCRIPTION		
DWH-1	DOMESTIC HOT WATER HEATER	199	MBH
B-1	BOILER	399	MBH
B-2	BOILER	399	MBH
AHU-1	AIR HANDLER	270	MBH
GEN	ENGINE GENERATOR	1063	MBH
TOTAL GAS LOAD		2330	MBH

- NOTES:
- PROPANE DELIVERY PRESSURE 11" W.C. IN BUILDING. PROVIDE REGULATOR TO 11" W.C. AT GENERATOR CONNECTION TO PROPANE TANK ASSEMBLY.
 - DISTANCE TO MOST REMOTE FIXTURE APPROX. 15' FROM REGULATOR TO AHU-1
 - (2) 1000 GAL PROPANE TANK TO BE PURCHASED BY OWNER. M.C. TO MOUNT & PIPE TANKS IN PARALLEL WITH APPROPRIATE SHUT OFF VALVES AND ACCESSORIES. SEE 1/P30. SEE CIVIL PLANS FOR MORE INFORMATION.




PLUMBING SYMBOLS LEGEND



GENERAL PIPING

 DIRECTION OF FLOW
 REDUCER FITTING
 ELBOW TURNED UP
 ELBOW TURNED DN.
 DROP IN HORIZ. RUN
 TEE TURNED UP
 TEE TURNED DN.
 BELL AND SPIGOT



 TEE IN HORIZ. RUN
 BRANCH TEE W/ OFFSET
 BRANCH TEE TURNED UP
 BRANCH TEE TURNED DN.
 CROSS IN HORIZ. RUN
 90° AND 45° ELBOWS
 END CAP CONNECTION
 UNION FITTING

DOMESTIC PIPING TYPES


















 -CW- DOMESTIC COLD WATER
 -HW- DOMESTIC HOT WATER
 -HWRC- DOMESTIC HOT WATER RECIRC.

















 -SAN- SANITARY WASTE
 -V- VENT

MISCELLANEOUS/MECHANICAL PIPING TYPES

 -CD- CONDENSATE DRAIN
 -LPG- LIQUID PETROLEUM GAS

PIPING FITTINGS, VALVES & SPECIALTIES

 NEW PLUMBING FIXTURE
 FIXT. NUMBER - SEE SCHED.
 BALL VALVE
 GATE VALVE
 GLOBE VALVE
 PLUG VALVE
 CHECK VALVE
 SOLENOID GATE VALVE
 BALANCING VALVE
 FLOAT VALVE
 DRAIN
 WALL HYDRANT OR HOSE BIBB
 FLEX. CONNECTION
 SENSOR (TEMP./FLOW)
 TEMP. GAUGE
 PRESSURE GAUGE
 FIRE EXTINGUISHER

 ANGLE VALVE
 BUTTERFLY VALVE
 PRESS. REDUCING
 2-WAY (ELECTRIC)
 2-WAY (PNEU. MTR.)
 2-WAY (SOLENOID)
 PNEUMATIC MOTOR
 3-WAY (ELECTRIC)
 3-WAY (PNEUMATIC)
 3-WAY (PNEU. MTR.)
 STRAINER
 STRAINER W/ BLOW-OFF
 VENT THRU ROOF
 PUMP
 P.O.D.C. - POINT OF DISCONNECTION
 P.O.C. - POINT OF CONNECTION

THIS IS A STANDARDIZED SYMBOLS LEGEND. ALL SYMBOLS SHOWN MAY NOT APPEAR ON OR WITHIN THIS SET OF CONTRACT DOCUMENTS.

PLUMBING SHEET LIST

P001	PLUMBING COVER SHEET
P101	FIRST FLOOR PLUMBING DOMESTIC WASTE AND VENT PLAN
P102	FIRST FLOOR PLUMBING DOMESTIC WATER PLAN
P103	ROOF PLUMBING PLAN
P301	PLUMBING DETAILS
P302	PLUMBING DETAILS
PS101	PLUMBING SITE PLAN



 ASSOCIATED • CONSTRUCTION • ENGINEERING
 2040 HARNISH BLVD.
 BILLINGS, MT 59102
 406-245-0136
 ACE JOB 21BL5442



HURON FISH AND WILDLIFE					SUB-SHEET	
PLUMBING COVER SHEET					P001	
MULTIPURPOSE BUILDING AND VISITOR CENTER						
DESIGNED AS	DRAWN TA	CHECKED TM	DATE 2022.04.29	DRAWING NO. 29320.07	SHEET 68 OF 74	

PLUMBING GENERAL DOMESTIC WASTE AND VENT NOTES	
1	CONTRACTOR SHALL CUT ALL FLOORS, WALLS, CEILINGS, AND ROOF AS REQUIRED TO PERFORM THE WORK DEPICTED IN THESE CONTRACT DOCUMENTS AND SPECIFICATIONS. GENERAL CONTRACTOR SHALL PATCH ALL ASSOCIATED FLOORS, WALLS, CEILINGS, AND ROOF AS REQUIRED TO THE SATISFACTION OF THE ARCHITECT/ENGINEER.
2	COORDINATE PLUMBING EQUIPMENT AND PIPING WITH ALL OTHER TRADES AS REQUIRED. COORDINATE PLUMBING SYSTEMS WITH THE OWNER PROVIDED EQUIPMENT.
3	REFERENCE ARCHITECTURAL PLANS FOR EXACT FIXTURE LOCATIONS.
4	COORDINATE UNDERSLAB PIPING WITH FOOTINGS AND STEM WALLS.
5	PROVIDE ALL FLOOR DRAINS AND FLOOR SINKS WITH TRAP PRIMERS. PROVIDE WALL ACCESS PANEL FOR TRAP PRIMER ACCESS AS REQUIRED. ACCESS PANELS SHALL BE RATED WHERE REQUIRED.
6	ALL UNDERFLOOR VENT SHALL BE MINIMUM 2".
7	PROVIDE CLEANOUTS ON ALL LINES SERVING SINKS.
8	CONTRACTOR SHALL COORDINATE PIPE ROUTING AND EQUIPMENT PLACEMENT WITH THE SHEET METAL, HYDRONIC PIPING, FIRE PROTECTION, AND EXISTING SYSTEMS PRIOR TO INSTALLING. THE SHEET METAL DUCT WORK SHALL HAVE THE ROUTING PRIORITY. PROVIDE OFFSETS AND TRANSITIONS AS REQUIRED.
9	CONTRACTOR SHALL VERIFY ALL SANITARY AND STORM DRAINAGE INVERT ELEVATIONS PRIOR TO INITIATING ANY WORK.
10	DRAWINGS REPRESENT GENERAL ROUTING. NOT ALL EXISTING CONDITIONS ARE SHOWN. CONTRACTOR SHALL MAKE PIPING OFFSETS AND TRANSITIONS AS NEEDED. CONTRACTOR SHALL FIELD VERIFY ALL EXISTING SIZES AND LOCATIONS PRIOR TO BIDDING AND CONSTRUCTING.
11	COORDINATE ALL PIPE PENETRATIONS WITH THE NEW STRUCTURAL LAYOUTS.
12	SPACE ABOVE CEILING BEING USED AS A RETURN AIR PLENUM. ALL MATERIALS TO BE RATED FOR PLENUM USE. MUST MEET 25/50 FLAME AND SMOKE SPREAD RATING.

PLUMBING KEYNOTES	
1	SEE CIVIL DRAWINGS FOR CONTINUATION.
2	SEE 4/P301 FOR PLUMBING CLEANOUT DETAILS, TYP.
3	2" VENT FROM (2) LAV-1 AND EWC-1. ROUTE OVER TO VTR.
4	3" VTR. SEE 3/P301 FOR VTR INSTALLATION DETAIL.
5	2" VENT DOWN UP IN WALL AND OVER TO VTR.
6	SEE 6/P301 FOR CONCENTRIC VENT DETAIL. CONFIRM CONCENTRIC VENT SIZING WITH MANUFACTURER'S REQUIREMENTS.
7	CIRCUIT VENT UP IN WALL. CONNECT TO VENT SYSTEM.




1 FIRST FLOOR PLUMBING DOMESTIC WASTE AND VENT PLAN
 P101 1/8" = 1'-0"



HURON FISH AND WILDLIFE FIRST FLOOR PLUMBING DOMESTIC WASTE AND VENT PLAN MULTIPURPOSE BUILDING AND VISITOR CENTER					SUB-SHEET P101
DESIGNED AS	DRAWN TA	CHECKED TM	DATE 2022.04.29	DRAWING NO. 29320.07	SHEET 69 OF 74

BIM 360/15442 - USFW HURON - VISITOR CENTER/21BL5442-PLUMBING_R20.rvt

BIM 360/16442 - USFW HURON - VISITOR CENTER/21BL5442-PLUMBING_R20.rvt



1 ROOF PLUMBING PLAN
 P103 1/8" = 1'-0"


PLUMBING GENERAL NOTES	
1	PLUMBING CONTRACTOR SHALL CUT ALL FLOORS, WALLS, CEILINGS, AND ROOF AS REQUIRED TO PERFORM THE WORK DEPICTED IN THESE CONTRACT DOCUMENTS AND SPECIFICATIONS. GENERAL CONTRACTOR SHALL PATCH ALL ASSOCIATED FLOORS, WALLS, CEILINGS, AND ROOF AS REQUIRED TO THE SATISFACTION OF THE ARCHITECT/ENGINEER.
2	COORDINATE HVAC AND PLUMBING EQUIPMENT WITH ALL OTHER TRADES AS REQUIRED.
3	REFERENCE ARCHITECTURAL PLANS FOR EXACT FIXTURE LOCATIONS.
4	ALL VALVES LESS THAN 2" SHALL BE BALL VALVES UNLESS OTHERWISE NOTED.
5	COORDINATE UNDERSLAB PIPING WITH FOOTINGS AND STEM WALLS.
6	INSULATION ON ALL DOMESTIC COLD WATER PIPING SHALL BE PROVIDED WITH A CONTINUOUS VAPOR BARRIER. OVERSIZE HANGERS FOR INSULATION SO NO PENETRATION OF THE VAPOR BARRIER OCCURS. PROVIDE INSERTS AND SADDLES AS REQUIRED TO PREVENT INSULATION DAMAGE FROM SUPPORTS.
7	NO DOMESTIC WATER PIPING SHALL BE ROUTED IN ANY EXTERIOR WALLS.
8	PROVIDE ALL FLOOR DRAINS AND FLOOR SINKS WITH TRAP PRIMERS. PROVIDE WALL ACCESS PANEL FOR TRAP PRIMER ACCESS AS REQUIRED. ACCESS PANELS SHALL BE RATED WHERE REQUIRED.
9	ALL UNDERFLOOR VENT SHALL BE MINIMUM 2".
10	ALL UNDERFLOOR COPPER SHALL BE TYPE "K" SEAMLESS.
11	PROVIDE CLEANOUTS ON ALL LINES SERVING SINKS AND URINALS.

PLUMBING KEYNOTES	
1	3" VTR. SEE 3/P301 FOR VTR INSTALLATION DETAIL.


ACE INC
 ASSOCIATED • CONSTRUCTION • ENGINEERING
 2040 HARNISH BLVD.
 BILLINGS, MT 59102
 406-245-0136
 ACE JOB 21BL5442




HURON FISH AND WILDLIFE					SUB-SHEET	
ROOF PLUMBING PLAN					P103	
MULTIPURPOSE BUILDING AND VISITOR CENTER						
DESIGNED AS	DRAWN TA	CHECKED TM	DATE 2022.04.29	DRAWING NO. 29320.07	SHEET 71 OF 74	




1 FLOOR DRAIN DETAIL
NOT TO SCALE




2 FLOOR SINK DETAIL
NOT TO SCALE




3 VENT THROUGH ROOF DETAIL
NOT TO SCALE




4 CLEAN OUT DETAILS
NOT TO SCALE




5 LPG CONNECTION DETAIL
NOT TO SCALE



6 CONCENTRIC VENT DETAIL
NOT TO SCALE



7 RADON COLLECTION SYSTEM DETAIL
NOT TO SCALE



NOTES:


- 1) SEAL ALL PENETRATIONS AND CRACKS/JOINTS IN CONCRETE FLOOR WITH POLYURETHANE (NO SILICONE CAULKS) SEALANT/CAULK. THIS SHALL INCLUDE SEWER PIPE, CONDUIT, AND OTHER PENETRATIONS INCLUDING SLAB JOINTS, POUR JOINTS, FLOOR/WALL JOINTS, ETC. USE BACKER ROD WHEN APPLYING CAULK IN LARGE CRACKS.
- 2) PROVIDE 4 - 6 INCHES OF ASTM SIZE #5 AGGREGATE OR EQUIVALENT UNDER ENTIRE SLAB.
- 3) INSTALL SYSTEM PER DETAILS ON THIS SHEET.
- 4) REFERENCE EPA "RADON PREVENTION IN THE DESIGN OF CONSTRUCTION OF SCHOOLS AND OTHER LARGE BUILDINGS" DOCUMENT DATED 6/1994.

ACE INC.
ASSOCIATED • CONSTRUCTION • ENGINEERING
2040 HARNISH BLVD.
BILLINGS, MT 59102
406-245-0136
ACE JOB 21BL5442




BIM 360//6442 - USFW HURON - VISITOR CENTER/21BL5442-PLUMBING_R20.rvt


HURON FISH AND WILDLIFE					SUB-SHEET	
PLUMBING DETAILS					P301	
MULTIPURPOSE BUILDING AND VISITOR CENTER						
DESIGNED AS	DRAWN TA	CHECKED TM	DATE 2022.04.29	DRAWING NO. 29320.07	SHEET 72 OF 74	



1 PROPANE TANK CONFIGURATION DETAIL
NOT TO SCALE



2 WATER RISER DETAIL
NOT TO SCALE



3 DOMESTIC WATER HEATING PIPING DETAILS
NOT TO SCALE


ACE INC
ASSOCIATED • CONSTRUCTION • ENGINEERING
2040 HARNISH BLVD.
BILLINGS, MT 59102
406-245-0136
ACE JOB 21BL5442





HURON FISH AND WILDLIFE					SUB-SHEET
PLUMBING DETAILS					P302
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED AS	DRAWN TA	CHECKED TM	DATE 2022.04.29	DRAWING NO. 29320.07	SHEET 73 OF 74

BIM 360/15442 - USFW HURON - VISITOR CENTER/21BL5442-PLUMBING_R20.MXD

PLUMBING KEYNOTES	
1	3/4" LPG CONNECTION TO ENGINE GENERATOR. SEE 5/P301 FOR GAS CONNECTION. PROVIDE REGULATOR FROM 10PSI TO 11" W.C.
2	3/4" LPG CONNECTION TO AHU-1. SEE 5/P301 FOR GAS CONNECTION DETAIL.





1 PLUMBING SITE PLAN
 PS101 1" = 20'-0"


ACE INC
 ASSOCIATED • CONSTRUCTION • ENGINEERING
 2040 HARNISH BLVD.
 BILLINGS, MT 59102
 406-245-0136
 ACE JOB 21BL5442



HURON FISH AND WILDLIFE				SUB-SHEET	
PLUMBING SITE PLAN				PS101	
MULTIPURPOSE BUILDING AND VISITOR CENTER					
DESIGNED AS	DRAWN AS	CHECKED TM	DATE 2022.04.29	DRAWING NO. 29320.07	SHEET 74 OF 74

BIM 360/16442 - USFW HURON - VISITOR CENTER/21BL5442-PLUMBING_R20.M