



			TAG ACTIVATION	LIGHTING CONTROL - SEQUENCE OF OPERATION DECRIPTION	SCHEDULE	LIGHTING GENERAL NOTE 1. REFER TO SPECIFICATION SECTION 26 0923 FOR ADDITIONAL DET
			A AUTO ON/OFF w/ DIMMING AUTO ON/OFF w/ WALL MO B MANUAL ON/OFF	JNTED AND/OR CEILING MOUNTED SENSOR(S) AS INDICATED ON PLANS. FIXTURE LIGHTING SHALL OPERATE MANUAL ON/OFF VIA TOGGLE SWITCH(ES)		MITHUR CONTROL C
						 3. INSTALL DEVICES SUCH THAT NO TWO DEVICES ON OPPOSITES S SAME WALL ARE WITHIN 6" OF EACH OTHER. 4. COORDINATE ALL DEVICES WITH ARCHITECTURAL PLANS AND CA
						5. ALL LIGHTING FIXTURES SHALL BE INSTALLED IN SUCH A WAY THAT ACCESSIBLE WITHOUT CUTTING OF CEILING. THE DESIGN TEAM SHIMMEDIATELY OF AREAS WHERE THIS IS NOT POSSIBLE.
						 6. ALL WALL-MOUNTED FIXTURES SHALL HAVE THEIR EXACT ROUGH DETERMINED BY THE DESIGN TEAM PRIOR TO ROUGH-IN. 7. THE ELECTRICAL CONTRACTOR SHALL EXTEND AN "UNSWITCHED CONDUCTOR FROM THE NEAREST LIFE SAFETY CIRCUIT TO EXIT S FOR EMERGENCY EGRESS OPERATION.
						8. CONTRACTOR SHALL PROVIDE A UL924 RATED TRANSFER DEVICE WHERE EMERGENCY EGRESS LIGHTING IS REQUIRED PER NFPA 10 CONTROLS MANUFACTURER SHALL DETERMINE EXACT QUANTITIE CONTROL ZONES AND LAYOUTS.
						9. UNLESS NOTED OTHERWISE BY DESIGNATED LIGHTING CONTROL SWITCHES SHOWN SHALL CONTROL ALL FIXTURES IN THE ROOM.
		ES90C2				10. REFER TO ARCHITECTURAL ELEVATIONS AND REFLECTED CEILIN THE SPECIFIC DEVICE ROUGH-IN AND PLACEMENT. ANY DEVIATION ARCHITECTURAL ELEVATIONS AND REFLECTED CEILING PLANS SHAND APPROVED BY THE DESIGN TEAM PRIOR TO ROUGH-IN.
						LIGHTING PLAN KEYED NOTES
		E E				L1 NO LIGHTING SCOPE IN THIS AREA.
7		E E E	L1 E E E	SE E E		REINSTALL AFTER ARCHITECTURAL WORK HAS BEEN CORECT AND RESTORE TO ORIGINAL FUNCTIONALITY EXTEND EXISTING 120V LIFE SAFETY BRANCH CIRCUIT F
STM	EB90W2 EB90W3 EB90W3	\$\$ F. F.	E E E E E E E			ES90C2 TO NEW LIGHT FIXTURES IN THIS SPACE. PROVII AS REQUIRED TO BE CONTROLLED WITH LIGHTING IN TH
I L	90W1 E EB90W1 E EB90W1 E EB90W1 E E E E E E E E E E E E E E E E E E E		A A A A A A A A A A A A A A A A A A A	E L1		NOTE: NOT ALL KEYED NOTES MAY BE USED ON EACH P
	E E E	EX \$\$ EX \$\$	FA L3 FA FA FA			
		E E E E	FA FA FA FA	A S S		
			EC90W1-22 FA	EA FA	——————————————————————————————————————	
			FA L3	FA		
			BB-20	A A A A A A A A A A A A A A A A A A A		
	E		SCOPE PROCESSING BB-20B	FA L3	D.3)	
	E E E	E E E E E	EC90W1-24 A PREPYASE SAME TO SAME T	MBLY / STORAGE B-18C MECHANICAL BA-70A		
	_ E	E E E E E		FB EXR L2		
			E E FA FA	FAN BA-70C EXR L4		
	E E			L3 S EA EXR E		
1 LOV	VER LEVEL - LIGHTING PLAN = 1'-0"					
1/0					NORTH	
						KEY PLAN LOWER LEVEL
						BID DOCUMENT SUB
	CONSULTANT	DESIGNER OF RECORD	STAMP Office of	Drawing Title LOWER LEVEL - LIGHTING PLAN	Phase Project Title PFF	
	♦IMEG	ANDERSON	I hereby certify that this plan, specification, or report was prepared by me or under my direct supervision and that I am a duly Licensed Construction and Facilities	es	FOR	R SPS EQUIPMENT Building I 9
	2882 106TH STREET DES MOINES IA 50322	13605 1st Ave. N. #100 Plymouth, MN 55441 P 763.412.4000 F 763.412.4090 ae-mn.com	Print Name: Andrew T. Weber	nt Approved:	FULLY SPRINKLERED Issue Date	GO, ND
		Anderson Engineering of Minnesota, LLC Proj # 17639	Signature:Audrew 7. Weber U.S. Depart of Veteran	tment	O1/22/	Checked Drawn E





COPPER CONDUCTOR AND CONDUIT SIZING CHART

	CONDU	JCTORS (THW	CONE	DUIT	PARALLEL				
	PHASE	NEUTRAL	GROUND	EMT	SCH 80	RUNS			
15/3	(3) #12 AWG	-	#12 AWG	1/2"	3/4"	1			
20/3	(3) #12 AWG	-	#12 AWG	1/2"	3/4"	1			
25/3	(3) #10 AWG	-	#10 AWG	1/2"	3/4"	1			
30/3	(3) #10 AWG	-	#10 AWG	1/2"	3/4"	1			
35/3	(3) #8 AWG	-	#10 AWG	3/4"	1"	1			
40/3	(3) #8 AWG	-	#10 AWG	3/4"	1"	1			
45/3	(3) #6 AWG	-	#10 AWG	1"	1"	1			
50/3	(3) #6 AWG	-	#10 AWG	1"	1"	1			
60/3	(3) #4 AWG	-	#10 AWG	1-1/4"	1-1/4"	1			
70/3	(3) #4 AWG	-	#8 AWG	1-1/4"	1-1/4"	1			
80/3	(3) #3 AWG	-	#8 AWG	1-1/4"	1-1/4"	1			
90/3	(3) #2 AWG	-	#8 AWG	1-1/4"	1-1/4"	1			
100/3	(3) #2 AWG	-	#8 AWG	1-1/4"	1-1/4"	1			
110/3	(3) #2 AWG	-	#6 AWG	1-1/4"	1-1/2"	1			
125/3	(3) #1 AWG	-	#6 AWG	1-1/2"	2"	1			
150/3	(3) 1/0 AWG	-	#6 AWG	2"	2"	1			
175/3	(3) 2/0 AWG	-	#6 AWG	2"	2"	1			
200/3	(3) 3/0 AWG	-	#6 AWG	2"	2-1/2"	1			
225/3	(3) 4/0 AWG	-	#4 AWG	2-1/2"	2-1/2"	1			
250/3	(3) 250 MCM	-	#4 AWG	2-1/2"	3"	1			
300/3	(3) 350 MCM	-	#4 AWG	3"	3"	1			
350/3	(3) 500 MCM	-	#3 AWG	3"	3-1/2"	1			
400/3	(3) 3/0 AWG	-	#3 AWG	2"	2-1/2"	2			
450/3	(3) 4/0 AWG	-	#2 AWG	2-1/2"	2-1/2"	2			
500/3	(3) 250 MCM	-	#2 AWG	2-1/2"	3"	2			
600/3	(3) 350 MCM	-	#1 AWG	3"	3"	2			

COPPER CONDUCTOR AND CONDUIT SIZING CHART


	COND	JCTORS (THW	CONE	UIT	PARALLEL			
	PHASE	NEUTRAL	GROUND	EMT	SCH 80	RUNS		
15/4	(3) #12 AWG	#12 AWG	#12 AWG	1/2"	3/4"	1		
20/4	(3) #12 AWG	#12 AWG	#12 AWG	1/2"	3/4"	1		
25/4	(3) #10 AWG	#10 AWG	#10 AWG	1/2"	3/4"	1		
30/4	(3) #10 AWG	#10 AWG	#10 AWG	1/2"	3/4"	1		
35/4	(3) #8 AWG	#8 AWG	#10 AWG	3/4"	1"	1		
40/4	(3) #8 AWG	#8 AWG	#10 AWG	3/4"	1"	1		
45/4	(3) #6 AWG	#6 AWG	#10 AWG	1"	1"	1		
50/4	(3) #6 AWG	#6 AWG	#10 AWG	1"	1"	1		
60/4	(3) #4 AWG	#4 AWG	#10 AWG	1-1/4"	1-1/4"	1		
70/4	(3) #4 AWG	#4 AWG	#8 AWG	1-1/4"	1-1/4"	1		
80/4	(3) #3 AWG	#3 AWG	#8 AWG	1-1/4"	1-1/4"	1		
90/4	(3) #2 AWG	#2 AWG	#8 AWG	1-1/4"	1-1/4"	1		
100/4	(3) #2 AWG	#2 AWG	#8 AWG	1-1/4"	1-1/4"	1		
110/4	(3) #2 AWG	#2 AWG	#6 AWG	1-1/4"	1-1/2"	1		
125/4	(3) #1 AWG	#1 AWG	#6 AWG	1-1/2"	2"	1		
150/4	(3) 1/0 AWG	1/0 AWG	#6 AWG	2"	2"	1		
175/4	(3) 2/0 AWG	2/0 AWG	#6 AWG	2"	2"	1		
200/4	(3) 3/0 AWG	3/0 AWG	#6 AWG	2"	2-1/2"	1		
225/4	(3) 4/0 AWG	4/0 AWG	#4 AWG	2-1/2"	2-1/2"	1		
250/4	(3) 250 MCM	250 MCM	#4 AWG	2-1/2"	3"	1		
300/4	(3) 350 MCM	350 MCM	#4 AWG	3"	3"	1		
350/4	(3) 500 MCM	500 MCM	#3 AWG	3"	3-1/2"	1		
400/4	(3) 3/0 AWG	3/0 AWG	#3 AWG	2"	2-1/2"	2		
450/4	(3) 4/0 AWG	4/0 AWG	#2 AWG	2-1/2"	2-1/2"	2		
500/4	(3) 250 MCM	250 MCM	#2 AWG	2-1/2"	3"	2		
600/4	(3) 350 MCM	350 MCM	#1 AWG	3"	3"	2		

FIXTURE WHIP FROM JUNCTION BOX (1,829mm (6') LONG MAX) HANGER WIRE & MOUNTING CHANNEL CEILING HANGER ATTACHED TO STRUCTURE REFER TO SPECIFICATION SECTION 26 51 00 LIPPED STEEL MOUNTING CEILING CROSS TEE, TYP. WIRE TIE THROUGH_ MOUNTING CHANNEL & CROSS BEAM, WIRE TIE THROUGH_ MOUNTING CHANNEL & CROSS BEAM, LOCKING SQUARE -WASHER & NUT JUNCTION CEILING_ MAIN BEAM 6.35mm (1/4") — SCREW GYPSUM BOARD


1. INSTALL IN ACCORDANCE WITH MANUFACTURER'S MOUNTING INSTRUCTIONS AND USING THE RECOMMENDED MOUNTING HARDWARE.

EXIT SIGN MOUNTING DETAIL - GYPBOARD CEILING

CEILING CROSS



NONE-LINE DIAGRAM - MOBILE SPD TRAILER



1. INTEGRAL GALVANIZED LIPPED STEEL MOUNTING CHANNEL LONGER THAN 915mm (36") SHALL BE INSTALLED WITH A CENTER SUPPORT ROD. SUPPORT RODS SHALL NOT BE GREATER THAN 457mm (18") APART.

- 2. FASTEN THREADED ROD TO STRUCTURE BY APPROVED METHOD PER SPECIFICATION 26 05 33, RACEWAY AND BOXES FOR ELECTRICAL SYSTEMS. FIELD VERIFY EXACT
- 3. FOR TRAPEZE INSTALLATIONS IN SEISMIC AREAS REFER TO SPECIFICATION SECTION 13 05 41, SEISMIC RESTRAINT REQUIREMENTS FOR NON-STRUCTURAL COMPONENTS.
- CONDUIT TRAPEZE MOUNTING DETAIL

ELECTRICAL RISER GENERAL **NOTES**

1. REFER TO [SITE PLAN CXXX AND] ELECTRICAL PLAN [EXXX] FOR ADDITIONAL REQUIREMENTS AND RESPONSIBILITIES.

2. ELECTRICAL POWER OUTAGES, IF REQUIRED, SHOULD BE STRATEGICALLY MINIMIZED AND SCHEDULED CLOSELY WITH OWNER. CHANGEOVERS COULD BE

REQUIRED TO OCCUR AT ANY HOUR. 3. MAINTAIN ALL SERVICE CLEARANCES REQUIRED BY THE NEC.

4. INSTALL ALL CONDUCTORS AS PER MANUFACTURER'S RECOMMENDATIONS. 5. ELECTRICAL CONTRACTOR SHALL PROVIDE CONDUCTOR LENGTHS AND BREAKERS

MANUFACTURER INFORMATION TO THE DESIGN TEAM FOR SELECTIVE COORDINATION PER NEC 700.28. NECESSARY DEVICES SHALL HAVE THE ABILITY TO BE SELECTIVELY COORDINATED.

RESPONSIBLE FOR FITTING SYSTEM PROVIDED INTO SPACE SHOWN ON PLANS.


6. ELECTRICAL SERVICE LAYOUT MAY VARY FROM WHAT IS SHOWN ON PLANS BASED ON MANUFACTURER PROVIDING THE SYSTEM. ELECTRICAL CONTRACTOR IS

ELECTRICAL RISER KEYED NOTES


- 〈ER1〉 REFER TO PANEL SCHEDULE FOR ADDITIONAL DETAILS.
- PROVIDE TEMPORARY 500KVA PAD-MOUNTED TRANSFORMER WITH 23.9KV PRIMARY AND 480V SECONDARY. TRANSFORMER SHALL HAVE PRIMARY 〈ER2〉 SURGE ARRESTORS. PROVIDE RENTAL FOR DURATION OF CONSTRUCTION. COORDINATE ORDERING WITH GENERAL CONTRACTOR AND ARRIVAL OF MOBILE SPD TRAILER.
- NOTE: NOT ALL KEYED NOTES MAY BE USED ON EACH PLAN


BID DOCUMENT SUBMISSION


Drawing Title Project Title Project Number CONSULTANT DESIGNER OF RECORD STAMP Office of 437-CSI-241 ONE-LINE DIAGRAM & ELECTRICAL PERFORM SITE PREP BID DOCUMENTS Construction **Building Number** DETAILS FOR SPS EQUIPMENT ANDERSON I hereby certify that this plan, specification, or report was prepared by me or under my direct and Facilities supervision and that I am a duly Licensed Drawing Number Professional Engineer under the laws of the Management State of Minnesota **2882 106TH STREET** FARGO, ND DES MOINES IA 50322 13605 1st Ave. N. #100 Plymouth, MN 55441 Print Name: Andrew T. Weber FULLY SPRINKLERED Checked Issue Date Drawn P 763.412.4000 | F 763.412.4090 | ae-mn.com E-501 **VA** U.S. Department of Veterans Affairs Signature: ____Audrew 7. Weber Anderson Engineering of Minnesota, LLC | Proj # 17639 Date 01/22/2025 License # 6271 01/22/2025 || ATW || JPC Date: Revisions: VA FORM 08 - 6231





T-SPD-PANEL NORMAL BRANCH MAINS TYPE: MLO MOUNTING: Surface MAINS TYPE: MCB MOUNTING: Surface **ENCLOSURE**: Type 1 VOLTS: 120/208 Wye MAINS RATING: 225 A **ENCLOSURE**: Type 1 MAINS RATING: 100 A MCB RATING 100 A FED FROM: @ MCB RATING NONE FED FROM: @ T-SPD-XFMR-30 LOCATION: SPD NONE SPD INTERNAL LOCATION: SCCR: 10,000 A SCCR: 10,000 A AVAILABLE Isc: AVAILABLE Isc: **NOTES:** EXISTING SQUARE D TYPE NQ PANELBOARD. LOAD DESCRIPTION LOAD DESCRIPTION 1 DACU-18A E 30 A 2 0 0 2 30 A E DACU-19B 100 A 2 8000 0 2 40 A TEMP AHU 1 STERIS HEATER PANEL 3 --0 0 8000 2700 5 DACU-19A E 30 A 2 0 0 2 30 A E DACU-17 5 TEMP ENCLOSURE LIGHTING 20 A 1 -- -- 0 0 20 A 2 250 540 9 RECEPTS BB-34 E 20 A 0 0 2 30 A E DACU-18B 250 250 20 A **HEAT TRACING** 250 250 11 SPARE E 20 A 1 11 HEAT TRACING 20 A 2 0 0 -- - -- --13 SPARE E 30 A 3 0 0 3 15 A E SPARE -- 250 1500 **AUTO OPERATORS HEAT TRACING** 20 A 2 250 19 SPARE E 20 A 3 0 0 3 | 15 A | E | SPARE 21 0 0 25 SPARE 3 70 A E SPARE E 30 A 3 0 0 0 0 29 --0 0 -- - -E 30 A 3 0 0 **Total Load:** 10540.00 VA 11450.00 VA 1283.33 VA 107.28 Total Amps: 99.70 0 0 E 30 A 3 0 0 3 | 15 A | E | SPARE LOAD CLASSIFICATION DEMAND FACTOR **ESTIMATED DEMAND** 100.00% 22.2 kVA 100.00% 22.2 kVA 0 0 -- - --0.54 kVA 100.00% TOTAL ESTIMATED DEMAND LOAD: 0.00 VA 0.00 VA TOTAL CONNECTED AMPS: 0.00 TOTAL ESTIMATED DEMAND AMPS: 64.6 A *TOTAL DEMAND CALCS SUBTRACT ANY REDUNDANT LOAD AND THE SMALLER OF ANY NONCOINCIDENT HVAC LOADS. THIS CALC IS DONE AT EACH PANEL. CIRCUIT KEY NOTES: A = ARC FAULT E=EXISTING G=GFI H=HANDLE LOCK ST=SHUNT TRIP CONNECTED LOAD DEMAND FACTOR ESTIMATED DEMAND LOAD CLASSIFICATION TOTALS* TOTAL ESTIMATED DEMAND LOAD: TOTAL CONNECTED AMPS: TOTAL ESTIMATED DEMAND AMPS: *TOTAL DEMAND CALCS SUBTRACT ANY REDUNDANT LOAD AND THE SMALLER OF ANY NONCOINCIDENT HVAC LOADS. THIS CALC IS DONE AT EACH PANEL. **CIRCUIT KEY NOTES:** A = ARC FAULT E=EXISTING G=GFI H=HANDLE LOCK ST=SHUNT TRIP LIGHTING FIXTURE SCHEDULE LAMP/CCT/CRI CONTROL DELIVERED WATTS VOLTS BOD TYPE MANUFACTURER **MODEL NUMBER DESCRIPTION** LITHONIA EDGR-1-RMR-BAA LED EDGE-LIT EXIT SIGN. SINGLE FACE. RED LETTERS ON MIRROR BACKGROUND. PROVIDE DIRECTIONAL CHEVRONS AS INDICATED ON PLAN. BAA COMPLAINT. 4.5 UNV DUAL-LITE, CHLORIDE LITHONIA LHQM-LED-R-HO-BAA LED COMBO EXIT SIGN/EXIT LIGHTS. WHITE THERMOPLASTIC BODY. RED LETTERS. HIGH OUTPUT LEDS WITH NICAD BATTERY. PROVIDE CHEVRONS AS INDICATED ON PLANS. BAA COMPLIANT. 4.3 | 120/277 | DUAL-LITE,CHLORIDE KENALL ES8-48-1-67L40K-DCC-DV-2H-PP-IP65 4' LED SURFACE MOUNTED WRAPAROUND WITH GASKETED LENS. IP65 RATED. UV-STABALIZED, PEARLESCENT POLYCARBONATE LENS. LED/4000K/82 0-10V, 1% 7,860 73 | 120-277 | ENGINEER APPROVED LITHONIA CLX48-4000LM-SEF-FDL-WD-MVOLT-GZ10-40K-80CRI-WH-BAA 4' LED STRIP FIXTURE. FLAT DIFFUSE LENS. PROVDE ACCESSORIES REQUIRED FOR SUSPENDED INSTALLATION. BAA COMPLIANT. LED/4000K/80 4,000 | 35 | UNV | METALUX CPX-2X4-4000LM-80CRI-40K-SWL-MIN10-MVOLT-BAA 4,818 32 UNV COLUMBIA, METALUX LITHONIA 2' X 4' LED BACK-LIT FLAT PANEL WITH SATIN WHITE LENS. BAA COMPLAINT. LED/4000K/80 0-10V BID DOCUMENT SUBMISSION Project Number Drawing Title Project Title CONSULTANT DESIGNER OF RECORD STAMP Office of 437-CSI-241 ELECTRICAL SCHEDULES PERFORM SITE PREP **BID DOCUMENTS** Construction **Building Number** FOR SPS EQUIPMENT ANDERSON I hereby certify that this plan, specification, or report was prepared by me or under my direct and Facilities supervision and that I am a duly Licensed Drawing Number Management Professional Engineer under the laws of the State of Minnesota **2882 106TH STREET** FARGO, ND DES MOINES IA 50322 Print Name: Andrew T. Weber 13605 1st Ave. N. #100 Plymouth, MN 55441 FULLY SPRINKLERED Issue Date Checked Drawn P 763.412.4000 | F 763.412.4090 | ae-mn.com E-602 **VA** U.S. Department of Veterans Affairs Signature: _____Audrew 7. Weber Anderson Engineering of Minnesota, LLC | Proj # 17639 Date 01/22/2025 License # 6271 || ATW || JPC 01/22/2025 Date: Revisions: VA FORM 08 - 6231






















TYPICAL TELECOM ROOM CONNECTIVITY DIAGRAM NO SCALE

- 1. THIS RISER IS DIAGRAMMATIC AND MAY NOT SHOW ACTUAL ROUTING OR QUANTITIES OF MATERIALS SHOWN. THIS RISER IS SHOWN FOR CLARIFICATION OF CONNECTION(S), LOCATIONS AND CABLE TYPE. ALL INFORMATION OUTLETS ARE TYPICAL OF THE OUTLETS IN THE AREA
- SHOWN. REFER TO FLOOR PLANS FOR MORE SPECIFIC ROUTING INFORMATION. REFER TO SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS. 2. REFER TO FLOOR PLANS FOR QUANTITY OF CABLES AND JACKS TO BE INSTALLED AT EACH

INFORMATION OUTLET. KEYNOTES: #

- 1. C# INDICATES VOICE/DATA FACEPLATE CONFIGURATION. REFER TO THE INFORMATION OUTLET SCHEDULE AND SPECIFICATION SECTION 27 15 13 FOR ADDITIONAL INFORMATION.
- 2. ALL EQUIPMENT EXISTING TO REMAIN RACK(S) OR CABINET(S). 3. REFER TO SPECIFICATIONS FOR FIBER PATCH CORD REQUIREMENTS.
- 4. RJ-45 TO RJ45 CATEGORY 6A UTP PATCH CORDS, REFER TO SPECIFIATIONS. 5. 4-PAIR, CATEGORY 6A UNSHIELDED TWISTED PAIR CABLE, REFER TO SPECIFICATIONS.




3 TELECOM ROOM ELEVATION TR-03

BID DOCUMENT SUBMISSION

CONSULTANT 2882 106TH STREET **DES MOINES IA 50322**

DESIGNER OF RECORD ANDERSON 13605 1st Ave. N. #100 Plymouth, MN 55441 P 763.412.4000 | F 763.412.4090 | ae-mn.com Anderson Engineering of Minnesota, LLC | Proj # 17639




Office of Construction and Facilities Management

VA U.S. Department of Veterans Affairs

					COIVILIA	
	Drawing Title	Phase	Project Title			Project Number
	TECHNOLOGY ENLARGEMENT	BID DOCUMENTS	PERFORM	SITE PR	EP	437-CSI-241
	PLANS	DID DOGGINETTO	FOR SPS E	QUIPME	ENT	Building Number 9
	Approved:		Location FARGO, ND			Drawing Number
		FULLY SPRINKLERED	Issue Date	Checked	Drawn	T200
ent		. OLL: OF MINICELIALS	1/15/2025		MATSTU	T200

Revisions:

VA FORM 08 - 6231



ELECTRONIC DOOR HAR REFER TO THE TECHNOI	CREDENTIAL READER							EDEN	TRIC I	LATCH	RETF R TYP	RACTI	ON, E	TC. SI	RE		OTHERS) IS	D ANI	DOR	ALLED	O BY C	THER	S.				(F	OTH REFE NOT	IER ER TO		
DOOR # VESTIBULE T-01A	CREDENTIAL READER TYPE		V L L	OPERATES MULTIPLE DOORS	AUTOMATIC DOOR OPERATOR	ELEVATOR	LOCKED BY EMERGENCY DURESS SEQUENCE	INFANT PROTECTION	REMOTE UNLOCK VIA INTERCOM MASTER	REMOTE UNLOCK VIA PUSHBUTTON			VIDEO SURVEILLANCE	WANDER PREVENTION SYSTEM	MOTION DETECTOR	LOCAL PUSHBUTTON DOOR HARDWARE OVERRIDE	INTERNAL ELECTRIFIED HARDWARE CONNECTION (BY	ELECTRONIC LOCKING HARDWARE (BY OTHERS)	MAG LOCK	LATCH STATUS DETECTION (BY OTHERS)	LOCAL ALARM HORN	MONITOR LATCH BOLT (BY OTHERS)	MONITOR DOOR POSITION SWITCH SPDT	MONITOR DOOR POSITION SWITCH DPDT	MONITOR DOOR POSITION SWITCH - OVERHEAD DOC	MONITOR DOOR POSITION SWITCH - ROOF HATCH	DELAYED EGRESS (BY OTHERS)	LOCAL 120VAC POWER SUPPLY	SCHEDULE BASED LOCKING	VISUAL STROBE/AUDIBLE ALARM	NOTES

TECHNOLOGY EQUIPMENT SCHEDULE

THE EQUIPMENT LIST ABBREVIATIONS AND THE TECHNOLOGY EQUIPMENT SCHEDULE ARE FOR THE CONVENIENCE OF THE CONTRACTOR. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFICATION OF QUANTITIES AND SHALL FURNISH ALL MATERIAL REQUIRED, WHETHER SPECIFIED OR NOT, TO PRODUCE A SATISFACTORY WORKING SYSTEM.

CATALOG NUMBERS ARE NOT TO BE CONSIDERED COMPLETE BUT ARE GIVEN ONLY TO AID THE CONTRACTOR IN THE SEARCH FOR MATERIAL. NO MATERIAL SHALL BE ORDERED BY MANUFACTURER AND CATALOG NUMBER ONLY. EACH CONTRACTOR SHALL FIRST READ THE COMPLETE DESCRIPTION OF THE MATERIAL ON THESE DRAWINGS AND SPECIFICATIONS. THE FIRST MANUFACTURER LISTED IS THE BASIS OF DESIGN. "STANDARD COLOR" INDICATES FACTORY FINISH AVAILABLE AT NO ADDITIONAL CHARGE.

EQUIPMENT LIST ABBREVIATION	EQUIPMENT LIST DESCRIPTION	MANUFACTURER AND MODEL
AC-CR1-W	ACCESS CONTROL AUTHORIZATION DEVICE, CARD READER KEY PAD. PIV ENABLE TWO-FACTOR AUTHENTICATION KEYPAD	HID
		SIGNO40T SERIES
		MATCH EXISTING IN BUILDING
PA-S1-C	PAGING SPEAKER, CEILING. 8" CEILING MOUNTED COAXIAL SPEAKER WITH 100Z MAGNET. 120° CONICAL COVERAGE. 15 WATT CONTINUOUS PROGRAM POWER, SENSITIVITY: 95DB AVG. SPL @ 1M, 47HZ-20KHZ ±6DB FREQUENCY RESPONSE, TAPS @ 5W, 2W, 1W, 0.5W & 0.25W @ 70.7V, LOW 0.5DB INSERTION LOSS. PROVIDE WITH BACKBOX, GRILL AND TILE BRIDGE WHERE REQUIRED.	LOWELL SPEAKER 810-T72 BACKBOX 8XD4 GRILL A8-AW T-BRIDGE LBS8-CP
		ATLAS SOUND QUAM
SC-CT-1	CABLE TRAY, WIRE MESH TYPE, 4" LOADING DEPTH, 18" WIDTH, COMPLETE WITH ALL FITTINGS AND MOUNTING HARDWARE. PROVIDE TRAPEZE SUPPORT WITH PLASTIC RETAINER. CUTTING OF THE MESH CABLE TRAY SHALL BE DONE WITH OFFSET BOLT CUTTERS ONLY. 10' MAXIMUM SUPPORT SPAN. EITHER SPLICE WASHERS OR TERMINAL GROUND SUPPORT AND JUMPER WIRE SHALL BE USED TO ATTAIN GROUNDING CONTINUITY THROUGHOUT. Z-BRACKETS SHALL BE USED FOR WALL MOUNTED APPLICATIONS. REFER TO MANUFACTURERS INSTALLATION INSTRUCTIONS AND SPECIFICATION SECTION 27 05 36 FOR ADDITIONAL INFORMATION. PROVIDE CABLE PATHWAY SEPARATOR AT 5' INTERVALS TO PROVIDE SEPARATE PATHWAYS FOR VOICE/DATA AND NURSE CALL VS. SECURITY AND PAGING.	LEGRAND CABLOFIL CF105/450 EZ OR PRE-APPROVED EQUAL
SC-IO-C	INFORMATION OUTLET, CEILING MOUNT. 2-PORT SURFACE MOUNT BOX AS INDICATED ON DRAWINGS. "#"INDICATES INFORMATION OUTLET FACEPLATE CONFIGURATION AS INDICATED ON THE PLANS. REFER TO T500 FOR INFORMATION OUTLET SCHEDULE FOR PIN CONFIGURATION.	COVERPLATE: ORTRONICS OR-40300549 (1-PORT) OR-40300548 (2-PORT)
	FOR 1#-WAP LOCATIONS, CONTRACTOR TO PROVIDE 1-PORT SURFACE MOUNT BOX (ORTRONICS OR-404TJ2) WITH (1) 3' PATCH CABLE, SEE SPECIFICATIONS.	JACK: ORTRONICS CAT6A OR-TJ6A00OR
		PRE-APPROVED EQUAL
SC-IO-W	INFORMATION OUTLET, WALL MOUNT. 2 OR 4 PORT COVERPLATE AS INDICATED ON DRAWINGS." # "INDICATES INFORMATION OUTLET FACEPLATE CONFIGURATION AS INDICATED ON THE PLANS. REFER TO T500 FOR INFORMATION OUTLET SCHEDULE FOR PIN CONFIGURATION.INSTALL INFORMATION OUTLET IN A 4' SQUARE BACKBOX WITH A SINGLE GANG PLASTER RING. INSTALL A 1" EMT CONDUIT TO NEAREST ACCESSIBLE CEILING. REFER TO SPECIFICATION SECTION 27 05 33 FOR ADDITIONAL INFORMATION.	,
		JACK: ORTRONICS CAT6A OR-TJ6A00OR
		PRE-APPROVED EQUAL
SC-WP-W	INFORMATION OUTLET, WALL PHONE. PROVIDE (1) RJ-45 JACK FOR VOICE AT +48" AFF FOR WALL HUNG PHONE. PROVIDE WITH STAINLESS STEEL FACEPLATE, MATING LUGS.	COVERPLATE: ORTRONICS OR-403STJ1WP
	INSTALL INFORMATION OUTLET IN A 4" SQUARE BACKBOX WITH A SINGLE GANG PLASTER RING. INSTALL A 1" EMT CONDUIT TO NEAREST ACCESSIBLE CEILING.	JACK: ORTRONICS CAT6A OR-TJ6A00OR
		PRE-APPROVED EQUAL

BID DOCUMENT SUBMISSION Project Number Drawing Title Project Title 437-CSI-241 TECHNOLOGY SCHEDULES PERFORM SITE PREP **BID DOCUMENTS** Building Number FOR SPS EQUIPMENT Drawing Number Location FARGO, ND FULLY SPRINKLERED Issue Date | Checked | Drawn T500 1/15/2025 MARWIT MATSTU

CONSULTANT

\$\ightarrow\$IMEG

2882 106TH STREET
DES MOINES IA 50322

Revisions:

Date:

VA FORM 08 - 6231

DESIGNER OF RECORD

ANDERSON

13605 1st Ave. N. #100 Plymouth, MN 55441
P 763.412.4000 | F 763.412.4090 | ae-mn.com
Anderson Engineering of Minnesota, LLC | Proj # 17639

STAMP

KRISTEN

SPINA

MO1081

MO1081

MO1081

Office of
Construction
and Facilities
Management

U.S. Departme

VA U.S. Department of Veterans Affairs